

Real-Time Driver Drowsiness Detection and Alert Module Using Arduino

Sujan Banerjee^{1*}, Saikat Barman², Koushik Mandal³, Srijan Kr. Dey⁴

Abstract

Driver fatigue is one of the leading reasons behind road accidents because it reduces driver attention, slows reaction time, and affects decision-making ability while driving. To address this issue, a real-time fatigue detection and alert system has been developed using Arduino-based embedded technology. The proposed framework continuously monitors the driver's eye activity with the help of an infrared eye blink sensor, which detects eyelid movement and eye closure patterns during driving conditions. The sensor data collected from the driver is processed by an Arduino Nano microcontroller, where the eye closure duration is compared with a predefined threshold value. If the system identifies an abnormal or prolonged eye closure that indicates fatigue or drowsiness, it immediately activates warning mechanisms such as a buzzer alarm and vibration alert to awaken the driver and prevent possible accidents. Experimental analysis shows that the developed system effectively distinguishes normal blinking from fatigue-related eye closure with reliable accuracy. The compact design, low implementation cost, and stable performance make the system suitable for practical vehicle safety applications. In addition, the framework can be further enhanced in the future by integrating intelligent processing methods and advanced monitoring algorithms to improve precision detection and overall driving safety.

Keywords: Arduino nano, driver drowsiness detection, eye blink sensor, embedded system, alert mechanism

INTRODUCTION

Driver fatigue is one of the primary reasons for road accidents across the world. Reduced alertness caused by drowsiness affects concentration, slows reaction speed, and weakens decision-making capability during vehicle operation. Long-distance driving, insufficient rest, and continuous exposure to stressful traffic conditions often increase the possibility of fatigue-related incidents.

Several monitoring techniques have been developed to identify driver drowsiness, including image-processing methods, physiological signal monitoring, and sensor-based embedded systems. Although these approaches provide effective detection performance, many require costly hardware components and involve complex implementation processes.

*Author for Correspondence

Sujan Banerjee
E-mail: hisujan96@gmail.com

¹⁻⁴Student, Department of Electrical Engineering, Swami Vivekananda School of Diploma, West Bengal State Council of Technical & Vocational Education and Skill Development, West Bengal, India

Received Date: April 03, 2026
Accepted Date: July 06, 2026
Published Date: September 05, 2026

Citation: Sujan Banerjee, Saikat Barman, Koushik Mandal, Srijan Kr. Dey. Real-Time Driver Drowsiness Detection and Alert Module Using Arduino. Research & Reviews: Journal of Embedded System & Applications. 2026; 14(2): 34–42p.

An embedded monitoring arrangement using an infrared eye blink sensor and Arduino Nano controller was utilized in this study to continuously observe eyelid activity. The controller evaluates eye closure duration and compares it with a predefined threshold to determine fatigue conditions. When an abnormal closure duration is detected, warning signals are generated instantly to regain the driver's attention.

The developed system offers a compact design, low implementation cost, operational reliability,

and easy deployment, making it suitable for practical vehicle safety applications. Future enhancements may include intelligent processing algorithms to further improve monitoring accuracy and system adaptability.

OBJECTIVES

The main objectives of the proposed system are as follows:

1. To design a real-time driver drowsiness detection module using Arduino
2. To monitor eye blinking patterns using an eye blink sensor
3. To identify prolonged eye closure as an indicator of drowsiness
4. To develop an effective alert mechanism using a buzzer and motor
5. To create a low-cost and portable system for practical applications
6. To improve safety by reducing the risk of accidents caused by driver drowsiness.

LITERATURE REVIEW

Driver drowsiness detection has received considerable attention owing to its importance in minimizing fatigue-related road accidents. Various techniques have been introduced to monitor driver alertness and provide immediate warning responses when fatigue conditions are detected.

Earlier studies developed integrated fatigue monitoring frameworks combining eye blink sensing with remote communication systems to improve safety response capability [1]. Hybrid approaches incorporating physiological signal monitoring together with infrared-based sensing demonstrated improved reliability under different operational environments [2]. Real-time monitoring systems supported by heartbeat analysis and GSM communication enabled rapid emergency notification and enhanced rider protection [3]. Image-processing-based methods further improved fatigue recognition by evaluating facial expressions, eye movement characteristics, and pressure-sensitive sensor responses [4]. Embedded implementations based on Arduino platforms demonstrated efficient real-time operation while maintaining low hardware complexity and affordability [5]. Compact sensor-integrated systems have shown practical suitability for large-scale implementation owing to their cost-effectiveness and simplified deployment [6]. Advanced fatigue monitoring approaches using EEG, ECG, and EMG signal processing improved prediction performance through simultaneous evaluation of multiple physiological indicators [7]. Microcontroller-driven warning systems also achieved reliable alert generation for immediate driver notification during fatigue conditions [8]. Comprehensive multi-sensor monitoring frameworks demonstrated improved classification accuracy and operational consistency under real driving conditions [9]. Recent developments in machine-learning-assisted image analysis significantly enhanced detection precision by evaluating yawning frequency, eyelid closure duration, and head-position variations in real time [10].

These findings indicate that embedded sensor-based fatigue monitoring systems provide an effective balance between detection accuracy, implementation simplicity, affordability, and practical deployment capability for vehicle safety applications.

COMPONENT DETAILS

The hardware components used in the proposed driver drowsiness detection system are presented in Figures 1–8.

Arduino Nano

The Arduino Nano, as shown in Figure 1, serves as the central processing unit of the system. Built around the ATmega328P microcontroller, it processes the sensor input signals and performs programmed decision-making operations. Its compact structure and low power requirement make it highly suitable for embedded applications.

Eye Blink Sensor

The infrared eye blink sensor illustrated in Figure 2 continuously monitors eyelid movement by detecting reflected infrared intensity. Variations in the reflected signals help determine whether the eye remains open or closed for an abnormal duration.

Piezo Buzzer

The piezo buzzer shown in Figure 3 produces an audible warning signal whenever fatigue conditions are detected. This mechanism is designed to attract the driver's attention immediately.

Relay Module

The relay module presented in Figure 4 functions as an electrically controlled switching device that activates external alert mechanisms when triggered by the controller.




Figure 1. Arduino Nano.



Figure 2. Eye blink sensor.



Figure 3. Piezo buzzer.



Figure 4. Relay module.

DC Gear Motor

The DC gear motor illustrated in Figure 5 converts electrical energy into controlled mechanical motion when activated by the controller. It operates as a physical alert mechanism to notify the driver immediately after fatigue detection. The gear arrangement ensures stable torque generation and reliable operation during warning activation.

SPST Switch

The SPST switch shown in Figure 6 enables manual control for activating and deactivating the system during operation.

Power Supply

The power supply arrangement illustrated in Figure 7 was designed to provide stable and efficient operation of the complete system. A 9 V battery was used to energize the Arduino Nano and other low-power components. In addition, rechargeable lithium-ion batteries based on 18650 cells, having a nominal voltage of 3.7 V and a capacity of 2200 mAh, were used to operate the relay module and DC gear motor, which require comparatively higher current. This separate power configuration improves reliability, maintains stable performance, and enhances portability for practical long-term use.



Figure 5. DC gear motor.



Figure 6. SPST switch.



Figure 7. Power supply.



Figure 8. Connecting (Jumper) wires.

Connecting (Jumper) Wires

The connecting wires shown in Figure 8 establish electrical pathways among all system components and ensure proper signal transmission.

METHODOLOGY

The proposed driver drowsiness detection system continuously monitors driver eye activity in real time and activates warning signals whenever fatigue conditions are detected. Sensor data are processed by the Arduino Nano controller, which evaluates eye closure duration and initiates the alert mechanism when necessary.

System Operation

The system starts functioning when electrical power is supplied to all connected components. The eye blink sensor continuously detects eyelid movement by emitting infrared light and receiving reflected signals. Based on the received signal intensity, the controller determines whether the eye is open or closed.

Signal Processing and Decision Making

The Arduino Nano processes incoming sensor signals and measures eye closure duration in real time. This measured value is compared with a predefined threshold to distinguish normal blinking from prolonged closure associated with driver fatigue.

Alert Generation

Whenever fatigue conditions are detected, the controller immediately activates the warning mechanism. The buzzer produces an audible alert, while the relay-controlled DC gear motor generates physical motion to strengthen driver notification.

Power Management

The system uses a dual power supply configuration to maintain stable operation. A 9 V battery powers the Arduino Nano and low-power components, whereas a separate rechargeable lithium-ion battery (18650 type) supplies power to the relay and motor.

Overall Workflow

The complete operating sequence is summarized below:

1. The eye blink sensor continuously monitors eyelid movement.
2. Sensor signals are transmitted to the Arduino Nano.
3. Eye closure duration is measured and analyzed.
4. The measured value is compared with the threshold level.
5. If fatigue is detected, warning mechanisms are activated.
6. Continuous monitoring is maintained during operation.

CIRCUIT DIAGRAM

The complete electrical arrangement of the developed monitoring system is presented in Figure 9. It illustrates the interfacing structure among the Arduino Nano, infrared eye blink sensor, relay unit, buzzer, DC gear motor, and dedicated power sources required for coordinated operation.

HARDWARE MODEL

The implemented prototype of the developed monitoring arrangement is shown in Figure 10. It demonstrates the practical integration of sensing, processing, and alert-generation units designed for continuous real-time fatigue detection.




Figure 9. Circuit diagram of the driver drowsiness detection system.




Figure 10. Practical hardware prototype of the system.

Table 1. Experimental response of the driver drowsiness monitoring module.

Condition	Eye closure duration	System response
Normal blinking	<1 second	No alert
Slight delay	1–2 seconds	No alert
Drowsiness condition	>2–3 seconds	Buzzer + Motor ON
Continuous eye closure	>3 seconds	Continuous alert

RESULTS AND DISCUSSION

The developed driver drowsiness detection system was experimentally evaluated under multiple operating conditions to verify its operational stability and detection accuracy during real-time eye monitoring.

Experimental Setup

The hardware prototype consisting of an Arduino Nano, eye blink sensor, buzzer, relay module, and DC gear motor was assembled, as shown in the implementation figure. The sensor was positioned near the eye using a wearable frame to ensure accurate detection. The system was powered using a dual supply configuration, including a 9 V battery for the control unit and a rechargeable 18650 lithium-ion battery for the motor and relay.

Observations

The system's behavior was observed under different eye conditions:

- During normal blinking, where eye closure lasted for a very short duration, the system did not trigger any alert, indicating proper discrimination between normal and abnormal conditions.
- When the eye was intentionally kept closed for a longer duration, the system successfully detected drowsiness and activated both the buzzer and motor.
- The response time of the system was found to be quick, with alerts generated almost immediately after exceeding the predefined threshold.
- The dual-alert mechanism (sound and motion) proved to be effective in drawing attention.

Sample Test Results

The experimental response of the driver drowsiness monitoring module under different eye closure conditions is presented in Table 1.

DISCUSSION

Experimental observations confirmed that the developed system effectively differentiated regular blinking activity from fatigue-related prolonged eye closure with satisfactory accuracy. The threshold-based detection method minimizes false triggering, whereas the combined audible and physical alert mechanism improves the overall reliability of practical real-time monitoring applications.

However, it was observed that external factors, such as ambient lighting and sensor positioning, can influence the performance of the eye blink sensor. Proper calibration and placement of the sensor are necessary to achieve optimal results. Despite these limitations, the system demonstrates effective operation and fulfills its intended purpose.

Advantages

The proposed driver drowsiness detection module offers several practical benefits:

- *Real-time monitoring:* The system continuously tracks eye activity and provides immediate alerts when drowsiness is detected.
- *Low-cost implementation:* Uses easily available and affordable components, making it economically feasible.
- *Simple design:* The hardware and programming are straightforward, allowing easy development and maintenance.

- *Compact and portable:* The use of Arduino Nano and battery supply makes the system lightweight and easy to carry.
- *Dual alert mechanism:* The combination of a buzzer and motor improves the effectiveness of warning signals.
- *Energy efficient:* Utilizes an optimized power supply with rechargeable batteries for longer operation.
- *Easy integration:* Can be integrated into vehicles or other safety systems with minimal modification.

Disadvantages

Although the system performs effectively, certain practical limitations remain that may influence the overall operational efficiency under varying conditions.

- *Sensor sensitivity:* Performance depends on proper positioning of the eye blink sensor.
- *Light interference:* External lighting conditions may affect sensor accuracy.
- *Limited detection parameters:* The system relies only on eye closure and does not consider other fatigue indicators.
- *Manual calibration required:* Threshold values may need adjustment for different users.
- *Wired setup:* Physical connections may reduce flexibility and long-term durability.
- *No data recording:* The system does not store or analyze past data for advanced insights.

CONCLUSION

The presented driver alert monitoring framework offers a practical and economical approach for improving road safety through continuous eye-state observation. By employing an infrared eye-monitoring sensor, the system identifies extended eyelid closure as an indication of fatigue and responds instantly through synchronized sound and motion-based warning actions.

Experimental evaluation confirms dependable differentiation between regular blinking behavior and fatigue-related eye closure with fast response characteristics. The combined warning arrangement increases operational dependability and improves user responsiveness during critical conditions. The separate power supply structure further supports stable controller performance throughout operation.

Although environmental factors and sensor alignment may influence detection precision, the developed arrangement performs effectively for real-time monitoring applications. Its compact structure, affordability, and ease of implementation make it suitable for practical deployment in intelligent vehicle safety systems.

Future Scope

The proposed system can be further enhanced by incorporating advanced technologies and additional features:

1. Integration of camera-based vision systems for more accurate detection.
2. Implementation of AI & machine learning algorithms to analyze multiple fatigue indicators.
3. Addition of GSM or IoT modules for sending alerts to remote users or authorities.
4. Development of a mobile application for real-time monitoring and notifications.
5. Integration with vehicle control systems to automatically reduce speed or stop the vehicle.
6. Use of multiple sensors (heart rate, head movement) for improved reliability.
7. Enhancement of system design to make it fully wireless and more compact.

REFERENCES

1. Hossan A, Kashem FB, Hasan MM, Naher S, Rahman MI. A smart system for driver's fatigue detection, remote notification and semi-automatic parking of vehicles to prevent road accidents. 2016 IEEE International Conference on Medical Engineering, Health Informatics and Technology (MediTec), Dhaka, Bangladesh. 2016. p.1-6. doi:10.1109/MEDITEC.2016.7835371.

2. Bhaskar A. EyeAwake: a cost effective drowsy driver alert and vehicle correction system. 2017 4th International Conference on Innovations in Information, Embedded and Communication Systems (ICIECS), Coimbatore, India. 2017. p.1-6. doi:10.1109/ICIECS.2017.8276114.
3. Sinha O, Singh S, Mitra A, Ghosh SK, Raha S. Development of a drowsy driver detection system based on EEG and IR-based eye blink detection analysis. In: Advances in Communication, Devices and Networking. Singapore: Springer; 2018. p.313-9. doi:10.1007/978-981-10-7901-6_34.
4. Hidayati Q, Fadhillah R. Real time monitoring for drowsiness and emergency detection on riders using XD-58C sensor. J Telemat Inform. 2019;7(2):111-7.
5. Satish K, Lalitesh A, Bhargavi K, Prem MS, Anjali T. Driver drowsiness detection. 2020 International Conference on Communication and Signal Processing (ICCSP), Chennai, India. 2020. p.380-4. doi:10.1109/ICCSP48568.2020.9182237.
6. Kondapaneni A, Hemanth C, Sangeetha RG, Vaishnavi Priyanka RSJ, Sanjay Saradhi M. A smart drowsiness detection system for accident prevention. Natl Acad Sci Lett. 2021;44(4):317-20. doi:10.1007/s40009-020-01000-3.
7. Kadam A, Gaikwad K, Jose J, Khairnar G, Deoghare SU. Drowsiness detection and alert system. 2022 6th International Conference on Computing, Communication, Control and Automation (ICCUBE). 2022. p.1-4.
8. Shilaskar S, Lokhande TJ, Mane GP, Masani PC, Kulkarni DN. Embedded system for driver drowsiness detection. In: Proceedings of the International Conference on Communication and Computational Technologies. Singapore: Springer; 2023. p.603-11. doi:10.1007/978-981-99-3485-0_48.
9. bin Muhammad 'Azmin MS, Sulthan SM, Al-Jumaily A. Real-time driver safety system based on detecting drowsiness and diagnosing fatigue. In: Wah YB, Al-Jumeily D, Berry MW, editors. Data Science and Emerging Technologies: Proceedings of DaSET 2024. Singapore: Springer Nature Singapore; 2026. p.551-68. doi:10.1007/978-981-96-7749-8_36.
10. Shalini L, Shravani HN, Tejashree NP, Poornima BV. Drivers drowsiness detection and alert system. In: Computer Vision and Robotics. Cham: Springer Nature Switzerland; 2026. p.326-39. doi:10.1007/978-3-032-14038-8_25.