STM JOURNALS

Journal of
Materials & Metallurgical Engineering

ISSN: 2231-3818 (Online)
ISSN: 2321-4236 (Print)
Volume 16, Issue 3, 2026
September–December
DOI (Journal): 10.37591/JoMME

https://journals.stmjournals.com/jomme

Review JoMME

Nanostructured Electrode Materials for Energy Storage

Ashita Garg[1], Aastha Sharma[1], Samjeet Singh Thakur[2,*]

Abstract

As the global transition toward renewable energy and electric mobility accelerates, the limitations of conventional "bulk" electrode materials have become a critical bottleneck. Traditional electrodes often suffer from slow ion diffusion kinetics, significant volume expansion during cycling, and restricted active surface area, ultimately resulting in low power density and limited cycle life. This study addresses these challenges through the design and fabrication of a novel hybrid nanostructured electrode material. The architecture utilizes a flexible carbon matrix characterized by high electrical conductivity and a large specific surface area, which serves as a robust framework for the incorporation of silver nanoparticles ranging from 10 to 40 nanometers in size. The primary objective of this research was to evaluate how this unique silver-carbon synergy influences electrochemical performance. By reducing the particle size to the nanoscale, the diffusion path lengths for ions are significantly decreased, allowing for more rapid charge-discharge cycles. Experimental results demonstrate that a supercapacitor utilizing this material with an aqueous electrolyte can achieve an impressive operating voltage of 2.6 V and a specific energy of 5.5 Wh/kg. This high voltage is particularly noteworthy for aqueous systems, which typically face lower decomposition limits. Ultimately, this work serves as a technical roadmap for enhancing energy storage density. Understanding the relationship between nanostructure morphology and electrochemical kinetics is vital for overcoming current performance plateaus and achieving a more efficient, electrified future.

Keywords: Nanostructure, Hybrid nanostructured electrode, silver nanoparticles, carbon matrix, supercapacitor, aqueous electrolyte, operating voltage, specific energy, and ion diffusion kinetics.

INTRODUCTION

The demand for high-performance energy storage is surging due to the rapid growth of electric vehicles and portable electronics. Traditional electrodes often struggle with limited capacity and stability, but nanostructured materials have emerged as a transformative solution. By engineering materials at the nanoscale, scientists can create electrodes with massive surface areas and tunable porosity, which significantly speeds up ion and electron transport. This leads to batteries and supercapacitors that charge faster, hold more power, and last longer through thousands of cycles [1-2].

***Author for Correspondence**
Samjeet Singh Thakur
E-mail: samjeet23chem@gmail.com

1MSC Student; Department of Chemistry, NSCBM Govt. College, Hamirpur Himachal, Pradesh (HP), India
2Assistant Professor, Department of Chemistry; NSCBM Govt. College, Hamirpur, Himachal Pradesh (HP), India

Received Date: August 22, 2026
Accepted Date: September 05, 2026
Published Date: October 29, 2026

Citation: Ashita Garg, Aastha Sharma, Samjeet Singh Thakur. Nanostructured Electrode Materials for Energy Storage. Journal of Materials & Metallurgical Engineering. 2026; 16(3): 67–96p.

A major shift is also occurring in how these devices are manufactured. Moving from old "thick-film" methods to thin-film technology can reduce internal resistance by orders of magnitude, which prevents the battery from overheating and improves overall safety. Furthermore, the development of a "*porous matrix*"—where a carbon or graphene structure is filled with active nanoparticles like Silicon (Si), Tin (Sn), or Antimony (Sb)—has proven to be a game-changer. For instance, a graphene-silicon composite can store up to 2000 mAh/g, doubling the capacity of standard graphene electrodes while maintaining better structural stability [3].

© STM Journals 2026. All Rights Reserved

Finally, increasing safety and lowering costs are top priorities. Switching from flammable organic electrolytes to aqueous (water-based) electrolytes makes batteries much safer to produce and operate. While water traditionally has a low "stability window" of 1.23V, new research aims to overcome this limit to achieve higher energy densities. By combining these advanced nanostructures with safer electrolyte materials, the next generation of energy storage will be more efficient, reliable, and sustainable [3-4].

Historical Background

The Evolution of Electrode Materials

Energy storage is shifting away from traditional bulk materials toward engineered nanostructures. This transformation is driven by the urgent need for batteries and supercapacitors that charge faster, hold more energy, and last longer, especially for electric vehicles and renewable energy grids [5-6].

Background and Rationale

Conventional bulk electrodes face major hurdles: they have poor ionic/electronic conductivity and often crack or break down under the physical stress of repeated charging and discharging. This limits the overall efficiency and lifespan of the device [7].

The Advantages of "Nanosizing"

Scaling materials down from micrometres to nanometres provides three transformative benefits:

a. **Faster Charging**: Reducing the size of particles shortens the distance ions must travel, allowing for rapid charge and discharge.
b. **Higher Capacity**: Nanostructures like nanowires and nanosheets have a massive surface area, providing more "active sites" for energy-storing reactions.
c. **Mechanical Stability**: Nanomaterials can better handle the volume expansion (swelling) that occurs during use, preventing structural failure [5-7].

Historical Milestones & Development

The landscape of energy storage has evolved rapidly through key discoveries:

a. **The 1990s:** The discovery of Carbon Nanotubes (CNTs) in 1991 and the later emergence of Graphene introduced high-conductivity, high-surface-area platforms.
b. **The 2000s:** In 2007, the introduction of Silicon Nanowires (SiNWs) as anodes proved that nanostructures could achieve much higher capacities than bulk silicon.
c. **2010 to Present:** Research now focuses on Hybrid Nanostructures, combining the high capacity of metal oxides with the superior conductivity of carbon (Graphene/CNTs).

Commercialization Prospects

While laboratory results are impressive, widespread commercial use is currently focused on practical additives, such as multi-walled CNTs and carbon coatings for silicon particles. The challenge remains in scaling these high-tech discoveries into cost-effective, mass-produced battery technologies [8].

Therefore, the transition to nanostructured electrodes is a leap toward more efficient and sustainable energy. By refining these materials, we are entering a new era of energy storage capable of meeting the rigorous demands of modern technology [9].

AIMs and OBJECTIVES

The main goal of investigation and creating nanostructured electrode materials for energy storage (batteries and supercapacitors) is to greatly improve energy density, power density, and cycle lifespan while enhancing safety[10]. Researchers seek to address the inherent limitations of traditional bulk materials, like slow ion transport and large volume changes, by manipulating material structure at the nanoscale (1-100 nm). The main goals of this study consist of:

© STM Journals 2026. All Rights Reserved

a. **Enhancing Surface Area and Active Sites:** Employing nanomaterials (such as nanowires, nanotubes, graphene, nanoparticles) and expands the electrode-electrolyte interface, creating additional active sites for electrochemical reactions, thereby boosting capacity [11].
b. **Enhancing Charge Transfer Kinetics:** Nano structuring minimizes the diffusion distance for ions and electrons, enabling quicker charging and discharging rates (elevated power density) [12].
c. **Improving Structural Integrity and Lifespan:** Nanostructured anodes (such as silicon) can effectively handle significant volume variations during cycling, avoiding fragmentation and prolonging the battery's life.
d. **Supressing Thermodynamic Constraints:** Creating novel materials that facilitate elevated operating voltages (for instance, >2.5V in aqueous electrolytes)
e. **Creating Sustainable and Affordable Materials:** Investigating substitutes for costly, rare materials to enhance accessibility and environmental friendliness of high-performance energy storage [13].
f. **Facilitating Lightweight and Flexible Gadgets:** Developing nanostructured electrodes suitable for wearable technology and sophisticated power management solutions.

CLASSIFICATION OF NANOSTRUCTURES

The secret of nanotechnology lies in ***"Dimensions"***. In the normal world, everything has three dimensions (length, width, height). In the nao-world, we *"shrink"* one or more of these dimensions to the size of atoms (1 to 100 nanometres).

In the context of energy storage, the ***"dimensionality"*** refers to the number of dimensions in which a material is not confined to the nanoscale. This classification is vital because as we decrease the size, the surface-to-volume ratio increases exponentially, and the electronic density of states changes, allowing for the faster redox kinetics[14-15].

Zero-Dimensional (0D): The "Dots"

All three spatial dimensions are shrunken into the nanoscale. For example: Quantum Dots, Nanospheres, Fullerenes (C_{60}).

Why Zero Dimensional?

a. **The "Surface Area" Rule**: Because they are so tiny, almost every atom is on the surface. In bulk materials, atoms are "*trapped*" inside, but 0D particles provide a massive concentration of active sites for ions to stick to.
b. **Role in Energy Storage:** They act as "*Fast-Reaction Sites*." Often used to "*decorate*" 2D or 3D structures to provide extra power (pseudo capacitance)[15-17].
c. **The Challenge**: They are "*lonely*" dots; electricity cannot flow easily between them because they don't touch well. They also tend to "*clump*" (aggregate) or undergo Ostwald Ripening (small particles merging into large ones), causing the battery to lose capacity over time.

One-Dimensional (1D): The "Highways"

Two dimensions are at the nanoscale, while one dimension remains long. For example: Nanowires, Nanotubes (CNTs), Nanofibers.

Why One Dimensional?

a. **The "Electron Highway":** Unlike 0D dots where electrons must "*hop*" between particles (creating resistance), 1D structures provide a direct, non-stop track for electrons to travel along the axis.
b. **Role in Energy Storage**: They act as Conductive Highways, moving electricity from the heart of the battery to the outside rapidly [17-18].
c. **Mechanical Integrity**: They act like "*Springs*." For materials like Silicon that swell during charging, 1D nanowires can bend and stretch without cracking or pulverizing.

© STM Journals 2026. All Rights Reserved

Two-Dimensional (2D): The "Sheets"

Only the thickness is at the nanoscale; the length and width are unconfined. For example: Graphene, MXenes, Nanosheets (MoS_2).

Why Two Dimensional?

a. **The "All-Surface" Material**: Every single atom in a 2D sheet is exposed to the electrolyte.
b. **Intercalation Concept:** Ions can slide between the sheets like credit cards in a wallet. In MXenes, this allows for ultra-fast "*sandwiching*" of ions, leading to power densities that rival traditional capacitors.
c. **The "Restacking" Problem**: Like wet pages in a book, these sheets like to stick together. If they restack into a solid block, ions can no longer get inside, which ruins the energy storage [18-20].

Three-Dimensional (3D): The "Sponges"

Hierarchical architectures composed of 0D, 1D, or 2D building blocks tangled together. For example: Nanoflowers, Aerogels, Nanofoams.

Why Three Dimensional?

a. **The "Sponge Effect"**: 3D structures solve the "*Dead Mass*" problem. In thick bulk electrodes, the liquid electrolyte cannot reach the centre. 3D structures have connected holes (porosity) that allow the electrolyte to soak through the entire material.
b. **Bimodal Porosity**: They use large holes (macropores) for fast liquid transport and tiny holes (mesopores) for high-capacity storage [21-22].
c. **Performance**: By maximizing the Electrode-Electrolyte Interface (EEI), 3D structures provide the high energy of a battery with the high power of a capacitor [23].

The *figure 1* shows that the classification of nanomaterials on the basis of dimensionality

SYNTHESIS AND FABRICATION STRATEGIRS OF NANOMATERIALS

Synthesis of Nanomaterials

Synthesis is the process of creating nanomaterials by controlling the arrangement of atoms and molecules [21-24]. Unlike traditional manufacturing, synthesis at the nanoscale requires precise control over **Nucleation** (the birth of the particle) and **Growth** (the expansion of the particle).

In energy storage, the goal of the synthesis is to create a material with high *Surface-to-Volume Ratio*. This ensures that maximum number of atoms are on the surface allowing the faster chemical reactions and higher energy storage capacity [24-25].

Classification of synthesis methods:

In this field of nanotechnology, synthesis strategies are fundamentally classified into two opposite philosophies based on the '*starting point'* of process: **Top-Down & Bottom-Up Approaches**

The Top-Down Approach: (Physical reduction): This approach starts with a large macroscopic "bulk" material and uses external force to break it down into nanoscale particles. It is similar to sculptor carving a statue from a large block of marble as shown in figure 2.

Mechanism: It relies primarily on physical and mechanical energy (crushing, grinding or blasting) to overcome the binding energy of the bulk material.

Key characteristics:

i. Produces large quantities of materials (Scalable).
ii. Particles often have irregular shape and a wide "size distribution" (some are big, some are small).
iii. Can introduce surface defects, which are sometimes useful for battery reactions.

© STM Journals 2026. All Rights Reserved




Figure 1. NMs classification based on Dimensionality [23].




Figure 2. Top-down and bottom-up approaches.

Primary methods:

I. **High-Energy Ball Milling:** High-Energy Ball Milling is a mechanical deformation process used to produce nanocrystalline powders. It is a "comminution" (size reduction) technique where coarse-grained bulk materials (like a piece of metal or graphite) are broken down into nanoparticles through severe cyclic deformation.

A) The working mechanism:

The process isn't just about breaking; it is a constant cycle of destruction and reconstruction.

a. **Loading the Vial:** You place the "Bulk" material and heavy milling balls (steel or ceramic) into a sealed container called a vial.

© STM Journals 2026. All Rights Reserved

b. **High-Energy Collision:** As the machine rotates, the balls fly across the vial. When a ball hits a particle against the wall or another ball, it delivers a massive amount of kinetic energy.

c. **The Three Stages of the Material:**

i. **Deformation (Flattening):** At first, the soft metal or carbon particles are flattened into tiny "pancakes" or flakes.

ii. **Cold Welding (Fusing):** Because the surfaces are fresh and clean, two flakes might actually stick together (weld) when hit.

iii. **Fracture (Breaking):** As the milling continues, the flakes become brittle and "work-hardened." Eventually, they can no longer bend, so they shatter into millions of tiny nano-sized pieces. (as shown in figure 3)

B. Key Parameters: How Scientists Control the "Chaos"

To get the perfect material for a battery, you have to tune these settings carefully:

a. **Ball-to-Powder Weight Ratio (BPR):**

i. If you have 10 grams of powder and 100 grams of balls, your BPR is 10:1.

ii. ***Why it matters:*** A higher ratio (like 20:1) means more collisions per second. This makes the particles smaller faster, but it also creates more heat and can cause more "contamination" from the balls.

b. **Rotational Speed (RPM):**

i. This is how fast the machine spins.

ii. ***Why it matters:*** Higher RPM increases the "Impact Energy." However, if it spins too fast, the balls might just stick to the walls due to centrifugal force and stop hitting the powder!

c. **Process Control Agents (PCA):**

i. These are "lubricants" like ethanol, hexane, or stearic acid.

ii. ***Why it matters:*** Without a PCA, the nano-powder might stick to the balls like gum, and the process stops. The PCA keeps the powder "dry" and flowing so it can keep being crushed.

d. **Milling Atmosphere:**

i. Replacing the air inside the vial with Argon or Nitrogen.

ii. ***Why it matters:*** Nano-powders have a huge surface area and are very "hungry" for oxygen. If you open a vial of nano-aluminium milled in air, it could explode or catch fire instantly (pyrophoricity).

C. The Role in Energy Storage: Why do we use it for Batteries?

a. **Creating "Active Sites":** The violent smashing creates Dislocations and Defects in the crystal lattice. Think of these as "doors" that allow Lithium ions to enter the material much faster than they could in a perfect crystal.

b. **Amorphization (Making it "Glass-like"):** HEBM can destroy the organized rows of atoms, turning them into a disordered (amorphous) state. In batteries (especially Silicon anodes), the material swells up when charging. A disordered structure can "stretch" better than a rigid crystal, preventing the electrode from cracking.

c. **Mechanical Alloying:** You can put two different materials (like Carbon and Silicon) in the mill, and the balls will "force" them to fuse together into a single Nanocomposite that you couldn't make by just mixing them as shown in table 1.

Table1. Advantages and Disadvantages of High Energy Ball Milling Method

Advantages	**Disadvantages**
Scalability: Can produce kilograms to tons of material.	**Contamination:** Small bits of the steel balls or vial can mix into the powder.
Cost-Effective: Simple machinery compared to CVD.	**Shape Control:** Hard to make "pretty" shapes; you mostly get irregular dust.
Solvent-Free: Often a "Green" dry process.	**Safety:** Nano-powders can catch fire if exposed to air too quickly.

© STM Journals 2026. All Rights Reserved




Figure 3. Process of High Energy Ball Milling.

II. **Laser Ablation method:** Laser Ablation is a sophisticated Top-Down synthesis strategy that uses concentrated photonic energy to transform bulk solids into high-purity nano colloids. While its low production yield makes it difficult for mass manufacturing, its ability to produce 'clean' and highly reactive surfaces makes it ideal for specialized, high-performance energy storage research. Laser Ablation uses optical energy (a laser beam) to blast a solid target into nanoparticles.

The Core Concept: Imagine a powerful laser pointer that can melt through metal. In this process, a solid slab of material (like Silver, Gold, or Silicon) is placed at the bottom of a container filled with a liquid (usually water or ethanol). A high-power pulsed laser hits the target, turning a tiny spot of solid into a super-heated plasma, which then cools down into nanoparticles.

A. The Step-by-Step Working Mechanism

a. **Laser Interaction:** A focused, high-energy laser pulse strikes the surface of the solid target immersed in a liquid.
b. **Plasma Formation:** The extreme heat instantly vaporizes the surface, creating a "Plasma plume" (a cloud of super-heated ions and electrons) at the interface between the solid and the liquid.
c. **Vapor Expansion & Shockwave:** The plasma expands rapidly against the liquid, creating a high-pressure shockwave.
d. **Nucleation & Quenching:** The cold liquid surrounding the hot plasma "quenches" (cools) the vapor almost instantly. This forces the atoms to stick together and form tiny, spherical nanoparticles that remain suspended in the liquid (creating a **colloid**). (as shown in figure 4)

B. Key Processing Parameters:

To control the size of the particles for your electrode, you must tune these variables:

a. **Laser Wavelength:** Usually, UV or Infrared lasers are used. Different materials absorb different colours of light more efficiently.
b. **Pulse Duration:** Most scientists use **Femtosecond** or **Nanosecond** pulses. Shorter pulses (femtosecond) prevent the target from getting too hot, leading to much smaller and more uniform nanoparticles.

© STM Journals 2026. All Rights Reserved

c. **Liquid Environment:** The liquid acts as a "stabilizer." For example, using a surfactant in the water can prevent the newly formed nanoparticles from sticking together (agglomeration).
d. **Ablation Time:** The longer the laser fires, the higher the concentration of nanoparticles in the liquid.

C. Role in Energy Storage (Why it's used for Batteries)

Laser ablation is a "clean" technology that offers unique benefits for electrode materials:

a. **Extreme Purity:** Since there are no milling balls or chemical precursors involved, the resulting nanoparticles are 99.9% pure. This is critical for battery life, as even tiny impurities can cause short circuits.
b. **Surface Functionalization:** The laser process creates "highly reactive" surfaces on the nanoparticles. When these are used in supercapacitors, they can hold more charge because the ions can bond more easily to the clean surface.
c. **Synthesis of Carbon Nanomaterials:** Laser ablation is one of the best ways to create **Single-Walled Carbon Nanotubes (SWCNTs)**. These are used as "conductive additives" in electrodes to help electrons travel faster.
d. **Alloying:** You can use a target made of two metals (like Tin and Antimony). The laser vaporizes both simultaneously, creating a perfectly mixed "nano-alloy" anode that can handle the expansion of a lithium-ion battery as shown in table 2.

Table 2. Advantages and Disadvantages of Laser Ablation Method

Advantages (The Good)	**Disadvantages (The Bad)**
Zero Contamination: No chemicals or physical tools touch the material.	High Cost: High-power pulsed lasers are very expensive compared to a ball mill.
Versatility: Can synthesize almost any material (metals, oxides, ceramics, carbons).	Low Yield: It produces milligrams of material, whereas ball milling produces kilograms.
"Green" Method: Can be done in pure water without toxic chemicals.	Complexity: Requires precise optical alignment and safety shielding for the laser.




Figure 4. Process of Laser Ablation Method

III. **Chemical Etching:** Chemical Etching is a precise Top-Down synthesis method that uses chemical reactivity to 'carve' nanostructures into bulk materials. It is uniquely essential for creating porous anodes and 2D materials like MXenes, which are critical for high-power, long-lasting energy storage devices. **Chemical Etching** is a vital process, especially for creating the "porous" structures needed for high-capacity battery anodes (like Silicon).

Chemical Etching (Top-Down Strategy): Chemical etching is a process where a solid material is submerged in a strong chemical solution (an **etchant**) that selectively dissolves parts of the material.

© STM Journals 2026. All Rights Reserved

Instead of crushing the material like ball milling, etching "eats away" at the surface to leave behind a nanoscale pattern or a highly porous network.

A. The Working Mechanism: How it Carves at the Nanoscale

- **a. Preparation:** A bulk material (like a silicon wafer or a metal sheet) is cleaned. Sometimes, a "mask" is placed on top to protect certain areas.
- **b. Chemical Reaction:** The material is exposed to an etchant (like Hydrofluoric Acid for silicon). The chemical reacts with the atoms on the surface, turning them into a liquid or gas that washes away.
- **c. Formation of Nanostructures:**
  - **i. Pore Formation:** If the acid attacks the surface unevenly, it creates millions of tiny "nano-pores."
  - **ii. Structure Definition:** If a mask is used, the acid only eats the unprotected areas, leaving behind nanopyramids, nanowires, or pillars.

B. Key Processing Parameters:

- **a. Etchant Concentration:** A stronger acid eats the material faster but can be harder to control. Low concentrations are used to get very precise, small pores.
- **b. Temperature:** Higher temperatures speed up the chemical reaction. This is used to control the **depth** of the etching.
- **c. Etching Time:** If you etch for too long, you might dissolve the entire material. Timing is critical to stop exactly when the nanostructure is formed.
- **d. Anisotropy:** This refers to whether the acid eats in all directions (Isotropic) or only straight down (Anisotropic). For energy storage, we often want **Anisotropic etching** to create deep, vertical pores.

C. Role in Energy Storage: The "Porous Silicon" Revolution

Why do we etch materials for batteries?

- **a. Handling Volume Expansion:** Silicon is a great anode because it holds a lot of energy, but it swells by 300% when charging, which causes it to crack.
  - i. **The Solution***:* By **etching** silicon to make it "porous" (like a sponge), we create empty space. When the silicon expands, it fills the pores instead of breaking the electrode.
- **b. Increasing Surface Area:** Etching turns a flat, smooth surface into a rough, "mountainous" landscape at the nanoscale. This allows more electrolyte to touch the electrode, leading to faster charging.
- **c. Creating MXenes:** Etching is the primary way to create **MXenes** (a famous class of 2D materials for supercapacitors). We use acid to "etch out" specific layers from a bulk crystal, leaving behind thin, highly conductive sheets as shown in table 3.

Table 3: Advantages and Disadvantages of Chemical Etching

Advantages	Disadvantages
High Precision: Can create very specific, complex shapes and deep pores.	**Hazardous Chemicals:** Uses very strong acids (like HF) that are dangerous to handle.
Uniformity: Unlike ball milling, etching creates a very consistent surface across the whole material.	**Waste Generation:** Produces a lot of chemical waste that must be treated.
Stress Relief: Excellent for making materials that won't crack during battery cycling.	**Material Loss:** You are "throwing away" the material you etch off, which can be expensive.

The Bottom-Up Approach (Chemical Assembly): This approach starts with the smallest possible building blocks-atoms, molecules, or ions and assembles them into a nanostructure. It is smaller to an architect building a house brick-by-brick.

© STM Journals 2026. All Rights Reserved

Mechanism: It relies on chemical reaction and "self-assembly". Atoms are manipulated in a liquid or gas phase, so they naturally bond together to form a specific shape.

Key characteristics:
(a) Extreme precision in size and shape (can make perfect tubes, wires, or dots).
(b) Produces materials with very high purity and fewer defects.
(c) Allows for "Morphology Tuning" (changing the shape by changing the temperature).

Primary methods:

I. **Hydrothermal synthesis:** Hydrothermal synthesis is a premier Bottom-Up strategy that utilizes high-pressure aqueous environments to 'grow' nanostructures with exceptional crystalline quality. Its ability to produce complex morphologies like nanoflowers makes it indispensable for developing high-rate supercapacitors and battery electrodes. In the world of energy storage, this is the "Gold Standard" for making metal oxide electrodes (like MnO_2 or TiO_2).

Hydrothermal Synthesis: Think of Hydrothermal synthesis as a **high-tech pressure cooker**. In nature, this is how giant quartz crystals grow deep inside the Earth's crust. In the lab, we mimic this by using high heat and extreme pressure to force atoms to bond into perfect nanocrystals.

A. **The Working Mechanism: The "Cook and Grow" Cycle**
   a. **Precursor Dissolution:** You dissolve metal salts (the raw ingredients) in water to create a clear solution. At room temperature, these chemicals stay separate.
   b. **The Autoclave (The Reactor):** The solution is poured into a Teflon-lined stainless-steel container called an **Autoclave**. It is sealed tightly so no air or steam can escape.
   c. **Heating and Pressure:** The autoclave is placed in an oven at temperatures typically between 100°C and 250°C. Because the liquid is trapped, the internal pressure rises significantly.
   d. **Nucleation and Crystal Growth:** Under these "supercritical" conditions, the water becomes very reactive. The metal atoms start bumping into each other and sticking together (Nucleation). They then grow into specific shapes (Growth) based on how long you "cook" them. (as shown in figure 5)

B. **Key Processing Parameters:**

How scientists "tune" the battery material?
a. **Reaction Temperature:** Higher temperatures usually lead to better "Crystallinity." If the crystals are perfect, electrons can move through the battery much faster.
b. **Reaction Time:** This is the "Shape Controller."
   i. *Short time (6 hours):* You might get small "nanodots."
   ii. *Long time (24 hours):* Those dots grow into long "nanowires" or "nanorods."
c. **pH Level (Acidity):** Adding a little bit of acid or base changes the surface charge of the particles. This determines if they grow into a "flower" shape or a "sphere."
d. **Fill Degree:** How much liquid you put in the autoclave (usually 60–80%) determines the internal pressure. More liquid = higher pressure.

C. **Role in Energy Storage: Why it's the "Best" for Oxides**
   a. **High Surface Area "Nanoflowers":** Hydrothermal synthesis is famous for creating 3D structures that look like flowers. This "open" structure allows the liquid electrolyte to soak deep into the electrode, providing massive energy storage.
   b. **Low Temperature: It is a "Soft Chemistry" (Chimie Douce) method.** Unlike some methods that need 1000°C, this happens at 150°C.This saves energy and prevents the nanoparticles from melting together.

© STM Journals 2026. All Rights Reserved

c. **Direct Growth on Foil:** You can put a piece of Nickel foam or Carbon cloth inside the autoclave. The nanomaterials will grow **directly** onto the cloth, creating a "Binder-Free" electrode that is much more conductive as shown in table 4.

Table 4. Advantages and Disadvantages of Hydrothermal Process

Advantages	Disadvantages
Excellent Shape Control: **Can make wires, tubes, stars, and flowers with high precision.**	**Slow Process:** It often takes 12 to 48 hours to complete one batch.
High Purity: **Since it's a closed system, no dust or contaminants can get in.**	**Safety Risk:** Working with high-pressure "bombs" (autoclaves) requires careful training.
Eco-Friendly: **Uses water as the primary solvent instead of toxic chemicals.**	**Black Box:** You cannot see what is happening inside the steel container while it's cooking.




Figure 5. Process of Hydrothermal Process.

II. **Sol-Gel method:** The Sol-Gel process is a versatile Bottom-Up technique that relies on controlled chemical hydrolysis and condensation to form solid networks from liquid phases. It is particularly valued in energy storage for its ability to provide molecular-level mixing, ensuring the production of highly uniform and chemically pure electrode materials.

Sol-Gel uses **chemical reactions at room temperature** to build a solid network from a liquid. It is "Soft Chemistry" (Chimie Douce) approach that is famous for making high-purity metal oxide nanoparticles (like SiO_2, TiO_2, or $LiFePO_4$).

Sol-Gel Method: The name tells you exactly what happens: you start with a liquid **"Sol"** (a stable suspension of tiny particles) and turn it into a solid **"Gel"** (a continuous network filled with liquid). It's like making jelly—you start with a liquid and end up with a solid structure.

A. **The Working Mechanism: Step-by-Step**
   a. **Preparation of the "Sol":** You dissolve a "precursor" (usually a metal alkoxide or metal salt) in a solvent like water or alcohol.

© STM Journals 2026. All Rights Reserved

b. **Hydrolysis:** Water is added, which reacts with the precursor to create reactive hydroxyl (-OH) groups.
c. **Condensation (Gelation):** These reactive molecules start sticking together, releasing water or alcohol. They form a 3D "skeleton" that spans the entire container. This is the **Gel**.
d. **Aging:** The gel is left for a few hours or days. During this time, the "skeleton" gets stronger and thicker.
e. **Drying:** The liquid trapped inside the gel is removed.
   i. If you dry it in an oven, it shrinks and becomes a **Xerogel** (a dense powder).
   ii. If you dry it under special "supercritical" conditions, it stays light and airy, becoming an **Aerogel**.

f. **Calcination (Firing):** The final powder is heated in a furnace to burn away any leftover chemicals and make the crystals perfect. (as shown in figure 6)

B. Key Processing Parameters:

a. **pH of the Solution:** This is the most important setting.
   i. **Acidic pH:** Leads to long, linear chains (better for making thin films or fibres).
   ii. **Basic pH:** Leads to clusters and spheres (better for making battery powders).
b. **Temperature:** Usually done at room temperature, which prevents the atoms from moving too fast, resulting in very small, uniform particles.
c. **Water-to-Alkoxide Ratio:** This determines how fast the "jelly" sets. More water usually means faster gelation.

C. Role in Energy Storage: Why use Sol-Gel for Batteries?

a. **Atomic-Level Mixing:** Because everything starts in a liquid solution, you can mix different elements (like Lithium, Iron, and Phosphorus) perfectly. This ensures that every single nanoparticle in your battery has the exact same chemical recipe.
b. **Thin-Film Electrodes:** Because the "Sol" is a liquid, you can easily dip a piece of metal into it or spin it to create a perfectly flat, nano-thin coating.
c. **High Purity:** Since it's done at lower temperatures than melting metals, there is very little chance of outside contamination.
d. **Complex Hybrids:** It is the best method to mix organic materials (polymers) with inorganic materials (metals) to make "Hybrid Electrodes" that are flexible and strong as shown in table 5.

Table 5. Advantages and Disadvantages of Sol-Gel Method

Advantages	Disadvantages
Uniformity: Produces particles that are almost the same size.	**High Cost:** The chemical "precursors" (alkoxides) can be very expensive.
Low Temperature: Saves energy compared to traditional melting or CVD.	**Shrinkage:** The gel can shrink significantly during drying, which might cause cracks.
Versatility: Can make powders, thin films, fibres, or even light-weight aerogels.	**Toxic Solvents:** Often uses alcohols or organic chemicals that require careful disposal.

III. Chemical Vapor Deposition: Chemical Vapor Deposition (CVD) is a premier Bottom-Up synthesis strategy that utilizes the thermal decomposition of gaseous precursors to engineer high-purity nanostructures. It is the definitive method for producing the high-conductivity carbon frameworks (Graphene and CNTs) required for next-generation, fast-charging energy storage systems.

CVD is the "Gold Standard" for synthesizing **Graphene** and **Carbon Nanotubes (CNTs)**, which are the most conductive materials used in modern energy storage.

© STM Journals 2026. All Rights Reserved




Figure 6. Process of Sol-Gel method.

Chemical Vapor Deposition (CVD): The Gas-Phase Growth

Imagine "printing" a layer of carbon or metal onto a surface using steam. In CVD, you turn a chemical into a gas, fly it over a hot surface, and let it "crystallize" or settle down to form a solid nanostructure.

A. The Working Mechanism: Step-by-Step:

- **a. Precursor Gas Injection:** A "source" gas (like Methane for carbon or Silane for silicon) is pumped into a high-temperature furnace.
- **b. Thermal Decomposition:** As the gas reaches the hot zone (usually 700°C to 1100°C the chemical bonds in the gas break apart.
- **c. Adsorption:** The free atoms (like Carbon) land on a solid surface called a **Substrate** (usually a piece of copper foil or a Silicon wafer).
- **d. Surface Reaction & Growth:** The atoms move around the surface until they find a stable spot to bond. They "grow" upwards or outwards into a solid layer, a wire, or a tube.
- **e. Exhaust:** The leftover gases that didn't react are pumped out of the system (as shown in figure 7).

B. Key Processing Parameters:

- **a. Temperature:** This is the "Energy Source." If it's too low, the gas won't break; if it's too high, the nanostructure might melt or become messy.
- **b. Gas Flow Rate:** This determines how many "bricks" (atoms) are available to build the structure. If you pump gas too fast, the layer might become too thick and lose its "nano" properties.
- **c. Pressure:** CVD can be done at atmospheric pressure (APCVD) or in a vacuum (LPCVD). Vacuum usually produces much cleaner and more uniform materials.
- **d. Catalysts:** To grow Carbon Nanotubes, scientists often "seed" the surface with tiny dots of Iron or Nickel. The nanotubes grow out of these dots like grass growing from seeds.

C. Role in Energy Storage: Why CVD is Essential

- ***a.*** **Making Graphene:** CVD is the only way to make large, high-quality sheets of Graphene. Graphene is used in supercapacitors because it can hold a massive amount of charge and move electrons at incredible speeds.
- ***b.*** **Vertical Carbon Nanotubes:** CVD can grow "forests" of nanotubes that stand straight up. This creates a 3D structure with a huge surface area, perfect for high-power battery electrodes.
- ***c.*** **Nano-Coating:** You can use CVD to put a thin "skin" of Carbon around a Silicon particle. This carbon skin acts like a "cage," holding the silicon together so it doesn't break during battery charging.

© STM Journals 2026. All Rights Reserved

d. **High Conductivity:** Because CVD happens at high temperatures, the resulting materials have very few defects, meaning electricity flows through them with almost zero resistance as shown in table 6.

Table 6. Advantages and Disadvantages of Chemical Vapour Deposition Method

Advantages	Disadvantages
Highest Quality: Produces the most pure and conductive nanostructures in the world.	**High Cost:** The equipment (furnaces, vacuum pumps, gas controllers) is very expensive.
Uniform Coating: Can coat complex 3D shapes (like a sponge) perfectly and evenly.	**Hazardous Gases:** Uses gases that can be toxic, explosive, or flammable (like Hydrogen).
Structural Control: Can grow 1D (tubes), 2D (sheets), and 3D structures with ease.	**High Energy:** Requires a lot of electricity to keep the furnace at 1000°C for hours.




Figure 7. Process of Chemical Vapor Deposition.

FABRICATION OF NANOMATERIALS

Fabrication is the "construction" phase. While synthesis creates the material, fabrication determines the **architecture** of the electrode. It involves techniques to deposit nanomaterials onto current collectors (like Copper or Aluminium foil) or building them into 3D structures.

The goal of fabrication in energy storage is to ensure **High Adhesion** (the material doesn't flake off), **High Porosity** (the electrolyte can reach every particle), and **Electrical Connectivity**.

Key Fabrication Processes:

A. **Solution-Based Processing (Slurry Casting):** This is the most common industrial method. You take your synthesized nano-powder and turn it into a "paint."
   a. **The Process:** Nanomaterials are mixed with a **Binder** (a polymer glue like PVDF) and a **Conductive Additive** (like Carbon Black) in a solvent to create a **Slurry**.
   b. **Doctor Blade (Tape Casting):** The slurry is placed on a metal foil, and a sharp blade moves across it, leaving a perfectly even layer of a specific thickness.

© STM Journals 2026. All Rights Reserved

c. **Spin Coating:** For thin-film batteries, the slurry is dropped onto a spinning disc, using centrifugal force to create an ultra-thin, uniform layer.

B. **Vapor-Phase Fabrication (Vacuum Deposition):** This is used when you need extreme purity and a very strong bond between the material and the metal.
   a. **Physical Vapor Deposition (PVD) / Sputtering:** In a vacuum chamber, high-energy ions hit a target of your material, knocking atoms off so they fly and stick to your electrode surface.
   b. **Thermal Evaporation:** Heating a material until it turns into vapor, which then condenses onto the cooler electrode.
   c. **Benefit:** These methods provide the best "adhesion," meaning the nanomaterial will not peel off during thousands of charging cycles.

C. **Structural Fabrication (3D Scaffolding):** This builds the "skeleton" of the electrode.
   a. **Electrospinning:** A high-voltage electric field pulls a liquid polymer/nanomaterial solution into incredibly thin **1D nanofibers**. This creates a 3D "non-woven mat" that looks like a sponge.
   b. **Benefit:** It creates a huge surface area and large pores, allowing the liquid electrolyte to flow through the battery very easily.

D. **Patterning (Lithography):** Used specifically for micro-batteries or sensors.
   a. **Photolithography:** Using UV light and a "mask" to print specific shapes (like tiny combs or grids) onto a substrate.
   b. **Soft Lithography:** Using a flexible stamp to "print" the nanomaterial pattern.

Critical Parameters in Fabrication:

a. **Binder Content:** If you use too much "glue" (binder), you block the electricity. If you use too little, the nanomaterial falls off.
b. **Mass Loading:** How much material can you pack into a small space? Fabrication must balance thickness with performance.
c. **Annealing (Post-Processing):** After fabrication, the electrode is usually heated (annealed) to remove solvents and strengthen the bond between the particles.
d. **Wettability:** The fabricated structure must be "hydrophilic" or "lyophilic" enough so that the liquid electrolyte can soak into all the nano-pores.

The role of fabrication in energy storage:

Fabrication is the engineering process of assembling synthesized nanomaterials into a functional electrode. In a battery or supercapacitor, the fabrication method determines three critical factors:

a. **Electronic Conductivity:** How well electrons move from the nanomaterial to the metal circuit.
b. **Ionic Diffusion:** How easily the liquid electrolyte can soak into the "pores" of the material.
c. **Mechanical Stability:** How well the material stays attached to the metal foil during 1,000+ charge/discharge cycles.

CARBON-BASED NANOMATERIALS: (GRAPHENE, CNTS, MXENES)

Carbon nanomaterials are at the forefront of materials science, offering unique properties and applications across various industries. This category encompasses a range of materials including *Graphene, Carbon Nanotubes (CNTs), MXenes*, and more, each with distinct characteristics that contribute to advancements in technology and innovation.

Graphene

Graphene is a single layer of sp^2 hybridized carbon atoms arranged in a 2D hexagonal "honeycomb" lattice. It is the basic structural unit of other graphitic materials (it can be wrapped into 1D CNTs or stacked into 3D Graphite).

© STM Journals 2026. All Rights Reserved




Figure 8. Schematic representation of the synthesis route from bulk graphite to reduced graphene oxide, involving the exfoliation of graphene, chemical oxidation to graphene oxide, and subsequent reduction

Key properties:

(a) Massive Surface Area: It has a theoretical surface area of *2630 m^2/g*. In a supercapacitor, charge is stored on the surface. If you have a huge surface area, you can "park" millions of ions at once, leading to massive energy storage in a tiny space.

(b) Ultra-High Electrical Conductivity: Electrons move through graphene as "massless Dirac fermions" at speeds of *10^6 m/s*. This low resistance means the battery doesn't get hot during fast charging. It allows for High Power Density.

(c) Superior Mechanical Strength: It is 200 times stronger than steel but incredibly flexible. During charging, electrode materials (like Silicon) expand and contract. Graphene acts as a "flexible cage" that holds these materials together so they don't shatter.

(d) High Thermal Conductivity: It conducts heat better than diamond or copper. It helps spread heat evenly across the battery pack, preventing "Thermal Runaway" (explosions).

Synthesis Methods for Graphene:

(a) Chemical Vapor Deposition (CVD):

Process*:* Growing graphene on copper foil using Methane gas.

Result: Produces the highest quality, "pristine" graphene. Best for high-end research.

(b) Chemical Exfoliation (Hummers' Method):

Process: Using strong acids to oxidize graphite into Graphene Oxide (GO), then reducing it to rGO.

Result: This is the "Mass Production" method. It is cheaper and produces "flakes" that are easy to mix into battery slurries.

Specific Applications in Electrodes

(a) As an Active Material (Supercapacitors): Because ions "stick" to the surface of graphene almost instantly, it allows a supercapacitor to charge in seconds rather than hours.

(b) As a Conductive "Wrap" (Batteries): Scientists wrap "High-Capacity" materials (like Sulphur or Silicon) inside graphene sheets. The graphene provides the "electrical highway" that these materials lack.

(c) As a Protective Coating: A thin layer of graphene on a metal foil prevents the liquid electrolyte from "eating away" at the metal (corrosion), making the battery last for years instead of months.

© STM Journals 2026. All Rights Reserved

The Restacking Problem and 3D Graphene Architectures:

The Problem: "The Wet Paper Effect" Graphene sheets have a natural tendency to stick back together due to strong Van der Waals forces. Imagine taking thousands of individual silk sheets and throwing them into water; they will clump together into a thick, solid block. In a battery, if graphene sheets restack, they turn back into Graphite. This *"hides"* the surface area, meaning ions can no longer reach the inner layers. This drastically reduces the battery's capacity and charging speed.

The Solution: *"Spacers"* and 3D Architecture To prevent this, scientists use *"Pillaring"* or *"Spacers"* to keep the sheets separated. This creates a 3D Graphene Architecture—a porous, sponge-like structure where every single sheet is accessible to the electrolyte.

i. **Carbon Nanotubes (CNTs) as Spacers:** 1D CNTs are inserted between 2D graphene layers. They act like "pillars" holding up a roof, creating a 3D conductive network with "tunnels" for ions to move through**.**
ii. **Nanoparticle Spacers:** Tiny nanoparticles (like Silicon or Metal Oxides) are placed between the sheets. This is a "double win": the particles prevent restacking, and the graphene prevents the particles from breaking during charging.
iii. **Self-Assembled 3D Hydrogels:** Using hydrothermal synthesis, graphene sheets can be forced to grow into a 3D "crumpled" foam. Because the sheets are wrinkled, they cannot lay flat against each other, leaving open "macro-pores" for the liquid electrolyte.

Carbon Nanotubes (CNTs):

Carbon Nanotubes are allotropes of carbon with a cylindrical nanostructure. They possess a high aspect ratio (length-to-diameter ratio), which can be as high as 132,000,000:1. This makes them the ultimate "1D conductor" for moving electrons. (as shown in figure 8)

Classification of CNTs

(a) **Single-Walled Carbon Nanotubes (SWCNTs):**
   i. **Structure**: A single cylinder of graphene.
   ii. **Properties:** Exceptional electrical conductivity and higher surface area.
   iii. **Role:** Used in high-end research and "Super-Fast" charging electrodes. (as shown in figure 9)

(b) **Multi-Walled Carbon Nanotubes (MWCNTs):**
   i. **Structure:** Multiple layers of graphene cylinders nested inside one another (like a Russian nesting doll).
   ii. **Properties:** Cheaper to produce and more mechanically robust.
   iii. **Role:** The "Industrial Standard" for adding conductivity to commercial battery slurries. (as shown as figure in 9)

Synthesis: The CVD Growth Mechanism

The specific "Growth Models" for CNTs:

(a) **Tip-Growth Model:** The metal catalyst particle (usually Iron or Nickel) sits on top of the growing nanotube. The carbon gas dissolves into the metal and "pushes" the tube up.
(b) **Base-Growth Model:** The catalyst particle stays stuck to the substrate, and the nanotube grows out of it like a hair growing from a root.

Why CNTs are Essential for Energy Storage?

(a) **The 3D Conductive Network:**

The Problem: Active materials like Lithium Iron Phosphate ($LiFePO_4$) are poor conductors.

© STM Journals 2026. All Rights Reserved

The Solution: Adding just 1–2% of CNTs creates a "spider web" of wires that connects every single particle to the current collector. This allows for High-Rate Capability (fast discharge).




Figure 9. Classification of Carbon Nanomaterials based on dimensionality and layers, comparing single-layered graphite, single-walled carbon nanotubes (SWCNTs), and multi-walled carbon nanotubes (MWCNTs).

(b) Mechanical "Binder" Replacement:

Because CNTs are so long and strong, they physically "wrap" around active particles. This helps prevent the electrode from cracking during the expansion/contraction of charging cycles.

(c) High Surface Area for Supercapacitors:

CNTs provide a large surface for ions to adsorb. Because the tubes are hollow, ions can sometimes even enter the inner core of the tube, increasing the storage capacity.

MXenes:

While Graphene is purely Carbon, MXenes are Inorganic 2D layers made of transition metals (like Titanium) and Carbon or Nitrogen. In the context of energy storage, MXenes are famous for being "Metallic Conductors" that actually like water, making them much easier to process than Graphene.

MXenes (pronounced "max-eens") are a large family of two-dimensional transition metal carbides, nitrides, or carbonitrides. Their general formula is $M_{n+1}X_n T_x$, where:

M: A transition metal (e.g., Titanium, Vanadium, Molybdenum).

X: Carbon or Nitrogen.

T_x: Surface terminations (like -OH, -F, or =O) that make them chemically active.

Synthesis: The Selective Etching Process (Top-Down):

"MAX Phase" is parent material. This is a critical technical detail.

a. **The Parent (MAX Phase):** You start with a bulk 3D crystal called a MAX phase (e.g., Ti_3AlC_2). Here, layers of Titanium Carbide are held together by "A-group" layers (usually Aluminium).
b. **Chemical Etching:** You submerged the MAX phase in a strong etchant, most commonly Hydrofluoric Acid (HF) or a mixture of HCl and LiF. (As shown in figure 10)

© STM Journals 2026. All Rights Reserved

c. **Selective Removal:** The acid specifically attacks and dissolves the Aluminium ("A") layers but leaves the Titanium Carbide ("MX") layers untouched.
d. **Delamination:** After etching, the material looks like an "opened accordion." You then use ultrasonication or "intercalation" to peel the layers apart into individual 2D sheets.

Why MXenes are "Better" for Energy Storage?

a. **Metallic Conductivity:** Unlike many 2D materials that are semiconductors, MXenes behave like metals. They have a very high *"Electron Density"* allowing for ultra-fast charge transport in battery electrodes.
b. **Hydrophilicity (Water-Loving):** Because of the surface groups (-OH and =O), MXenes disperse perfectly in water without needing harsh chemicals. This makes Fabrication very easy. You can make MXene *"clay"* or *"ink"* and simply paint it onto an electrode.
c. **Large Interlayer Space:** The space between MXene sheets is adjustable. This acts like a "multi-story parking garage" where Lithium, Sodium, or Potassium ions can slide in and out (intercalation) with very little resistance.
d. **High Volumetric Capacity:** MXenes are much denser than Carbon. This means a battery made of MXene can store more energy in a smaller volume, which is perfect for smartphones and wearable tech.

Specific Roles in Electrodes:

a. **Supercapacitors**: MXenes show "Pseudo capacitance." This means they store energy both by ions sticking to the surface (like Graphene) and through fast chemical reactions on the metal surface.
b. **Ion-Sieving Membranes**: Because they are 2D sheets, they can be fabricated into membranes that allow only specific battery ions to pass through, preventing short circuits.
c. **Conductive "Glue"**: MXenes can be mixed with high-capacity materials (like Silicon) to act as both a binder and a conductive network.




Figure 10. Synthesis of multilayer MXene by the process of Etching

METAL OXIDES & HYBRID NANO-COMPOSITES

Metal oxides offer the high theoretical capacity needed for next-generation energy storage, but their poor conductivity and structural instability limit their use. By engineering Hybrid Nano-Composites, we combine the energy density of oxides with the electrical 'highways' and mechanical flexibility of carbon nanomaterials, creating electrodes that are both powerful and durable.

Metal Oxide Nanostructures:

Metal oxides (like MnO_2, TiO_2, Fe_3O_4, and Co_3O_4) are materials where a metal is bonded with oxygen. In energy storage, they are prized for their **Theoretical Capacity**, which is often 3x to 5x higher than traditional graphite.

The Storage Mechanism: Conversion vs. Pseudo capacitance

(a) Conversion Reaction: Unlike graphite where ions just "sit" between layers, metal oxides actually undergo a chemical change during charging (e.g., $Fe_3O_4 + 8Li^+ \rightarrow 3Fe + 4Li_2O$). This allows them to store a massive amount of Lithium.

© STM Journals 2026. All Rights Reserved

(b) Pseudo capacitance: Materials like MnO_2 store energy through fast "redox" reactions on the surface. This gives them the speed of a capacitor but the energy of a battery.

The "Major Problem": Volume Expansion

The biggest drawback of metal oxides is that they "breathe" too much. When Lithium ions enter, the metal oxide can swell by **200% to 300%**.

Result: The material eventually shatters (pulverization), loses contact with the circuit, and the battery dies quickly.

Hybrid Nano-Composites: The "Better Together" Strategy:

To solve the problems of metal oxides, scientists create **Hybrids**. A hybrid composite combines a "High-Capacity" material with a "High-Stability" material.

The Architecture: Metal Oxide + Carbon

The most successful hybrid is **Metal Oxide nanoparticles grown on Carbon (Graphene or CNTs)**.

(a) The Carbon Role: Acts as a "*Flexible Scaffold*" and a "Conductive Highway." It moves electrons quickly and holds the metal oxide pieces together.

(b) The Metal Oxide Role: Acts as the "*Energy Reservoir*." It provides the high capacity that carbon lacks.

Synergy:

(a) Stress Buffer: The carbon matrix (like a 3D graphene foam) has empty spaces that "cushion" the expansion of the metal oxide.

(b) Short Diffusion Paths: By using **0D metal oxide dots** on **1D CNTs**, the ions only have to travel a few nanometres to react, making the battery charge in minutes.

(c) Prevention of Aggregation: The carbon sheets keep the metal oxide nanoparticles separated, preventing **Ostwald Ripening** (where particles clump together and lose their nano-power) as shown in table 7.

Table 7. Examples of High-Performance Hybrids

Hybrid Type	Component A (Active)	Component B (Support)	Application
Silicon/Carbon	Silicon Nanoparticles	Graphene Sheets	High-capacity Anodes
MnO_2/CNT	Manganese Oxide	Carbon Nanotubes	Fast-charging Supercapacitors
SnO_2/MXene	Tin Oxide	2D MXene layers	Long-life Sodium-ion batteries

CHARACTERIZATION OF NANOSTRUCTURED ELECTRODES

The revolution of nanotechnology lies in the ability to manipulate matter at the atomic level, creating materials with extraordinary chemical and mechanical properties. However, synthesizing these materials is only the first step; precise characterization is the bridge that connects a nanomaterial's physical structure to its real-world performance.

Characterization involves a rigorous analysis of a material's composition and architecture to reveal the "structure-property" relationship. By utilizing advanced tools like electron microscopy, X-ray diffraction, and various spectroscopic techniques, researchers can verify the success of the synthesis process and ensure quality control. These insights into size, shape, and crystal structure are indispensable for tailoring nanostructured electrodes to meet the specific demands of next-generation energy storage systems.

Morphological Characterization (Visualizing the Nano-Architecture): The primary goal of morphological study is to confirm that the material has transitioned from a "*Bulk*" state to a "*Nano*" state with high surface area.

© STM Journals 2026. All Rights Reserved

FESEM (Field Emission Scanning Electron Microscopy):

Working Principle: A high-energy electron beam scans the surface of the electrode. It provides a 3D topographic image with nanometre resolution. (as shown in figure 11)

Function in Energy Storage: It is used to observe the "*Open 3D Architecture*." For Graphene and CNTs, FESEM confirms that the sheets are not "restacked" and the tubes are well-dispersed, ensuring the electrolyte can soak into the entire electrode.




Figure 11. Schematic diagram and working principle of a Field Emission Scanning Electron Microscopy (FESEM).

HRTEM (High-Resolution Transmission Electron Microscopy):

Working Principle: Electrons pass *through* an ultra-thin sample. It can image the internal atomic lattice. (as shown in figure 12)

Function in Energy Storage: It measures the interlayer d-spacing. For MXenes, HRTEM proves that the Aluminium "A-layers" have been removed, creating wide channels for ions to slide into during charging.




Figure 12: High-Resolution Transmission Electron Microscopy (HRTEM) lattice image alongside the corresponding optical ray diagram and electron diffraction pattern formation.

© STM Journals 2026. All Rights Reserved

Structural and Chemical Fingerprinting (The Identity Test)

These techniques prove the chemical purity and the quality of the "**Carbon Matrix.**"

XRD (X-Ray Diffraction):

Working Principle: X-rays hit the crystal lattice and diffract at specific angles (2θ) according to Bragg's Law. (as shown in figure 13)

Function in Energy Storage: It tracks the Delamination process. In MXenes, the (002) peak shifts to a lower angle, proving the layers have expanded. For Graphene, the disappearance of the sharp Graphite peak at 26.5°C proves successful exfoliation.




Figure 13: Schematic representation of X-ray diffraction (XRD), showing (a) the experimental setup with an X-ray beam striking a crystal, and (b) the geometric derivation of Bragg's Law for constructive interference between crystal planes.

Raman Spectroscopy:

Working Principle: Laser light interacts with molecular vibrations, causing a frequency shift. (as shown in figure 14)

Function in Energy Storage: It measures the Conductivity vs. Defects. The G-band represents high electrical conductivity, while the D-band represents defects (active sites). A balanced I_D/I_G ratio is essential for an electrode that is both fast-conducting and high-capacity.

Performance & Surface Characterization (The Engine Test)

This is where we quantify the energy storage capability.

a. BET (Brunauer–Emmett–Teller) Analysis:

Working Principle: Nitrogen gas is adsorbed onto the surface at cryogenic temperatures to measure the total surface area.

Function in Energy Storage: It quantifies the Porosity. Since energy storage is surface-dependent, a high BET value (e.g., 1500m^2/g) directly correlates to higher energy density in supercapacitors.

© STM Journals 2026. All Rights Reserved




Figure 14. Schematic diagram and optical configuration of a Raman spectrometer, showing the path from the laser source to the sample and the subsequent detection of scattered light.

b. GCD (Galvanostatic Charge-Discharge):

Working Principle: A constant current is applied to the electrode while the change in voltage is measured over time.

Function in Energy Storage: It measures the Specific Capacity (*mAh/g).* The linear slope of the GCD curve tells us how many ions were stored and how long the battery will last in a real-world device.

ENERGY STORAGE MECHANICS (EDLC VS. PSEDUCAPACITANCE)

Introduction to Electrochemical Interphases:

Energy storage in nanostructured electrodes is governed by the behaviour of charge carriers at the Electrode-Electrolyte Interface (EEI). In bulk materials, ion diffusion is slow and limited by the small surface area. Nano structuring transforms this by providing a "shortened diffusion path" (L), where the time (t) taken for an ion to diffuse is proportional to the square of the distance ($t \approx L^2/D$). By reducing L to the nanoscale, we achieve near-instantaneous power delivery.

Electrical Double-Layer Capacitance (EDLC):

i. **Mechanism:** Electro sorption (Non-Faradaic)

EDLC is the "physical" storage of energy, primarily found in **Graphene** and **Carbon Nanotubes (CNTs)**.

The Helmholtz Layer: When a carbon electrode is charged, it creates a surface charge density. To maintain neutrality, a layer of solvated ions from the electrolyte aligns at a distance (d) from the surface. This creates two layers of opposite charges—a microscopic capacitor. (as shown in figure 15)

Governing Equation: The capacitance (C) is defined by the formula:

$$C = \frac{\varepsilon A}{d}$$

Where ε is the dielectric constant, A is the **Specific Surface Area (SSA)**, and d is the distance to the centre of the ion layer.

© STM Journals 2026. All Rights Reserved

ii. **The Nano Benefit:** Since d is fixed at the molecular level, the only way to increase C is to maximize A. This is why Graphene's theoretical surface area of **2630 m²/g** is the industry goal.
iii. **Kinetics:** Because no chemical bonds are broken and no electrons cross the interface (Non-Faradaic), there is no "activation energy" required. This results in **ultra-high-power density** and a lifecycle exceeding **1,000,000 cycles**.




Figure 15. Schematic diagram and equivalent electrical circuit of an electrochemical double-layer capacitor (EDLC), illustrating charge accumulation at the Helmholtz layers and internal resistance contribution.

Pseudo Capacitance

Mechanism: Reversible Redox (Faradaic): This is the "chemical" storage of energy, dominant in MXenes and Metal Oxides. Unlike a battery, where chemical changes happen deep inside the bulk (slow), pseudo capacitance involves fast surface redox reactions. Electrons are transferred across the interface, but so quickly that the device still behaves like a capacitor.

Three Types of Pseudo capacitance:

a. **Underpotential Deposition:** Metal ions form a monolayer on a different metal surface.
b. **Redox Pseudo capacitance:** Fast chemical reactions on the surface (e.g., $MnO_2 + C^+ + e^- \leftrightarrow MnOOC$).
c. **Intercalation Pseudo capacitance**: This is key for **MXenes**. Ions slide between the 2D layers (intercalation) without causing a phase change in the material.

The MXene Advantage: MXenes possess functional groups (-OH, -F, =O) on their surface. These groups act as "active sites" for protons (H^+) or metal ions (Li^+, Mg^{2+}) to bond and release electrons rapidly. (as shown in figure 16)

Energy vs. Power: Pseudo capacitance offers significantly higher Energy Density than EDLC because it utilizes chemical valence changes, but it has slightly lower Power Density due to the time required for the chemical reaction to occur.

ELECTROCHEMICAL PERFORMANCE & ANALYSIS

Why Performance Analysis is Critical?

Synthesis and structural characterization (SEM/TEM) confirm the physical identity of a nanomaterial, but **Electrochemical Performance Analysis** determines its functional value. In the context of energy storage, we need to quantify how much energy a material can hold **(Capacity),** how fast it can deliver that energy **(Power)**, and long it survives under stress **(Stability).**

© STM Journals 2026. All Rights Reserved




Figure 16. Schematic illustration of the three primary mechanisms of pseudo capacitance: (a) underpotential deposition, (b) redox pseudo capacitance, and (c) intercalation pseudo capacitance as shown in table 8.

Table 8. Comparison Table for EDLC and Pseudo capacitance

Property	**EDLC (Carbon-based)**	**Pseudo capacitance (MXenes/Oxides)**
Origin of Charge	Physical accumulation of ions	Chemical electron transfer (Redox)
Active Sites	Surface pores and edges	Surface atoms and functional groups
Charge/Discharge Time	10^{-3} to 10^{-1} seconds	10^{-1} to 10^{2} seconds
Cyclability	>1,000,000 (Excellent)	10,000 - 50,000 (Good)
Material Example	Graphene, CNTs, Carbon Foam	$Ti_3C_2T_x$ MXenes, RuO_2, MnO_2

For nanostructured electrodes, this analysis is vital because it reveals the "Nano-Effect"—how reduced dimensions and increased surface area physically change the kinetics of ion transport. Without these tests, we cannot compare a new material like an **MXenes** to a traditional commercial **Graphite** electrode.

Cyclic Voltammetry (CV): Kinetic & Identity Study:

CV is the first test performed to identify the "DNA" of the electrode's storage mechanism. It measures the current response while sweeping the voltage linearly.

a. The Identity Test: Rectangular Shapes:

Typical of **Graphene/CNTs**, indicating ideal **EDLC**. The lack of peaks shows that ions are simply adsorbing on the surface without chemical changes.

Redox Peaks: Indicate **Pseudo capacitance**. In **MXenes**, these peaks are often broad, showing that surface redox reactions are happening at lightning speed.

b. The Power Law *($i = av^b$)*: By changing the scan rate (v), we calculate the **b-value**. A b-value of 1.0 proves the material is "surface-controlled" (super-fast), while 0.5 proves it is "diffusion-controlled" (slow battery-like).

Galvanostatic Charge-Discharge (GCD): The Gold Standard:

GCD is the most reliable way to measure **Specific Capacity**. It simulates real-world usage by charging and discharging the electrode at a constant current (I).

Linear vs. Plateau: A perfectly linear triangle proves the material is a **Capacitor**.

A curve with a "plateau" (flat region) proves it is a **Battery** material undergoing a phase change.

© STM Journals 2026. All Rights Reserved

a. The IR Drop Phenomenon: When the current is reversed, there is a sudden voltage drop (ΔV_{IR}). This is caused by the internal resistance of the electrode.

The Nano Factor: Because CNTs and Graphene are highly conductive, they show a near-zero IR drop, meaning they don't waste energy as heat.

b. Calculation: Specific Capacity (C) is derived as:

$$C = \frac{I \times \Delta t}{m \times \Delta V}$$

Electrochemical Impedance Spectroscopy (EIS): Mapping Resistance:

EIS is a deep-dive into the *"internal friction"* of the battery. It uses an AC signal to separate different types of resistance.

(a) The Nyquist Plot:

i. **R_s (Intercept):** Resistance of the electrolyte and contacts.
ii. **R_{ct} (Semicircle):** The *"Charge Transfer"* resistance. A tiny semicircle is the hallmark of a **High-Performance Nanostructure**, proving electrons can hop from the electrolyte to the electrode with ease.
iii. **Warburg Impedance (Tail):** The 45° line at the end. A very steep line proves that ions are moving through the **3D pores** of the electrode with zero congestion.

(b) Rate Capability and Cycling Stability: The "Stress Test"

This section proves if the nanomaterial can survive the *"Real World."*

i. **Rate Capability:** Testing the capacity at high currents (e.g., 10 A/g). Nanostructured materials excel here because their short diffusion paths allow them to maintain 80--90% of their energy even when forced to discharge in seconds.
ii. **Cycling Stability:** Measuring capacity retention over 5,000--10,000 cycles.

Hybrid Nanocomposites (like metal oxides wrapped in graphene) prevent the material from cracking, ensuring a long life.

Therefore, The electrochemical analysis confirms that nano structuring is not merely a structural change, but a functional one. By minimizing the charge-transfer resistance (R_{ct}) and maximizing the ion diffusion kinetics, materials like Graphene and MXenes bridge the gap between high-power capacitors and high-energy batteries.

ADVANTAGES & DISADVANTAGES

Advantages of Nanostructured Electrodes:

The shift from bulk materials to nanostructures offers several *"game-changing"* benefits that solve the limitations of traditional batteries.

i. **High Specific Surface Area (SSA):** By reducing particle size to the nanoscale, the surface-to-volume increases exponentially. This provides a massive number of **active sites** for ion adsorption (EDLC) and surface redox reaction (Pseudo capacitance), leading to significantly higher energy density.
ii. **Shortened Diffusion Paths:** In bulk materials, ions must travel long distances through the solid to reach the center. In nanostructures (especially **1D Nanowires** and **2D Sheets**), the diffusion distance is reduced to a few nanometers. This enables **ultra-fast charging** and high-power delivery.
iii. **Enhanced Electrical Conductivity:** Materials like **Carbon Nanotubes (CNTs)** and **Graphene** act as a continuous conductive network. They reduce the internal resistance of the electrode, allowing electrons to flow freely without generating excessive heat (low IR drop).
iv. **Superior Mechanical Flexibility:** Nanomaterials can *"breathe"*. During the charging process, materials like Silicon or Oxides expand. Nanostructures (like **3D Nanofoams)** have empty spaces that accommodate this volume expansion, preventing the electrode from cracking or pulverizing.

© STM Journals 2026. All Rights Reserved

Disadvantages of Nanostructured Electrodes:

Despite their performance in the lab, nanostructured materials face significant hurdles before they can replace traditional commercial batteries.

i. **High Self-Discharge Rates:** Because the surface area is so high, nanostructured electrode more prone to "leakage" or side reactions with the electrolyte. This can lead to the battery losing its charge quickly when not in use.
ii. **Thermodynamic Instability (Aggregation):** Nanoparticles have high surface energy, which makes them *"unhappy"*. Theu naturally want to stick together to form a larger clump (Aggregation) or undergo **Ostwald Ripening.** This causes the material to lose its "nano-power" and capacity over time.
iii. **Complex and Expensive Synthesis:** Producing high-quality **MXenes** or **Single-Walled CNTs** requires expensive chemicals (like HF acid for etching) and complex processes (like Chemical Vapor Deposition). Scaling these from a small lab beaker to a massive factory is technically difficult and costly.

CHALLENGES & MITIGATION STRATEGIES

Challenge 1: Thermodynamic Instability (Aggregation)

Nanoparticles possess extremely high surface energy. To reach a stable state, they naturally tend to *"clump"* together (Aggregation) or merge into larger particles (Ostwald Ripening).

a. **Impact:** Once they clump, the material loses its *"nano"* properties, the surface area drops, and the battery capacity fades rapidly.
b. **Mitigation Strategy:** Surface Functionalization & Scaffolding
c. **Solution:** Engineers use Surfactants or Capping Agents to create a repulsive force between particles.
d. **Hybrid Approach:** Growing nanoparticles directly onto a *"Scaffold"* like Graphene sheets or Carbon Nanotubes (CNTs) keeps the particles physically separated and anchored, preventing them from moving and merging.

Challenge 2: Low Volumetric Energy Density (The *"Fluffiness"* Problem)

Nanostructured materials are often highly porous and *"fluffy."* While they have high energy per gram (Gravimetric), they take up a massive amount of space per unit of energy (Volumetric).

a. **Impact:** This makes them difficult to use in compact devices like smartphones or electric vehicle battery packs where space is limited.
b. **Mitigation Strategy:** Hierarchical Assembly
c. **Solution:** Designing Hierarchical 3D Structures. By assembling 0D nanoparticles into dense but porous 3D *"micro-spheres"* or *"nanoflowers,"* researchers can maintain high surface area while increasing the tap density (packing density) of the material.

Challenge 3: Poor Initial Coulombic Efficiency (ICE)

During the very first charge cycle, a high-surface-area electrode reacts with the electrolyte to form a Solid Electrolyte Interphase (SEI) layer.

a. **Impact:** Because the surface area is so large, a huge amount of Lithium is *"trapped"* in this layer, leading to a permanent loss of capacity (often 20-30%) in the first cycle.
b. **Mitigation Strategy:** Atomic Layer Deposition (ALD) & Pre-lithiation
c. **Solution:** Applying an ultra-thin (angstrom-scale) protective coating using Atomic Layer Deposition (ALD) of materials like Al_2O_3. This *"artificial SEI"* protects the surface from reacting too much with the electrolyte.
d. **Pre-lithiation:** Adding extra Lithium to the electrode during manufacturing to *"pre-fill"* the SEI layer so that no energy is lost from the main battery during the first use.

Challenge 4: High Production Cost & Scalability

Many laboratory methods (like CVD for nanotubes or HF-etching for MXenes) are expensive, dangerous, or hard to scale to a factory level.

© STM Journals 2026. All Rights Reserved

a. **Mitigation Strategy:** Green Synthesis & Solution Processing
b. **Solution:** Moving toward Hydrothermal Synthesis and Liquid-Phase Exfoliation. These are *"bottom-up"* chemical methods that use water-based solutions and low temperatures, making it easier and cheaper to produce tons of nanostructured material at once.

FUTURE PROSPECTS AND STRATEGIC OUTLOOK

The evolution of nanostructured electrodes is moving beyond simple material synthesis toward **smart, multi-functional, and sustainable** energy systems. The following areas represent the *"Next Frontier"* in energy storage research.

All-Solid-State Batteries (ASSBs):

Current lithium-ion batteries use liquid electrolytes, which are flammable and limit the use of high-voltage nanostructured cathodes.

i. **The Future:** Replacing liquid electrolytes with **solid-state electrolytes** (like ceramics or polymers).
ii. **The Nano Role:** Nanostructured interfaces will be critical to solving the *"Contact Resistance"* problem between a solid electrode and a solid electrolyte. 3D "*interpenetrating*" networks of nanomaterials will ensure ions can move across this solid boundary efficiently.

Beyond Lithium: Sodium and Multivalent-Ion Storage:

Lithium is expensive and limited in supply. The future lies in earth-abundant elements like **Sodium (Na), Magnesium (Mg), and Aluminium (Al)**.

i. **The Challenge:** These ions are larger than Lithium and can "*clog*" or break traditional electrodes.
ii. **The Nano Solution: MXenes** and **Expanded Graphene** are perfect candidates for Sodium-ion batteries because their adjustable interlayer spacing (d-spacing) can be "*tuned*" to fit larger ions without damaging the structure.

Smart and Self-Healing Electrodes:

Future electronics (wearables, foldable phones) require batteries that can bend or even repair themselves.

i. **Flexible Nano-mats:** Using **CNT-yarns** or **Graphene-papers** as current collectors allows for batteries that can be folded thousands of times.
ii. **Self-Healing:** Research is exploring nanostructured polymers that can "heal" cracks in the electrode automatically, significantly extending the life of electric vehicle batteries.

Artificial Intelligence (AI) in Nanomaterial Discovery

The "*Trial and Error*" method of lab research is too slow.

i. **Machine Learning:** Future scope involves using AI to predict which **Hybrid Nanocomposite** will have the highest capacity before even stepping into the lab.
ii. **Digital Twins:** Creating a "*Digital Twin*" of a nanostructured electrode to simulate how it will degrade over 10 years of use.

Sustainability: The "Green Nano" Era

As we produce millions of tons of nanomaterials, we must consider the environmental impact.

Recyclability: Developing methods to *"unzip"* or recover **Carbon Nanotubes** and **MXenes** from old batteries.

Green Synthesis: Moving away from toxic chemicals (like Hydrofluoric Acid used for MXenes) toward **bio-inspired synthesis** using plant extracts or water-based chemistry.

© STM Journals 2026. All Rights Reserved

CONCLUSION

The evolution of energy storage technology has reached a critical turning point, shifting away from traditional bulk-material electrodes toward meticulously engineered **nanostructured architectures**. This includes how the transition to **0D, 1D, 2D, and 3D nanomaterials** provides the high surface area and shortened diffusion paths necessary to meet the escalating demands of electric vehicles, portable electronics, and renewable energy grids. Thus, nanostructured electrode materials represent more than just a laboratory innovation; they are the fundamental building blocks of a sustainable, electrified future. As we refine the synthesis of materials like **MXenes** and optimize **all-solid-state systems**, nanotechnology will continue to be the driving force behind safer, faster-charging, and longer-lasting energy solutions that align with modern global energy demands.

REFRENCES

1. Lakshmi, K. S., & Vedhanarayanan, B. (2023). High-performance supercapacitors: A comprehensive review on paradigm shift of conventional energy storage devices. Batteries, 9(4), 202.
2. Yao, Y., Rui, X., Bai, R., Ouyang, Y., Li, G., Zhao, Y., ... & Yu, Y. (2025). Roadmap for next-generation electrochemical energy storage technologies: Secondary batteries and supercapacitors. ACS Nano, 19(34), 30568–30687.
3. Mujumdar, A. S., Barzigar, A., Hosseinalipour, S. M., & Edalatpour, A. (2025). Critical review of drying processes for electrode materials: Bridging fundamentals and advanced manufacturing for energy storage devices. Drying Technology, 43(14), 2042–2067.
4. Ferdous, A. R., Shah, S. S., Shah, S. N. A., Johan, B. A., Al Bari, M. A., & Aziz, M. A. (2024). Transforming waste into wealth: Advanced carbon-based electrodes derived from refinery and coal by-products for next-generation energy storage. Molecules, 29(9), 2081.
5. Admase, A. T., Asrade, E. D., & Fanta, S. W. (2025). A comprehensive review on energy storage materials & technologies: Applications of nanofabrication techniques for enhanced performance and efficiency. Materials for Renewable and Sustainable Energy, 14(3), 56.
6. Xu, R., Du, L., Adekoya, D., Zhang, G., Zhang, S., Sun, S., & Lei, Y. (2021). Well-defined nanostructures for electrochemical energy conversion and storage. Advanced Energy Materials, 11(15), 2001537.
7. Lu, X., Li, S., Li, Y., Wu, F., Wu, C., & Bai, Y. (2024). From lab to application: Challenges and opportunities in achieving fast charging with polyanionic cathodes for sodium-ion batteries. Advanced Materials, 36(36), 2407359.
8. Yu, X., & Manthiram, A. (2021). Sustainable battery materials for next-generation electrical energy storage. Advanced Energy and Sustainability Research, 2(5), 2000102.
9. Khan, Y., Sadia, H., Ali Shah, S. Z., Khan, M. N., Shah, A. A., Ullah, N., ... & Khan, M. I. (2022). Classification, synthetic, and characterization approaches to nanoparticles, and their applications in various fields of nanotechnology: A review. Catalysts, 12(11), 1386.
10. Barhoum, A., García-Betancourt, M. L., Jeevanandam, J., Hussien, E. A., Mekkawy, S. A., Mostafa, M., ... & Bechelany, M. (2022). Review on natural, incidental, bioinspired, and engineered nanomaterials: History, definitions, classifications, synthesis, properties, market, toxicities, risks, and regulations. Nanomaterials, 12(2), 177.
11. Paras, N., Yadav, K., Kumar, P., Teja, D. R., Chakraborty, S., Chakraborty, M., ... & Hang, D. R. (2022). A review on low-dimensional nanomaterials: Nanofabrication, characterization and applications. Nanomaterials, 13(1), 160.
12. Wang, T., Chen, S., & Chen, K. J. (2023). Metal-organic framework composites and their derivatives as efficient electrodes for energy storage applications: Recent progress and future perspectives. The Chemical Record, 23(6), e202300006.
13. Qin, J., Yang, Z., Xing, F., Zhang, L., Zhang, H., & Wu, Z. S. (2023). Two-dimensional mesoporous materials for energy storage and conversion: Current status, chemical synthesis and challenging perspectives. Electrochemical Energy Reviews, 6(1), 9.

© STM Journals 2026. All Rights Reserved

14. Hachem, K., Ansari, M. J., Saleh, R. O., Kzar, H. H., Al-Gazally, M. E., Altimari, U. S., ... & Kianfar, E. (2022). Methods of chemical synthesis in the synthesis of nanomaterial and nanoparticles by the chemical deposition method: A review. BioNanoScience, 12(3), 1032–1057.
15. Jiang, Z., Li, W., Peng, B., Huang, S., & Zhang, X. (2025). Recent advances in nano-engineered thermochemical energy storage materials: Morphologies, characteristics, and performance. Nanomaterials, 15(19), 1476.
16. Dudina, D. V., & Bokhonov, B. B. (2022). Materials development using high-energy ball milling: A review dedicated to the memory of M. A. Korchagin. Journal of Composites Science, 6(7), 188.
17. Balachandran, A., Sreenilayam, S. P., Madanan, K., Thomas, S., & Brabazon, D. (2022). Nanoparticle production via laser ablation synthesis in solution method and printed electronic application—A brief review. Results in Engineering, 16, 100646.
18. Jiang, Z., Li, L., Huang, H., He, W., & Ming, W. (2022). Progress in laser ablation and biological synthesis processes: "Top-down" and "bottom-up" approaches for the green synthesis of Au/Ag nanoparticles. International Journal of Molecular Sciences, 23(23), 14658.
19. Attallah, A. H., Abdulwahid, F. S., Ali, Y. A., & Haider, A. J. (2023). Effect of liquid and laser parameters on fabrication of nanoparticles via pulsed laser ablation in liquid with their applications: A review. Plasmonics, 18(4), 1307–1323.
20. Nandagudi, A., Nagarajarao, S. H., Santosh, M. S., Basavaraja, B. M., Malode, S. J., Mascarenhas, R. J., & Shetti, N. P. (2022). Hydrothermal synthesis of transition metal oxides, transition metal oxide/carbonaceous material nanocomposites for supercapacitor applications. Materials Today Sustainability, 19, 100214.
21. Alabada, R., Kadhim, M. M., Sabri Abbas, Z., Rheima, A. M., Altimari, U. S., Dawood, A. H., ... & Kianfar, E. (2023). Investigation of effective parameters in the production of alumina gel through the sol-gel method. Case Studies in Chemical and Environmental Engineering, 8, 100405.
22. Yin, X. T., Huang, H., Xie, J. L., Dastan, D., Li, J., Liu, Y., ... & Ma, X. G. (2022). High-performance visible-light active Sr-doped porous LaFeO3 semiconductor prepared via sol-gel method. Green Chemistry Letters and Reviews, 15(3), 546–556.
23. Sabzi, M., Mousavi Anijdan, S. H., Shamsodin, M., Farzam, M., Hojjati-Najafabadi, A., Feng, P., ... & Lee, U. (2023). A review on sustainable manufacturing of ceramic-based thin films by chemical vapor deposition (CVD): Reaction kinetics and the deposition mechanisms. Coatings, 13(1), 188.
24. Snyders, R., Hegemann, D., Thiry, D., Zabeida, O., Klemberg-Sapieha, J., & Martinu, L. (2023). Foundations of plasma enhanced chemical vapor deposition of functional coatings. Plasma Sources Science and Technology, 32(7), 074001.
25. Etafa, Y., Elangovan, S., Legesse, K., & Chewaka, M. (2025). Synthesis and fabrication techniques for nanomaterials. In Exploring Nanomaterial Synthesis, Characterization, and Applications (pp. 241–266). IGI Global Scientific Publishing.

© STM Journals 2026. All Rights Reserved