

Design and Implementation of Smart Grocery Packaging System

Sidhant Sanjay Kulkarni^{1,*}, Snehal Arjun Avhad², Pankaj Sanjay Nirgude²,
Hrushikesh Ravindra Patole², Aditya Prakash Wani²

Abstract

The increasing demand for speed, accuracy, and cost efficiency in retail operations has accelerated the adoption of automation technologies in grocery packaging systems. Traditional grocery packaging methods rely heavily on manual labor, which often leads to errors in quantity measurement, inconsistent packaging quality, increased labor costs, and slower processing times. To address these challenges, this work presents the design and implementation of a smart automated grocery packaging system aimed specifically at small and medium-scale retail establishments. The proposed system integrates an Arduino-based microcontroller with infrared (IR) sensors, servo motors, and a user-friendly interface consisting of a keypad and LCD. The system automatically detects the presence of grocery items, controls the dispensing mechanism, and performs accurate packaging operations based on user-defined parameters such as weight or cost. Real-time sensor feedback enables closed-loop control of the dispensing process, ensuring precise and consistent packaging with minimal human intervention. Experimental validation was carried out using common grocery items such as rice, sugar, wheat, and groundnuts. The prototype demonstrated a dispensing accuracy within $\pm 2\%$, significantly outperforming manual packaging methods that typically show variations of $\pm 5\text{--}10\%$. Additionally, the average packaging cycle time was reduced from 10–15 seconds in manual operations to approximately 3.5 seconds using the proposed system. The system also exhibited reliable performance across repeated trials and varying material densities. The modular and scalable design allows the system to be adapted for different packaging capacities and retail requirements. The results indicate that the proposed automated grocery packaging system offers a cost-effective, reliable, and efficient solution for modernizing small-scale retail packaging operations, while improving productivity, reducing labor dependency, and minimizing packaging errors.

Keywords: Arduino microcontroller, automation, error reduction, IR sensors, retail automation, smart grocery packaging

INTRODUCTION

In the present era, automation in the packaging of groceries is rapidly evolving. It mainly aims to enhance efficiency and accuracy and provide low-cost solutions to retail supply chains. Traditional packaging systems largely depend on manual labor, which may lead to human errors and inefficiencies in grocery handling. Consumers demand faster and more reliable services from small-scale businesses; therefore, it is time to adopt automation technologies in this sector. Studies in the automation field focus on improving accuracy, reliability, and user convenience. The microcontroller-based system demonstrated accurate weight measurement and automated dispensing with effective control over packaging [1, 2]. Infrared (IR) and proximity sensors are used to determine the location of an object and regulate

*Author for Correspondence

Sidhant Sanjay Kulkarni

E-mail: kulkarnisidhantmk@sanjivani.org.in

¹Assistant Professor, Department of Mechatronics Engineering, Sanjivani College of Engineering, Kopergaon, Maharashtra, India

²Undergraduate Student, Department of Mechatronics Engineering, Sanjivani College of Engineering, Kopergaon, Maharashtra, India

Received Date: January 24, 2026

Accepted Date: January 29, 2026

Published Date: February 10, 2026

Citation: Sidhant Sanjay Kulkarni, Snehal Arjun Avhad, Pankaj Sanjay Nirgude, Hrushikesh Ravindra Patole, Aditya Prakash Wani. Design and Implementation of smart Grocery Packaging System. Trends in Mechanical Engineering & Technology. 2026; 16(1): 46–52p.

the flow of grocery items in packaging containers [3]. Even with these advancements, many systems require manual calibration and are not user-friendly for operators [4]. The user can input the quantity and cost preferences per the customized requirement using a keypad and LCD for more flexible operations [5]. For better detection and control, some sophisticated systems even integrate machine vision at the cost of complex programming and increased cost [6]. Additionally, commercial dispensing machines facilitate retail automation, especially for bulk product distribution. Nevertheless, they encounter problems, such as clogging, calibration drift, and uneven flow control [7]. Many grocery stores employ manual packaging, leading to increased labor costs, slower processing, and inconsistency in product quantities, resulting in customer dissatisfaction and financial losses [8]. Therefore, it is time to develop a low-cost, precise, and user-friendly automated packaging system, specially designed for small businesses. The goal of this study was to bridge the gap between small-scale retail applicability and advanced packaging automation. The proposed method aims to modernize supermarket packaging in a feasible and scalable manner by creating a simplified, sensor-integrated system that strikes a compromise between performance and affordability. The proposed work fits the latest developments in supply chain management's digital transformation and smart retail [9, 10].

This study proposes an *automated grocery packaging system* that integrates Arduino microcontrollers, infrared (IR) sensors, and motor-driven mechanisms to detect, sort, and distribute grocery items with minimal human intervention. The goal is to improve the packaging speed and accuracy while maintaining system affordability and accessibility for small retail settings. The system efficiently classifies goods and routes them to the appropriate packing units using sensor-based automation, thereby reducing errors and increasing the operational throughput.

RESEARCH METHODOLOGY

The present system was designed and developed using a systematic and iterative approach to achieve enhanced accuracy, low-cost, and a user-friendly interface for the user. The system was designed by following the steps of architectural design, hardware–software integration, development of a prototype module, and validation and comparative performance analysis. Requirement analysis was initially conducted to understand the packaging requirements of small retail stores. The following subsections elaborate on these steps.

System Architecture and Design

After the requirement analysis, the hardware and software architecture were developed. A block diagram of the proposed system is shown in Figure 1. The design consists of microcontrollers as control units, IR sensors for item presence detection, and servo motors for actuating the dispensing nozzles. A user interface, including an LCD and keypad, allows users to enter the weight or cost of the item to be dispensed. The architectural design ensures scalability and modularity for various retail scenarios.

The Arduino IDE was used to program the microcontroller circuitry, which enabled the precise interpretation of the sensor data and servo motor actuation based on the real-time inputs entered by the user. The system can be considered a closed-loop control system that operates in a continuous feedback loop, processing sensor inputs to modify motor movements until predetermined packaging requirements, such as price or weight, are met. The entire process is illustrated in Figure 2.




Figure 1. Block diagram of the automated grocery packaging system.




Figure 2. Flowchart of system operation.

Prototype Implementation

The hardware components were selected by considering the trade-off between cost and performance. The Arduino Uno was selected as the microcontroller unit considering its adaptability, sufficient processing speed, and open-source support. The IR sensor facilitates accurate detection and tracking of items. The nozzle dispensing mechanism was operated precisely using servo motors, whereas an LCD and keypad module offered a simple and intuitive user-input interface. After the architectural design and components were finalized, a functional prototype was assembled and tested on a test bench. A mechanical frame was designed to maintain the sensors and actuators in fixed alignment. Test food items, such as rice, sugar, wheat, and groundnuts, were used to program and calibrate Arduino. During testing, the system responded satisfactorily to user inputs and dispensed food items with an error margin of less than 2%. In contrast to human processes, which take 10–15 s per package, the average packing time for each cycle was approximately 3.5 s. The IR sensors correctly detected the presence of the item and the location of the bag, initiating the dispensing process automatically.


Validation and Comparative Evaluation

The developed prototype was compared with conventional manual methods. The accuracy, speed, cost-effectiveness, and user involvement were compared. The automated system-maintained precision within $\pm 2\%$, whereas human operations showed weight variances of up to 10%. The new technology also provides modular upgradability and decreases reliance on human labor. Table 1 shows the time required for grocery packing for weights of 200 g and 1 kg. For testing wheat, rice, groundnuts, and sugar.

The methodology employed a well-structured and iterative development process, resulting in a prototype that significantly improved the manual grocery packaging process. The successful integration of mechanical, electronic, and software components demonstrates the feasibility of implementing such a system in retail settings.

Table 1. Test results for prototype dispensing

S.N.	Grocery item	Weight	Time (in seconds)
1	Sugar	200 g	2
2	Rice		4
3	Wheat		4
4	Groundnut		6
5	Sugar	1 kg	10
6	Rice		20
7	Wheat		20
8	Groundnut		30

**Figure 3.** Performance metric of the designed system.

RESULTS AND DISCUSSION

The performance of the automated grocery packaging system was evaluated using a combination of simulation and physical prototype testing. The objective of this study was to validate the accuracy, responsiveness, operational efficiency, and usability of the device in both controlled and practical settings. The following subsections summarize the outcomes and key findings of this study.

Simulation Results

A simulation was performed prior to the actual hardware implementation to validate the control logic, sensor interfacing, and motor actuation mechanisms. These components were simulated to study the behavior of the entire system under various operational conditions. In addition, it enabled the design and testing of collision avoidance, flow control during packaging, and customized user-input handling in constrained environments. The simulation results demonstrated that the system could accurately detect the presence of items and provide real-time responses throughout packaging operations. The dispensing mechanism was adjusted to control the input variations, thereby allowing a smooth flow without blockages or misalignment. The system achieved 98% accuracy in weight-based dispensing, demonstrating its feasibility before real-world testing. The chart in Figure 3 shows the performance metrics of the proposed system.

Prototype Testing

After simulation validation, a functional prototype was developed and tested using various grocery items. The system achieved precise dispensing with less than 2% deviation from the actual weight in both the weight- and cost-based modes. The average packaging time was recorded at approximately 3.5 s, which is faster than that of manual methods, which took approximately 10–15 s. Figure 4 depicts the designed setup of the prototype, which integrates IR sensors to facilitate grocery detection, a 16×2 LCD with a keypad interface to provide a user-friendly interface for customized user-input. Figure 5 shows a cylinder view of the item dispensing.



Figure 4. Actual setup of prototype assembly.



Figure 5. Cylinder/nozzle view for item dispensing.

The prototype of the system demonstrated was consistent with the simulated design, showing minimal deviation in terms of dispensing. Different grocery items can be accurately delivered in quantities with less than *2% error margin*, even under repeated usage. During testing, the system exhibited a reliable performance across various grocery types. The flow rate was automatically adjusted based on sensor feedback, helping to maintain accuracy even with inconsistent material densities. The nozzle mechanism functioned well without clogging, even during repeated use.

Comparative Analysis

A comparative evaluation of the proposed system and traditional manual packaging was performed. The designed system showed improvements in various parameters, as shown in Table 2. To provide a clearer comparison, Table 3 summarizes the time and accuracy differences between the manual and automated packaging methods for various items and weights


Figure 6 shows a comparative performance graph for the manual and designed automated systems. The automated system could achieve a dispensing error margin of less than 2%, which is better than the 5%–10% margin recorded in typical manual methods. The significant reduction in packaging time from 10–15 s in the manual method to 3.5 s in the proposed system can boost productivity. In addition, the designed system requires minimal manual supervision compared with manual methods, which require at least two operators, resulting in labor cost savings. Additionally, the system exhibits excellent scalability and customization capabilities, supporting a range of product types to satisfy changing retail needs. These improvements demonstrate how the system's increased speed, precision, and operational efficiency can revolutionize grocery store packing in small businesses.

Table 2. Comparison of manual methods and the proposed system

Parameter	Manual method	Proposed system
Accuracy	$\pm 5\text{--}10\%$	$\pm 2\%$
Average cycle time	10–15 seconds	3.5 seconds
Labor requirement	2 Operators	Minimal supervision
Scalability	Limited	Modular & flexible

Table 3. Summary of time and accuracy for manual versus automated methods.

Grocery item	Weight	Manual time (s)	Automated time (s)	Accuracy (manual)	Accuracy (automated)
Sugar	200 g	10	2	$\pm 8\%$	$\pm 2\%$
Rice	1 kg	25	20	$\pm 10\%$	$\pm 2\%$
Groundnut	200 g	15	6	$\pm 9\%$	$\pm 2\%$

**Figure 6.** Comparative performance graph: manual versus automated system.

Limitations and Future Enhancements

Although the prototype performed well under typical conditions, prolonged testing revealed several drawbacks. Larger or heavier grocery items were difficult to handle owing to the mechanical frame and motor capacity; hence, the system was best suited for small-to medium-sized packages. Furthermore, the accuracy of the IR sensors decreased under low-light conditions, occasionally resulting in slight detection errors. The real-time performance was affected by frequent adjustments to the input parameters, which caused minor delays in data processing and dispensing response. Additionally, the endurance of the system for long-term industrial use without structural improvements is limited by the use of lightweight materials, notwithstanding their effectiveness for proof-of-concept.

Several potential improvements are suggested to overcome the existing constraints and increase the system's capabilities. Heavy weights can be handled by strengthening the dispensing mechanism using strong structural materials and high-torque motors. Furthermore, AI-assisted control algorithms facilitate self-calibration and allow for quicker reactions to dynamic input changes.

Scalability and Adaptability in Real-World Conditions

The proposed system demonstrates high scalability, which is attributable to its modular hardware and programmable firmware. Each component, including the dispensing units, motor controls, and sensor interfaces, can be configured individually or grouped into parallel configurations. This design allows the system to support both small and mid-sized retail setups with minimal architectural alterations. A

key feature of this system is its ability to adapt to various packaging requirements. By enabling input-based adjustments in parameters such as weight or cost, the system dynamically modifies the dispensing duration and servomotor angles. This flexibility ensures compatibility with different container sizes and customer preferences. In practical implementations, the system can be expanded by incorporating multiple dispensing units, all of which are coordinated through a single microcontroller interface. This expansion supports a higher throughput while retaining precision in item measurement and delivery. To address the variability in flow rates encountered in different grocery products, real-time feedback from infrared (IR) sensors was utilized. Products with fine textures, such as rice and sugar, are dispensed more rapidly than heavier or clumping items, such as groundnuts. The dispensing mechanism accounts for these differences without the need for frequent recalibration. Additionally, the system can handle diverse item types. During prototype testing, it maintained a stable performance when operating with both granular and coarse products. The use of optimized nozzles and preprogrammed material profiles ensured continuous operation without clogging or flow disruption. Overall, the structural modularity and intelligent control mechanisms of the system contribute to its robustness and flexibility. It is well-suited for deployment in real-world environments, where varying product types, packaging demands, and operational scales are common.

CONCLUSION

This study demonstrates an automated grocery packaging system that efficiently and precisely automates the processes of measuring, packaging, and dispensing grocery items with minimal human intervention. The system utilizes hardware components, such as an Arduino Uno microcontroller, servo motors, IR sensors, an LCD, and a keypad interface, to ensure accurate weight measurement and efficient packaging in small-to-medium-sized grocery stores. The system is appropriate for various retail and packaging scenarios because of its user-input-based dispensing mechanism, which allows variable operations based on the amount or cost. Compared with manual methods, the experimental results show significant improvements in speed, accuracy, and consistency, providing a viable and economical option, particularly for small-scale merchants. Even if the system performs well, future advancements might concentrate on adding AI-driven inventory management, which could improve the system's efficiency and flexibility with sophisticated weight measurements. With these developments, the proposed solution can revolutionize the retail packaging industry by improving overall operational efficiency, decreasing labor costs, and increasing precision.

REFERENCES

1. Sharma P, Gupta A. Automation in retail packaging: Current trends and future directions. *Int J Mechatron Syst.* 2021;9(1):15–23.
2. Abdullah ZW, Dong Y. Recent advances and perspectives on starch nanocomposites for packaging applications. *J Mater Sci.* 2018;53(22):15319-15339. doi:10.1007/s10853-018-2613-9.
3. Tan Y, Li H. Infrared sensor applications in automated packaging. *Sens Appl.* 2019;11(4):210–218.
4. Kumar R, Patel S. Review on automated grocery dispensers: Challenges and opportunities. *Autom Retail.* 2020;6(2):33–41.
5. Ali M, Singh D. User interfaces for embedded packaging devices. *Adv Smart Syst.* 2022;3(1):5–72.
6. Altaf U, Kanojia V, Rouf A. Novel packaging technology for food industry. *J Pharmacogn Phytochem.* 2018;7(1):1618-1625.
7. Kwon J, Lee H. Design of bulk dispensing machines: A comparative study. *J Ind Autom.* 2021;14(3):89–95.
8. Desai T, Mehta K. Impact of manual errors on grocery packaging accuracy. *Retail Technol Rev.* 2019;7(2):58–64.
9. Babu PJ. Nanotechnology mediated intelligent and improved food packaging. *Int Nano Lett.* 2022;12(1):1-14. doi:10.1007/s40089-021-00348-8.
10. Roy P, Saha A. Internet of Things in retail supply chains: A technological overview. *J Emerg Retail Tech.* 2023;2(1):12–19.