

A Review on Automatic Railway Gate Control System

Ravi Patil¹, Radhika Nikam², Shravani Pawar³, S.R. Takale^{4,*}

Abstract

Railway transportation is one of the most efficient and widely used modes of transport; however, safety at level crossings remains a critical issue, especially at unmanned or manually operated gates. A significant number of accidents happen as a result of human carelessness, insufficient coordination, and postponed gate operations. To address these issues, the Automatic Railway Gate Control System has been created as a viable solution to improve safety and minimize human involvement. An overview of the several methods and tools utilized in automated railway gate control systems is given in this study. The fundamental objective of these systems is to automate the opening and closing of railway gates by detecting the arrival and departure of trains. Different detection methods, such as infrared (IR) sensors, ultrasonic sensors, and pressure-based systems, are commonly used due to their simplicity and cost-effectiveness. Additionally, advanced approaches using RFID and GPS technologies provide more accurate train detection and real-time tracking capabilities. Microcontrollers and programmable logic controllers (PLCs) are widely used to process input signals from sensors and execute control actions for gate operation. These embedded systems ensure timely and reliable functioning of the gate mechanism. In recent years, the incorporation of Internet of Things (IoT) technology has significantly enhanced the efficiency of railway gate systems by facilitating real-time monitoring, remote access, and data communication. Wireless technologies such as GSM, Zigbee, and RF modules also play an important role in enhancing system flexibility and scalability. Safety features are a key component of automatic railway gate control systems. Modern systems incorporate fail-safe mechanisms, obstacle detection sensors, and warning signals such as alarms and visual indicators to alert road users and train operators. Proper synchronization between railway signaling systems and gate operation is essential to prevent accidents and ensure smooth traffic flow. This review also highlights the advantages and limitations of existing systems, including issues related to cost, maintenance, environmental conditions, and reliability. Additionally, it addresses forthcoming trends including the utilization of artificial intelligence, machine learning, and computer vision to enhance detection precision and system efficacy. In summary, automated railway gate control systems are crucial for enhancing railway safety and operational effectiveness. By decreasing reliance on manual operations and integrating advanced technologies, these systems greatly reduce the likelihood of accidents and aid in the advancement of intelligent transportation systems.

Keywords: Automatic level crossing gate, IR sensor-based gate control, RFID-based railway automation, IoT-enabled railway system, obstacle detection system

*Author for Correspondence

S.R. Takale

E-mail: swapnil.takale@sknscoe.ac.in

¹⁻³Students, Department of Electronics and Telecommunication Engineering, SKN Sinhgad College of Engineering, Pandharpur, Maharashtra, India

⁴Assistant Professor, Department of Electronics and Telecommunication Engineering, SKN Sinhgad College of Engineering, Pandharpur, Maharashtra, India

Receiving Date: May 05, 2026

Accepted Date: June 30, 2026

Published Date: July 07, 2026

Citation: Ravi Patil, Radhika Nikam, Shravani Pawar, S.R. Takale. A Review on Automatic Railway Gate Control System. Journal of Control & Instrumentation. 2026; 17(2): 1–7p.

INTRODUCTION

Railway transportation is one of the most significant and commonly utilized forms of transport owing to its cost-effectiveness, efficiency, and capacity to transport substantial quantities of passengers and goods across extensive distances. Despite its advantages, railway safety remains a significant concern, particularly at level crossings where railway tracks intersect with roadways [1–5]. These crossings are often vulnerable points in the

transportation network, and a considerable number of accidents occur owing to human error, negligence, or lack of proper coordination between the railway and road traffic systems. Unmanned railway crossings, in particular, pose a serious risk as they rely entirely on road users to make safe decisions without any automated warning or control mechanisms [6–10].

Traditionally, railway gates at level crossings are operated manually by gatekeepers or controlled using semi-automatic systems. Such methods are not only labor-intensive but also prone to delays and errors, which can lead to severe accidents, loss of life, and property damage. In many regions, especially in developing areas, the absence of reliable infrastructure and trained personnel further increases the likelihood of accidents at railway crossings. Therefore, there is a critical need for a more efficient, reliable, and automated solution to ensure safety and smooth operation at these intersections [11–14].

The Automatic Railway Gate Control System has emerged as a viable solution to address these issues. This system is intended to automate the process of opening and closing railway gates in response to the detection of incoming or outgoing trains. By eliminating the need for human intervention, it significantly reduces the chances of errors and enhances overall safety. The system typically uses sensors, such as infrared (IR), ultrasonic, or pressure sensors, to detect train movement. More advanced implementations incorporate technologies such as RFID and GPS to accurately track train location and timing [15–20].

In addition to detection mechanisms, embedded systems, such as microcontrollers and programmable logic controllers (PLCs), are used to process sensor data and control gate operations. These systems ensure that the gates close well in advance of the train arrival and reopen promptly after the train passes [21–25]. Furthermore, the integration of Internet of Things (IoT) technology has enabled real-time monitoring and remote control of railway gate systems, thereby improving their efficiency and responsiveness. Communication technologies such as GSM, Zigbee, and radio frequency (RF) modules have also been employed to facilitate data transmission and system coordination [26–28].

Safety features are essential in automatic railway gate control systems. Modern designs incorporate obstacle detection mechanisms, warning alarms, and visual signals to alert road users and prevent such accidents. Fail-safe operations have been established to guarantee that the system operates effectively even during instances of component failure or power interruption. The appropriate synchronization of railway signals with gate control systems is essential for ensuring a seamless flow of traffic and avoiding congestion. In summary, the Automatic Railway Gate Control System signifies major progress in the realms of railway safety and automation. By leveraging modern technologies and intelligent control strategies, it offers a reliable and efficient solution for reducing accidents at railway crossings. As technology continues to evolve, further improvements and innovations in this field are expected to contribute to the development of safer and smarter transportation systems.

LITERATURE REVIEW

Table 1 presents a comparative analysis of various automatic railway gate control systems based on their system architecture, implementation cost, ease of deployment, operational performance, user experience, and limitations. This comparison highlights the evolution of railway gate automation technologies and their suitability for different operational environments.

PLC-based railway gate control systems offer high reliability and precise control by utilizing programmable logic controllers, sensors, and motor drives. Although these systems provide excellent performance and dependable operation, they involve relatively high installation costs and require trained personnel for programming and maintenance purposes. Sensor-based automatic gate control systems use ultrasonic or similar sensors with microcontrollers to detect approaching trains. These systems are economical and simple to implement but may experience reduced accuracy under adverse weather conditions or when the sensors become contaminated.

Arduino-based railway gate controllers provide an affordable and user-friendly solution by integrating microcontrollers with IR or ultrasonic sensors and motor-actuators. Although suitable for academic and prototype applications, their long-term reliability in harsh outdoor environments is limited. IoT-enabled systems enhance functionality by incorporating wireless communication and cloud-based monitoring, thereby enabling remote supervision and data analysis. However, their performance depends on stable Internet connectivity.

Wireless communication-based systems improve train detection through dedicated transmitter and receiver modules, thereby reducing the need for extensive wiring. However, electromagnetic interference may occasionally affect communication reliability. Vision-based gate control systems employ cameras and image-processing platforms, such as Raspberry Pi, to identify approaching trains and to monitor obstacles. These systems achieve high detection accuracy but require adequate lighting conditions and greater computational resources to operate.

Table 1. Comparative analysis of automatic railway gate control systems.

Project/ paper	System architecture	Cost	Ease of implementation	Performance	User experience	Limitations
PLC-based Railway Level crossing gate control	Uses PLC with sensors and motor drives. PLC handles logic for gate movement based on input triggers	Moderate to high	Medium	High	Good	Higher hardware cost, needs skilled personnel for programming and maintenance
Sensor-based Automatic control of railway Gates	Ultrasonic sensors detect incoming trains, microcontroller processes sensor input to control gate motors	Low to medium	Easy	Good	Fair	Sensors can false detect in bad weather or if dirty, limited long-range detection
Arduino-based Automatic Railway Gate Control and Obstacle Detection System	Arduino microcontroller receives signals from IR/ultrasonic sensors, operates gate servos or motors, may include LCD	Low	Easy	Medium	Better	Not industrial-strength, limited environmental tolerance, needs precise sensor placement
IoT-based Automatic Railway Gate Control System	Sensors + Microcontroller + Wi-Fi/ Internet + Cloud dashboard	Low-Medium	Medium	Good	Better	Dependent on internet connectivity
Wireless Communication-based Train Detection System	Train module + Wireless receiver+ Controller + Actuator	Medium	Medium	Good	Good	Signal interference possible
Vision/CV-based Automatic Gate Controller	Cameras + Image Processing unit (e.g., Raspberry Pi)	Medium	Medium-high	High	High	Needs good lighting and clear view
GPS/GSM-based Gate Control System	GPS on train + GSM messaging + Gate controller	Medium	Medium	Medium	Good	GPS errors in tunnels/dense areas
Solar-powered Automatic Railway Gate Control	Solar panels + Battery + Controller + Sensors	Medium	Medium	Reliable	Good	Higher initial cost for solar installation

GPS/GSM-based systems determine the train location using satellite positioning and cellular communication, allowing remote gate operation. However, their effectiveness may decrease in tunnels or areas with weak GPS signals. Solar-powered railway gate systems utilize renewable energy sources to improve sustainability and maintain operations in remote locations. Despite their higher initial installation costs, they reduce long-term energy consumption and support environmentally friendly railway infrastructure.

PROPOSED METHODOLOGY

The suggested Automatic Railway Gate Control System aims to improve safety and efficiency at railway level crossings by removing the need for manual intervention and automating gate operations through the use of embedded systems and sensor technology. The system primarily consists of sensors, a microcontroller unit, a gate-driving mechanism, and alerting devices. Infrared (IR) or ultrasonic sensors are strategically installed on both sides of the railway track at specific distances to detect the presence and movement of approaching trains. These sensors continuously monitor the track and send real-time signals whenever a train enters the detection zone of the track.

When the approaching train is detected by the first sensor, the signal is transmitted to the microcontroller unit, which acts as the central processing element of the system. The microcontroller is programmed to interpret the sensor inputs and execute appropriate control actions based on predefined logic. Upon receiving the signal, the microcontroller immediately initiates the gate-closing sequence to ensure that the railway crossing is secured before the train reaches the intersection. A motor driver circuit is used to control the gate barrier, allowing smooth and reliable opening and closing.

Simultaneously, the system activates warning indicators, such as red signal lights, buzzers, and alarm systems, to alert road users of the approaching train. As the train continues to move along the track, it eventually passes the first detection sensor and reaches the second sensor, which is placed after the crossing point. The second sensor plays a crucial role in confirming the complete passage of the train.

The controller processes this input and verifies that no train is present in the crossing area. After successful verification, the microcontroller triggers the gate-opening mechanism, allowing normal road traffic to resume. This automated process ensures smooth coordination between train movement and road traffic without requiring supervision.

To enhance the safety and reliability of the system, an obstacle detection module can be integrated near the railway crossings. This module ensures that no vehicle or object is present while the gate is closing or opening, thereby preventing potential accidents from occurring. In addition, fail-safe mechanisms are implemented to ensure that the system remains operational even during partial failures or power interruptions.




Figure 1. Block diagram of automatic railway gate control system.

Furthermore, modern advancements, such as Internet of Things (IoT) technology, can be integrated into the system to enable remote monitoring and control. This allows railway authorities to track the gate status in real time through cloud platforms or mobile applications. Wireless communication modules, such as GSM, RF, and Zigbee, can also be used to transmit alerts and system updates over long distances.

Overall, the proposed methodology ensures a reliable, efficient, and automated approach to railway-gate control. By combining sensor technology, embedded systems, and intelligent control logic, the system significantly reduces human dependency, minimizes accident risks, and improves the overall safety of railway-level crossings. Figure 1 shows a block diagram of the automatic railway gate control system.

Power Supply

- It delivers the essential electrical power to every component within the circuit (Arduino, sensor, and servo motor).
- Usually, a 5V DC power supply (such as a battery or adapter) is used to operate the system.
- Ensures stable and regulated voltage to prevent damage to the components.

Arduino Uno

- The main controller or brain of the system.
- It receives input signals from the ultrasonic sensor and makes decisions based on the programmed instructions.
- It sends control signals to the servo motor to open or close the gate.
- Acts as the interface between input (sensor) and output (motor).

Ultrasonic Sensor

- Detects the presence and distance of an object (such as a vehicle or person) in front of the gate.
- It works by emitting ultrasonic waves and measuring the time delay of the echo that bounces back from the object.
- The distance information is sent to the Arduino, which then decides whether to open or close the gate.

Servo Motor

- The actuator that physically moves the gate.
- Receives position control signals from the Arduino.
- Based on those signals, it rotates to a specific angle for example:
- If an object is detected (vehicle approaching), the servo rotates to open the gate.
- If no object is detected: servo rotates back to close the gate.

Gate

- The mechanical barrier that controls entry or exit.
- It opens or closes based on the movement of the servo motor.
- Connected mechanically to the servo arm or linkage that drives its movement.

CONCLUSION

The Automatic Railway Gate Control System is an effective and reliable solution for improving safety at railway level crossings by minimizing human intervention. The manual operation of railway gates is highly prone to errors, delays, and negligence, which often leads to serious accidents and loss of life. By automating the gate control process, the system ensures the timely opening and closing of gates based on real-time train detection, thereby significantly reducing the risk of collisions between trains, vehicles, and pedestrians.

In addition, the use of obstacle detection further enhances safety by identifying any object, vehicle, or animal present on the track during gate operation. This is especially beneficial in rural and forest areas, where wildlife crossings are common and accidents are more frequent. The system also improves traffic management by ensuring smooth and uninterrupted coordination between rail and road transport.

Furthermore, the proposed system reduces the dependency on human operators, thereby eliminating the possibility of human error and increasing overall reliability. It can also be enhanced using modern technologies such as the Internet of Things, wireless communication, and advanced sensing techniques for real-time monitoring and improved performance.

However, despite its advantages, the system has certain limitations, such as sensor dependency and possible false detection under adverse environmental conditions.

It not only helps prevent accidents but also contributes to the development of smart and automated railway infrastructure, making transportation safer, smarter, and more efficient.

REFERENCES

1. Sayanna M, Pranathi B, Gowthami A, Sindhu V, Ganesh C. A new innovative and effective system for trains and railway stations for auto announcements of trains, power saving and auto railway gate control. *Int J Data Sci IoT Manag Syst.* 2026;5(2):476-89.
2. Adekeye DL, Saleh I, Akinseli YE. Design and implementation of an automatic gate for cars at railway crossings. *FUDMA J Eng Technol.* 2025;1(2):208-19.
3. Pawar MP, Neethupriya A, Srinath DG, Ratnamala MS, Kiran BS, Rao SV. Intelligent train engine to avoid accidents and controlling railway gate automatically. *Int J Data Sci IoT Manag Syst.* 2026;5(2):432-45.
4. Pwint HN, Tun ZM, Tun HM. Automatic railway gate control system using microcontroller. *Int J Sci Eng Technol Res.* 2014 May;3(5):1547-1551.
5. Ilampiray P, Deepak K, Santhosh MD, Kishore S. Automated railway gate control system using Arduino and ultrasonic sensors. *J Phys Conf Ser.* 2021;1916(1):012081.
6. Rajendran MP, Ramaswamy K, Varadharajan V, Rajendran J, Thangavel M, Kumar V, et al. Bluetooth controlled robot with ultrasonic object detection using Arduino and L293D driver. *AIP Conf Proc.* 2025;3306(1):060038.
7. Yayla R, Üçgün H, Korkmaz OA. An embedded computer vision approach to environment modeling and local path planning in autonomous mobile robots. *Comput Model Eng Sci.* 2025;145(3):4055.
8. Swami S, Singh R, Gehlot A, Iqbal MI, Sharma SD, Kumar D, et al. Vision-based approach for human motion detection and smart appliance control. *IAES Int J Robot Autom.* 2024;13(4):445.
9. Ahmed Amin A, Mubarak A, Manzoor HU. Design of intelligent vehicular and sensor communication network: a comprehensive survey. *Syst Sci Control Eng.* 2025;13(1):2529187.
10. Rambabu K, Dubey S, Reddy BS, Ravuri V, Ruthumani J, Saipriya K. Arduino controlled radar guided defence system for detecting and tracking threats. In: *Recent Trends in VLSI and Semiconductor Packaging*. Boca Raton (FL): CRC Press; 2025. p. 141-8.
11. Shelke D, Pawar P, Tate P, Shinde P, Mali AS. Trends and technologies in obstacle avoidance systems based on Arduino. *Int J Adv Res Sci Commun Technol.* 2025;5(4):440-455. doi:10.48175/IJAR SCT-29427.
12. Kumar KP, Al-Rubaie YB, Allassedi Z, Bavireddi V, Srikar D, Reddy R. IoT based advanced security system in military for identification of trespassers using ultrasonic radar. In: *Proceedings of the 2024 International Conference on Augmented Reality, Intelligent Systems, and Industrial Automation (ARIIA)*; 2024 Dec 20-21; Manipal, India. 2024. p. 1-4. doi:10.1109/ARIIA63345.2024.11051534.
13. Mulani AO, Mane PB. Watermarking and cryptography based image authentication on reconfigurable platform. *Bull Electr Eng Inform.* 2017;6(2):181-7.

14. Raad MW, Deriche M, Sheltami T. An IoT-based school bus and vehicle tracking system using RFID technology and mobile data networks. *Arab J Sci Eng*. 2021;46(4):3087-97.
15. Brintha NC, Tarun CVP, Abhishikth L, Rao BPK, Reddy MT. Smart railway crossing surveillance system. In: *Proceedings of the 2022 International Conference on Computing, Communication, Security and Intelligent Systems (IC3SIS)*; 2022 Jun 23-24; Kochi, India. 2022. p. 1-5. doi:10.1109/IC3SIS54991.2022.9885699.
16. Patale JP, Jagdale AB, Mulani AO, Pise A. A systematic survey on estimation of electrical vehicle. *J Electron Comput Netw Appl Math*. 2023;3(1):1-6.
17. Kambale A. Home automation using Google Assistant. *UGC Care approved journal*. 2023;32(1):1071-7.
18. Kolhe ML, Karande KJ, Deshmukh SG, editors. *Artificial intelligence, Internet of Things (IoT) and smart materials for energy applications*. Boca Raton (FL): CRC Press; 2022.
19. Pol DR, Mulani AO, Bhalerao M. Cloud based memory efficient biometric attendance system using face recognition. *Stoch Model Appl*. 2021;25(2):403-16.
20. Mali AS, Ghadge SK, Adat AS, Karande SV. Intelligent medication management system. *IJSRD Int J Sci Res Dev*. 2024;12(3):125-127.
21. Saha G, Shahrin F, Khan FH, Meshkat MM, Azad AA. Smart IoT-driven precision agriculture: land mapping, crop prediction, and irrigation system. *PLoS One*. 2025;20(3):e0319268.
22. Modi S, Misal V, Kulkarni S, Mali AS. Hydroponic farming monitoring system: automated system to monitor and control nutrient and pH levels. *J Microcontroller Eng Appl*. 2025;12(3):11-6.
23. Gangonda S, Mukherji P. Speech processing for Marathi numeral recognition using MFCC & DTW features. *Int J Eng Res Appl*. 2012 Mar. p. 118-22.
24. Anandakumar H, Arulmurugan R, Roshini A. Intelligent vehicle system problems and future impacts for transport guidelines. In: *Proceedings of the 2019 International Conference on Smart Systems and Inventive Technology (ICSSIT)*; 2019 Nov 27-29; Tirunelveli, India. 2019. p. 1-5. doi:10.1109/ICSSIT46314.2019.8987831.
25. Sharada KA, Kathiravan A, Mannam P, Akila D, Kumar BS, Godase VV. Advanced neural network models for optimal energy management in microgrids with integrated electric vehicles. In: *Proceedings of the 2025 5th International Conference on Trends in Material Science and Inventive Materials (ICTMIM)*; 2025 Apr 18-19; Kanyakumari, India. 2025. p. 1869-1874. doi:10.1109/ICTMIM65579.2025.10988248.
26. Salunkhe A, Pawar V, Pise P, Mule S, Survase A, Godase V, et al. A review on real-time RFID-based smart attendance systems for efficient record management. *Adv Res Analog Digit Commun*. 2025;2(2):32-46.
27. Gangwar AK, Sarojwal A, Singh PP. A study and solution for unmanned railway crossings with complete automation. In: *Proceedings of the 2024 13th International Conference on System Modeling & Advancement in Research Trends (SMART)*; 2024 Dec 6-7; Moradabad, India. 2024. p. 820-824. doi:10.1109/SMART63812.2024.10882235.
28. Zade MM, Mukane DS. Enhancement of image with the help of switching median filter. In: *National Conference on Emerging Trends in Electronics & Telecommunication Engineering (NCET)*; 2013 Dec; SVERI's College of Engineering, Pandharpur; 2013.