

Piezoelectricity for Power Generation

Rohit Kushwaha^{1,*}, Rachit Srivastava²

Abstract

Undeniably, piezoelectric materials are an exciting possibility for serving as a workable energy source; the question is whether technologies at this point in their development are ready for wide-scale application. This requires considering their value in the real context of modern urban environments and ecological conditions. A critical literature review has been carried out in this paper for the identification of the most successful piezoelectric generation techniques that have been utilized to date. Comparing these various methods with respect to their energy output and socio-economic impact provides a clearer understanding of the specific hurdles and advantages involved. The overall findings indicate the practical, positive role that the implementation of piezoelectric systems could play in the support of global power generation. A promising family of energy harvesting devices that can transform ambient mechanical energy into usable electrical power is represented by piezoelectric nanogenerators (PENGs). These systems provide a sustainable substitute for traditional batteries by taking advantage of the piezoelectric effect at the microscale and nanoscale, especially for distributed and low-power electronic applications. The development of piezoelectric materials and device architectures that have greatly increased mechanical flexibility, long-term durability, and energy conversion efficiency is examined in this article. The focus is on nanostructured materials that have shown improved electromechanical coupling and scalability, such as zinc oxide nanowires, lead zirconate titanate, and newly developed lead-free piezoelectric composites. Additionally covered is the integration of PENGs with power management circuits and energy storage devices, emphasizing methods for output stabilization and continuous operation. Optimized piezoelectric nanogenerators can capture energy from human motion, vibrations, and ambient sources to power portable electronics and sensors, according to recent experimental demonstrations. Notwithstanding these developments, problems with material toxicity, manufacturing costs, and system dependability still exist. In order to move piezoelectric power generation from laboratory research to broad commercial and industrial applications, it will be essential to address these challenges through creative material design and large-scale manufacturing procedures.

Keywords: Power generation, piezoelectricity, energy collector, piezoelectric slats, piezoelectric breakwater

*Author for Correspondence

Rohit Kushwaha

E-mail: rohitkush199@gmail.com

¹Student, Department of Electrical Engineering, Bansal Institute of Engineering and Technology Lucknow, Uttar Pradesh, India

²Assistant Professor, Department of Electrical Engineering, Bansal Institute of Engineering and Technology Lucknow, Uttar Pradesh, India

Received- December 11, 2025

Accepted- December 13, 2025

Published- December 22, 2025

Citation: Rohit Kushwaha, Rachit Srivastava. Piezoelectricity: For Power Generation. International Journal of Electro-Mechanics and Material Behavior. 2025; 3(2): 1–5p.

INTRODUCTION

With increasing densification and the continued rise in energy usage, we must look to a future where upgrading our current infrastructure is a standard practice to create intelligent, self-sustaining urban environments. One potential path toward this objective is “energy harvesting,” as discussed by Priya and Inman. Essentially, this means capturing clean, free residual energy from our environment to supplement our power needs [1–5]. Unfortunately, turning this into a practical reality is easier said than done; the expected rise in energy demand calls for heavy research and development into newer forms

of generating power. This leads to the intriguing question: Is it possible that daily commutes, afternoon strolls through the park, or even waves within our oceans will someday be able to power our cities?

This idea is based on the principle of piezoelectricity, which was discovered by the Curie brothers as far back as 1880. Although this technology is ancient, its applications have changed considerably. Piezoelectricity refers to the capability of certain materials to produce an electric voltage when mechanical pressure is applied. Modern research is currently finding a wide range of uses for this principle, from pressure-sensitive bricks on pedestrian sidewalks to sensors embedded in railways and roads, and further to specialized breakwaters in littoral areas. Current literature indicates that piezoelectric materials may play an important role in the future generation of sustainable power [6–10].

In this context, the present study intends to analyze these energy harvesting methodologies and their socio-economic implications. We want to see how piezoelectric solutions can contribute to the rising energy matrix without changing the physical structure of the urban environment. For this reason, this study compares the different methodologies for energy production and evaluates the practicality of production with respect to different energy parameters. This paper is organized as follows: In the first section, a reference framework for piezoelectric energy collection is presented, followed by the results of our review. Conclusions and broader implications are discussed, hoping that this may constitute a stimulus for stakeholders in the productive sector to invest in emerging technologies compatible with urban development and citizens' needs.

FRAMEWORK AND PROPOSAL FOR PIEZOELECTRICITY

The next section describes the major techniques utilized in harnessing piezoelectric materials for energy support, giving equal attention to their specific strengths and weaknesses. In addition to typical techniques, we examine unique case studies and innovative proposals in the Table 1. This is followed immediately by a critical assessment of the broader picture: consideration of the environmental footprint and the economic viability of the technologies considered. The paper concludes by integrating these findings into a specific proposition regarding the future of piezoelectric power generation.

Table 1. Comparative generation capacity.

Generation method	Energy production	Place of harvest	Source
Piezoelectric tiles	27 kWh/day	Macquarie University, Sydney, Australia	[1]
Piezoelectric pavement	840 kWh/day	Avenida Boyacá and Calle 17, Bogotá, Colombia	[2]
Piezoelectric railways	2880 kWh/day	Israel	[3]
Piezoelectric breakwaters	4 kWh/day	Cantabria, Santander, Spain	[4]

PIEZOELECTRIC SLATES

Reflects the idea of a “smart” floor tile that acts as a small power plant, captivating in the simple gestures of walking and turning them into usable electricity. Such a system enables micro-power generation owing to the kinetic energy of passersby being converted into electrical energy using piezoelectric materials. In most studies, scientists divide mechanics into two ways: “hitting” and “vibrating.” Although the “hitting” method involves modules receiving direct impact loads, the “vibration” method is considered more practical for implementation on a larger scale. Because it can bear superficial loads better, the vibration method offers better durability and provides significant power when distributed over larger surface areas.

Considering that human mobility is a constant, high-traffic environment, such as crosswalks, office lobbies, shopping malls, and nightclubs, are ideal settings to capture this energy. This provides a uniquely reliable path to clean energy, as long as people move from one place to another, the “raw material” of this power source is virtually guaranteed.

PIEZOELECTRIC ROADWAY AS ENERGY COLLECTOR BY ROAD TRAFFIC

The most promising application is the “piezoelectric pathway,” in which harvesting devices are embedded directly beneath asphalt. These systems capture the pressure and vibrations exerted by moving vehicles and convert the mechanical stress to electric power. Due to the nature of this energy production, coming in irregular pulses, system-specific circuitry is needed for rectification and transformation to make it into stable, storable electricity.

This technology fully corresponds to the global need to extend the road network as car fleets continue to grow. As the former Assemblyman Mike Gatto mentioned in regard to California, it makes sense to capture the renewable energy “right beneath our tires” rather than wasting it. This idea has not remained in the realm of theory, and special sections of roads have already begun testing this technology in countries such as Israel, Japan, the United States, and Colombia.

This application is particularly compelling because of its dual utility. Beyond generating significant power, particularly when triggered by heavy trucks, the piezoelectric layer acts as a smart sensor, collecting valuable data on vehicle speed, weight, and traffic frequency. Research indicates that even short stretches, such as one kilometer of roads, possess a high generation capacity. On routes dominated by heavy freight, the energy potential is sufficiently high that the system can theoretically achieve grid independence and eventually recover its own installation costs. Thus, this brings us to our second proposition: future road design, particularly for heavy traffic corridors, should prioritize the integration of piezoelectric pavements to maximize power generation.

RAILWAYS MODIFIED WITH PIEZOELECTRIC DEVICES

The use of train tracks to generate electricity is an extension of the idea of piezoelectric pavements used on roads. The benefit of applying this technology to railways is that the pressure from trains is consistently applied at the same points, making the energy capture more reliable. Piezoelectric devices placed in the joints of rails can convert this mechanical stress into usable electricity, which can then be directed to power trains, operate railway signals, or even feed into the main electrical grid. Studies suggest that the movement of trains could produce approximately 120 kWh of clean energy while also providing valuable data such as train speed, weight, and wheel count. Because trains naturally create vibrations and pressure along tracks, this system can support self-sustaining railway signals and, in the case of electric trains, reduce their dependence on the grid. Thus, adapting piezoelectric devices for railways offers a promising method of harvesting energy to support power generation (Figure 1).




Figure 1. Schematic view.

PIEZOELECTRIC BREAKWATER

Wave energy signifies a huge and clean source of power that can be achieved using piezoelectric devices. The immense power of ocean waves presents a huge opportunity for power generation, as the

seas cover nearly 70% of our planet's surface. A key technology for this involves the placement of devices on offshore buoys or floating platforms. For these systems to be cost-effective, they must be developed and applied on a large and profitable scale. A major benefit of these systems is that they cause minimal disruption to marine life. The construction itself can serve additional drives, such as holding direction-finding sensors. This massive unused energy source provides a significant opportunity for coastal areas that now struggle with power reliability, offering a chance to reduce the cost of building substructures while supplying renewable and environmentally friendly electricity.

RESEARCH METHODOLOGY

To meet the objectives of this study, a complete review of the existing literature was conducted following the framework suggested by earlier investigators. The focus was on analyzing publications related to piezoelectricity as a means of supporting power generation, while placing the discussion within a global context.

For data collection in this study, we first focused on primary sources retrieved from respected academic databases, such as ScienceDirect, JSTOR, and EBSCO. We also utilized secondary sources, such as Google Scholar, ResearchGate, and Academia, and in some limited cases, we directly reached the authors for information. Our literature review covered publications from 1994 to 2019, with a special emphasis on research directly concerning energy harvesting using piezoelectric devices. The paper year and language primarily concentrate on works in English and Spanish.

This initial sweep brought up 51 documents, including journal articles, theses, and books. We excluded 14 of these based on a lack of relevance. In the second stage, we closely examined the abstracts of the remaining papers, which led to the removal of seven additional papers. This meticulous process yielded a final pool of 34 highly relevant studies that were included in our review. Our search strategy was guided by specific keywords such as piezoelectricity, power generation, and energy harvesting. To ensure that the information was as current as possible, we preferred documents published within the last five years of the search period, as they offered the most up-to-date insights available in the field (Table 1).

RESULTS

In the early stage of the appraisal, 51 papers were included. After applying the selection criteria, this number was reduced to 34 documents for deeper analysis. The useful sources include studies on general piezoelectricity, piezoelectric tiles, piezoelectric pavements, wave-based applications, environmental aspects, economic considerations, and solar support systems. However, several documents were excluded, such as those focusing on specific material types, operating frequencies, microcircuits, crystal structures, wind generation, and microgeneration.

After examining the content of the 30 most relevant documents from stage two, the study was able to identify key insights into the strengths and limitations of different piezoelectric energy harvesting methods.

Among the methods reviewed, the railways have the highest potential. Their energy generation capacity was approximately 343% greater than that of the piezoelectric pavements. To put this into perspective, the electricity produced by piezoelectric railways could power approximately 2,400 sodium lamps for 12 h a day over an entire month. This highlights the potential of piezoelectricity as a supplemental energy source in areas where these systems can be applied.

Each method has its own strengths, depending on the environment. For example, piezoelectric pavements can generate more than enough electricity to cover street lighting needs: 125% of the demand for sodium lamps and 287% for LED lamps.

DISCUSSIONS AND CONCLUSIONS

Schemes based on piezoelectric tiles are growing fast. The concept of producing electricity from eccentric sources is clearly expanding. Roads joining piezoelectric resources can generate energy simply from vehicle movement, and this potential has been validated by several pilot projects globally.

Following its success, plans are underway to expand this technology to other roads in the country.

Among the studied methods, railways offer the highest energy generation capacity. The data shows that piezoelectric railways significantly outperform pavements and tiles. According to previous research, the structural nature of rail transport makes it ideal for piezoelectric applications. With countries having wide rail networks, some averaging 40,000 km, this method holds great promise for future energy reaping.

Climate change and environmental concerns make it vital to adopt clean and sustainable energy solutions. Piezoelectric skill fits this need well because it can be combined into current construction without causing damage or creating harmful emissions. Because it relies slightly more on motorized stress than burning, it offers an eco-friendly way to generate electricity. This makes piezoelectric systems a valuable option for secondary sustainable development as they align with global efforts to reduce pollution and defend biodiversity.

One of the main challenges in piezoelectric energy harvesting is its economic position in the market. For technology to prosper, strong support from governments and private investors is required. See-through policies, monetary inducements, and long-term funding are crucial for inspiring innovation and making schemes viable. Although renewable energy acceptance has grown significantly universally, piezoelectric schemes still face hurdles in terms of profitability and large-scale applications. However, with better asset frameworks and helpful public policies, these methods could become more modest and will be generally adopted in the future.

REFERENCES

1. Laumann F, Sørensen MM, Jul Lindemann RFJ, Hansen TM, Tambo T. Energy harvesting through piezoelectricity – technology foresight. *Energy Procedia*. 2017;142:3062–3068. doi:10.1016/j.egypro.2017.12.445.
2. Li X, Strezov V. Modelling piezoelectric energy harvesting potential in an educational building. *Energy Convers Manag*. 2014;85:435–442. doi:10.1016/j.enconman.2014.05.096.
3. Armando D, Zapata T. Como proyecto piloto en un perfil vial de Bogotá. [Unpublished report].
4. González Díaz M. Obtención de energía de las olas empleando materiales piezoeléctricos [Ocean wave power generation using piezoelectric devices]. Facultad de Ciencias; 2017.
5. Sun XM, Peng WF, Zhang L, Zhang MQ. An overview on piezoelectric power generation system for electricity generation. In: *Electrical Engineering and Automation. Proceedings of the International Conference on Electrical Engineering and Automation*. Singapore: World Scientific Publishing; 2017. p. 340–347. doi:10.1142/9789813220362_0043.
6. Manbachi A, Cobbold RSC. Development and application of piezoelectric materials for ultrasound generation and detection. *Ultrasound*. 2011;19(4):187–196. doi:10.1258/ult.2011.011027.
7. Lee BY, Zhang J, Zueger C, Chung WJ, Yoo SY, Wang E, et al. Virus-based piezoelectric energy generation. *Nat Nanotechnol*. 2012;7(6):351–356. doi:10.1038/nnano.2012.69.
8. Guerin S, Stapleton A, Chovan D, Mouras R, Gleeson M, McKeown C, et al. Control of piezoelectricity in amino acids by supramolecular packing. *Nat Mater*. 2018;17(2):180–186. doi:10.1038/nmat5045.
9. Li X, Strezov V. Modelling piezoelectric energy harvesting potential in an educational building. *Energy Convers Manag*. 2014;85:435–442. doi:10.1016/j.enconman.2014.05.096.
10. Howells CA. Piezoelectric energy harvesting. *Energy Convers Manag*. 2009;50:1847–1850. doi:10.1016/j.enconman.2009.02.020.