

Deep Learning for Traffic Sign Recognition in Autonomous Vehicles: Challenges, Trends and Future Directions

Pradip S. Togrikar^{1,*}, Pritish M. Vibhute²

Abstract

Traffic Sign Recognition (TSR) serves as a fundamental task in the domain of autonomous vehicles (AVs), enabling systems to detect, classify, and respond to road signs with the level of accuracy and speed required for safe navigation. As AV technology continues to evolve, the role of intelligent TSR systems has become increasingly vital. Traditional computer vision techniques, while foundational, often fall short under challenging real-world conditions such as poor lighting, occlusion, and environmental variability. The emergence of deep learning has significantly transformed TSR, offering robust feature extraction and superior generalization capabilities. Convolutional Neural Networks (CNNs) have been widely adopted for image classification tasks, while real-time object detection frameworks like YOLO (You Only Look Once) have enabled fast and accurate sign localization. More recently, Vision Transformers (ViTs) have shown promise in capturing global context and improving performance in complex scenarios. Despite these advances, several challenges persist. Deep learning models can be sensitive to adversarial attacks, require large annotated datasets, and often struggle in edge cases involving small or distorted signs. This review critically evaluates state-of-the-art deep learning approaches for TSR, highlighting their strengths and limitations. Furthermore, it discusses emerging trends such as transfer learning, self-supervised learning, data augmentation, and the integration of multimodal data from additional sensors. Future directions are explored with an emphasis on enhancing robustness, interpretability, and real-time capabilities of TSR systems in autonomous vehicles. By consolidating current research and outlining key challenges, this study aims to provide a foundation for future advancements in intelligent traffic sign recognition.

Keywords: Traffic sign recognition, deep learning, YOLO, vision transformers, autonomous vehicles, intelligent transportation systems

INTRODUCTION

Traffic Sign Recognition (TSR) plays a pivotal role in the perception system of Autonomous Vehicles

*Author for Correspondence

Pradip S. Togrikar

E-mail: pradeep.togrikar@gmail.com

¹Research Scholer, Department of Electronics & Computer Engineering, Sanjivani University Kopargaon., Ahmednagar, Maharashtra, India

²Associate Professor, Department of Electronics & Computer Engineering, Sanjivani University Kopargaon., Ahmednagar, Maharashtra, India

Received Date: January 19, 2026

Accepted Date: July 03, 2026

Published Date: July 06, 2026

Citation: Pradip S. Togrikar, Pritish M. Vibhute. Deep Learning for Traffic Sign Recognition in Autonomous Vehicles: Challenges, Trends and Future Directions. Journal of Advancements in Robotics. 2026; 13(2):1–7p.

(AVs), enabling them to navigate safely through diverse and complex road networks. TSR refers to the task of detecting and classifying road signs, which provides essential information for vehicles to comply with traffic laws and make intelligent driving decisions. With the rapid advancements in deep learning techniques, TSR has evolved from traditional computer vision-based approaches to more robust and accurate deep neural network (DNN) models that have significantly enhanced autonomous driving capabilities [1, 2].

Autonomous vehicles (AVs) rely on the real-time detection of traffic signs as part of their broader perception system, which also includes object

detection, lane tracking, and road condition analysis. Unlike human drivers, AVs must process traffic signs instantly and accurately under various conditions, such as varying lighting, adverse weather, and traffic congestion. The challenge of accurately identifying traffic signs, especially in cluttered and dynamic environments, has spurred the development of deep learning techniques, particularly Convolutional Neural Networks (CNNs), which excel in image classification tasks [3]. Moreover, more recent models like YOLO (You Only Look Once (YOLO) and Vision Transformers (ViTs), have been integrated into TSR systems, significantly improving both the detection speed and accuracy [4, 5].

While deep learning-based TSR systems have shown remarkable performance, there remain several challenges to their real-world deployment. These include issues such as model generalization across diverse environments, robustness of models against adversarial attacks, and the need for real-time processing. Furthermore, the complexity of handling varying road sign appearances owing to different designs across regions, partial occlusion, and weather conditions necessitates the development of more sophisticated and resilient models [6, 7]. In addition to traditional models, emerging techniques such as data augmentation, adversarial training, and federated learning have been explored to address these challenges [8, 9].

The goal of this review is to provide an in-depth analysis of recent advancements in TSR systems powered by deep learning. We examine the methodologies, challenges, and solutions presented by recent research, and discuss the future directions in this field. By focusing on current trends in model architecture, dataset development, and practical deployment strategies, we aim to contribute to the broader conversation on safe and effective traffic sign recognition systems for autonomous vehicles. Ultimately, this review offers insights into the critical role that TSR will play in the future of intelligent transportation systems and autonomous driving technology.

METHODOLOGY USED

Overview of Traffic Sign Recognition (TSR)

TSR systems have evolved significantly from traditional computer vision methods, which rely on handcrafted features such as color histograms and edge detection [7]. Modern TSR systems, especially those based on deep learning, automatically learn feature representations directly from large-scale data, achieving higher accuracy and adaptability [8]. These systems typically consist of two primary steps: detection, in which traffic signs are localized within images, and classification, in which the detected signs are assigned to specific categories based on learned features. In the context of autonomous vehicles, TSR must handle various challenges, such as varying environmental conditions, traffic congestion, and dynamic road scenarios. Consequently, TSR models are expected to function with high precision and speed in real-world settings, demanding both accuracy and computational efficiency [9].

Deep Learning Techniques in TSR

CNNs have become the backbone of TSR due to their ability to learn hierarchical features from raw pixel data. Early work on CNNs for TSR demonstrated the potential of CNNs to achieve real-time recognition under challenging conditions by utilizing attention mechanisms to enhance feature extraction [10]. YOLO-based models, especially YOLOv4 and YOLOv3, have been widely adopted for traffic sign detection because of their real-time performance and robustness [11]. Recent work on Vision Transformers (ViTs) has shown promise in addressing the limitations of CNNs, particularly in handling large-scale data and capturing global dependencies in images [12].

Common Datasets for TSR

Several datasets are widely used for TSR model training and evaluation, as shown in Table 1. The German Traffic Sign Recognition Benchmark (GTSRB) is one of the most commonly used benchmarks and contains a large variety of signs for classification tasks [13].

Other datasets, such as the Belgian Traffic Sign Classification (BTSC) dataset and the LISA Traffic Sign Dataset, offer additional challenges, such as different weather conditions and sign occlusion, which help test the generalizability of TSR models in diverse environments [14].

Table 1. Shows summary of dataset used.

Dataset name	Specification	Total images (approx.)
GTSRB	German road signs; 43 classes; resolution: 30x30 to 100x100	~51,839
LISA	U.S. traffic signs; 47 classes; varied lighting and occlusion	~6,610 (cropped), ~7,855 frames
Synthetic GTSRB	Synthetic version of GTSRB; generated for rare sign balancing	Varies (user-defined)
Augmented weather dataset	GTSRB-like with weather effects (rain, fog, snow, etc.)	Varies (augmented from base sets)
Simulated intersection	Synthetic scenes for DRL in Avs at intersections	Varies (simulation-driven)
KITTI	Real-world driving data; multiple tasks	~15,000 labeled frames
Waymo	High-resolution, multi-sensor AV data; for detection and tracking	~12 million labeled images

Pre-processing and Data Augmentation

Preprocessing and data augmentation play crucial roles in improving the performance and robustness of TSR models. Common techniques include image resizing, color normalization, and contrast adjustment to improve visibility under various conditions. Furthermore, data augmentation methods, such as rotation, flipping, and brightness variation, have proven essential for training models that can generalize well to real-world driving scenarios [15].

LITERATURE REVIEW

CNN-Based Classification Models

CNNs have become foundational in Traffic Sign Recognition (TSR) because of their ability to learn rich spatial hierarchies of features. Early studies have demonstrated that CNNs outperform traditional methods, such as HOG and SIFT in Classification tasks [16]. Attention-enhanced CNNs further improved recognition by focusing on relevant image regions, achieving real-time performance with higher accuracy [10]. Recent advancements have emphasized lightweight architectures, such as MobileNet and ShuffleNet, making CNNs more suitable for embedded systems in autonomous vehicles (AVs) [17, 18].

Object Detection Models

Object detection frameworks, particularly the You Only Look Once (YOLO) family, play a pivotal role in TSR by enabling simultaneous detection and classification in real time. YOLOv3 and YOLOv4 achieved strong performance in terms of both accuracy and speed [19]. Newer iterations, such as YOLOv5 and YOLOv8, have further enhanced detection by refining loss functions and incorporating attention mechanisms, thereby improving reliability in cluttered and complex driving environments [20, 21].

Transformer-Based Models

Transformers have shown considerable promise in the TSR domain. While still emerging, models such as ViTs have outperformed traditional CNNs in certain object recognition tasks owing to their self-attention mechanisms, which can capture long-range dependencies in images. ViTs have been increasingly applied to TSR to enhance detection accuracy, particularly in complex scenarios [22].

Adversarial Robustness and Real-World Constraints

A critical area of research is improving the robustness of TSR models to adversarial attacks. Studies have shown that even minor perturbations in input images can significantly affect the performance of deep learning models, as shown in Figure 1. Adversarial training and robust optimization techniques have been explored to mitigate such risks and enhance the reliability of TSR systems under real-world conditions [23, 24].

The line chart illustrates the performance of various Traffic Sign Recognition (TSR) models based on accuracy and speed. YOLOv8 and ViT stand out with the highest accuracy, reaching 96% and 95%, respectively. MobileNet and ShuffleNet demonstrated the fastest inference speeds, exceeding 60 frames per second, making them highly suitable for real-time use in embedded systems. Attention-CNN offers improved accuracy over the standard CNN but operates at a slightly reduced speed. The YOLO family (v3 through v8) shows a steady enhancement in both accuracy and speed, with each new version offering more reliable performance in real-time scenarios than its predecessor. Overall, the chart emphasizes the trade-off between accuracy and speed, helping to identify the models best suited for specific TSR deployment contexts.

CHALLENGES AND FUTURE SCOPE

Despite major advances, deep learning-based Traffic Sign Recognition (TSR) systems still face significant real-world implementation challenges in autonomous vehicles. Key issues include ensuring model generalization and robustness across diverse roads and weather conditions in the future. Traffic signs differ widely by region in terms of shape, color, and design, making it difficult for models to generalize across datasets. Environmental factors, such as lighting, fog, and snow, further complicate detection accuracy [1, 2, 6]. Real-time TSR is essential for safe autonomous navigation; however, balancing speed and accuracy remain difficult. Small, occluded signs often go undetected, and high-accuracy models can be too resource-intensive for onboard systems [3, 7].

Adversarial attacks pose another risk, where small input changes can mislead deep models, leading to incorrect or missed recognition. Although adversarial training helps, full robustness is still lacking [4, 6]. Training requires large and diverse datasets that capture global traffic sign variations. However, data collection and annotation are expensive and time-consuming, and data augmentation methods are limited in their ability to replicate real-world complexity [8, 9]. Finally, integrating TSR with other vehicle perception modules, such as object detection and lane tracking, remains a challenge, particularly in complex driving environments where module synchronization is critical for safety [5, 7].

As AVs operate in diverse and changing environments, continuous learning and adaptation are necessary to maintain high performance. Models trained on static datasets often fail to generalize about new and unseen situations. Federated learning approaches, which allow models to learn from decentralized data, have been explored as a solution to this problem [10]. However, ensuring data privacy and efficient collaboration across multiple vehicles while minimizing computational costs remains a challenge in implementing scalable and adaptive TSR systems.




Figure 1. Shows model performance of accuracy and speed.




Figure 2. Shows comparison of deep learning models for traffic sign recognition.

FINDINGS AND DISCUSSIONS

1. *Robustness against adversarial attacks:* Future TSR systems must be resilient to adversarial examples that can mislead models with minor perturbations. Research is ongoing into defensive strategies like adversarial training, input pre-processing, and robust feature learning [25–28, 29]. TSR is expected to play a more integral role in fully end-to-end deep learning models for autonomous driving, with a focus on integrating TSR into unified perception and planning systems [30].
2. *Multi-agent and cooperative learning:* Emerging studies explore the use of multi-agent reinforcement learning, wherein vehicles share knowledge and coordinate their behavior at intersections or during complex maneuvers.
3. *Standardization and benchmarking:* As research diversifies, standardized evaluation protocols and open-source benchmarks will be critical for objectively comparing different TSR approaches and fostering collaboration across the field (Figure 2).

A comparative analysis of several deep learning models for traffic sign recognition based on their accuracy (%) and inference time (ms). YOLOv8 demonstrates the highest accuracy with the fastest inference time, making it the most efficient among the evaluated models. Vision Transformers and Sparse R-CNN also offer high accuracy but at a slightly higher computational cost. Spike neural networks, custom CNN, and federated learning exhibit lower accuracy and longer inference times, indicating a trade-off between distributed training or specialized architectures and performance. This visual clearly emphasizes the importance of balancing accuracy and real-time processing for effective deployment in autonomous vehicles.

CONCLUSION

This paper provides a comprehensive overview of deep learning techniques for Traffic Sign Recognition (TSR) in autonomous vehicles. It highlights the strengths of convolutional neural networks (CNNs), attention-based mechanisms, and real-time models, such as YOLOv8, which have proven effective in achieving high accuracy with minimal latency. These models have significantly facilitated the integration of the TSR into embedded automotive systems. However, several challenges remain.

Existing models often underperform in adverse conditions such as poor lighting, occlusion, and regional variations in traffic signs. Moreover, they are susceptible to adversarial attacks and struggle to generalize across different domains.

Future research should focus on improving the robustness, interpretability, and adaptability of these models. Promising directions include leveraging federated and multi-agent learning to enable privacy-preserving collaboration across vehicles, utilizing synthetic data and domain adaptation techniques to improve generalization across geographical contexts, and pursuing end-to-end integration of TSR into comprehensive autonomous navigation systems.

Addressing these challenges is essential for developing safe, scalable, and dependable autonomous vehicle systems capable of navigating the complexities of real-world environments.

Acknowledgment

I would like to express my sincere gratitude to our academic supervisors, Dr. Kiran Wakchaure and Dr. P.M. Vibhute, for their insightful guidance and continuous support throughout the preparation of this review paper. We also extend our gratitude to Sanjivani University, Kopergaon for providing the necessary resources and research environment

REFERENCES

1. Triki N, Karray M, Ksantini M. A real-time traffic sign recognition method using a new attention-based deep convolutional neural network for smart vehicles. *Appl Sci (Basel)*. 2023;13(8):4793.
2. Liang T, Bao H, Pan W, Pan F. Traffic sign detection via improved Sparse R-CNN for autonomous vehicles. *J Adv Transp*. 2022;2022:3825532.
3. Kanagaraj N, Hicks D, Goyal A, Tiwari S, Singh G. Deep learning using computer vision in self-driving cars for lane and traffic sign detection. *Int J Syst Assur Eng Manag*. 2021;12(6):1011-25.
4. Xie K, Zhang Z, Li B, Kang J, Niyato D, Xie S, et al. Efficient federated learning with spike neural networks for traffic sign recognition. *IEEE Trans Veh Technol*. 2022;71(9):9980-92.
5. Dewi C, Chen RC, Jiang X, Yu H. Deep convolutional neural network for enhancing traffic sign recognition developed on YOLO v4. *Multimed Tools Appl*. 2022;81(26):37821-45.
6. Güney E, Bayılmış C, Çakan B. An implementation of real-time traffic signs and road objects detection based on mobile GPU platforms. *IEEE Access*. 2022;10:86191-203.
7. Singh K, Malik N. CNN based approach for traffic sign recognition system. *Adv J Grad Res*. 2022;11(1):23-33.
8. Ahmed S, Kamal U, Hasan MK. DFR-TSD: a deep learning based framework for robust traffic sign detection under challenging weather conditions. *IEEE Trans Intell Transp Syst*. 2022;23(6):5150-62.
9. Antonio GP, Maria-Dolores C. Multi-agent deep reinforcement learning to manage connected autonomous vehicles at tomorrow's intersections. *IEEE Trans Veh Technol*. 2022;71(7):7033-43.
10. Wan J, Ding W, Zhu H, Xia M, Huang Z, Tian L, et al. An efficient small traffic sign detection method based on YOLOv3. *J Signal Process Syst*. 2021;93(8):899-911.
11. Bathla G, Bhadane K, Singh RK, Kumar R, Aluvalu R, Krishnamurthi R, et al. Autonomous vehicles and intelligent automation: applications, challenges, and opportunities. *Mob Inf Syst*. 2022;2022:7632892.
12. Dewi C, Chen RC, Liu YT, Tai SK. Synthetic data generation using DCGAN for improved traffic sign recognition. *Neural Comput Appl*. 2022;34(24):21465-80.
13. Hasanujjaman M, Chowdhury MZ, Jang YM. Sensor fusion in autonomous vehicle with traffic surveillance camera system: detection, localization, and AI networking. *Sensors (Basel)*. 2023;23(6):3335.
14. Chib PS, Singh P. Recent advancements in end-to-end autonomous driving using deep learning: a survey. *IEEE Trans Intell Veh*. 2024;9(1):103-18.

15. Girdhar M, Hong J, Moore J. Cybersecurity of autonomous vehicles: a systematic literature review of adversarial attacks and defense models. *IEEE Open J Veh Technol*. 2023;4:417-37.
16. Chen L, Teng S, Li B, Na X, Li Y, Li Z, et al. Milestones in autonomous driving and intelligent vehicles—Part II: perception and planning. *IEEE Trans Syst Man Cybern Syst*. 2023;53(10):6401-15.
17. Zakaria NJ, Shapiai MI, Abd Ghani R, Yassin MN, Ibrahim MZ, Wahid N. Lane detection in autonomous vehicles: a systematic review. *IEEE Access*. 2023;11:3729-65.
18. Parekh D, Poddar N, Rajpurkar A, Chahal M, Kumar N, Joshi GP, et al. A review on autonomous vehicles: progress, methods and challenges. *Electronics (Basel)*. 2022;11(14):2162.
19. Deng Y, Zhang T, Lou G, Zheng X, Jin J, Han QL. Deep learning-based autonomous driving systems: a survey of attacks and defenses. *IEEE Trans Ind Inform*. 2021;17(12):7897-912.
20. Wang S, Li C, Ng DW, Eldar YC, Poor HV, Hao Q, et al. Federated deep learning meets autonomous vehicle perception: design and verification. *IEEE Netw*. 2023;37(3):16-25.
21. Köylü F. A comparative analysis of YOLO-based traffic sign detections with a novel Turkish traffic sign dataset. *IEEE Access*. 2026;14:7744-63.
22. Mani MK, Rajagopal S, Kavitha D, Ramachandran S. Deep learning-based traffic sign detection and recognition for autonomous vehicles. In: *Digital twin and blockchain for smart cities*. 2024. p. 407-28.
23. Kozhamkulova Z, Bidakhmet Z, Vorogushina M, Tashenova Z, Tussupova B, Nurlybaeva E, et al. Development of deep learning models for traffic sign recognition in autonomous vehicles. *Int J Adv Comput Sci Appl*. 2024;15(5).
24. Sah CK, Shaw AK, Lian X, Baig AS, Wen T, Jiang K, et al. Advancing autonomous vehicle intelligence: deep learning and multimodal LLM for traffic sign recognition and robust lane detection [Preprint]. 2025. arXiv:2503.06313.
25. Mingwin S, Shisu Y, Wanwag Y, Huig S. Revolutionizing traffic sign recognition: unveiling the potential of vision transformers [Preprint]. 2024. arXiv:2404.19066.
26. Omidian F, Abdi A. Appsign: multi-level approximate computing for real-time traffic sign recognition in autonomous vehicles [Preprint]. 2024. arXiv:2411.10988.
27. Toshniwal D, Loya S, Khot A, Marda Y. Optimized detection and classification on GTRSB: advancing traffic sign recognition with convolutional neural networks [Preprint]. 2024. arXiv:2403.08283.
28. Patel V, Mehta J, Iyer S, Sharma AK. Traffic sign recognition using deep learning. *Int J Veh Auton Syst*. 2022;16(2-4):97-107.
29. Naik UP, Rajesh V, Kumar R. Implementation of YOLOv4 algorithm for multiple object detection in image and video dataset using deep learning and artificial intelligence for urban traffic video surveillance application. In: *2021 Fourth International Conference on Electrical, Computer and Communication Technologies (ICECCT)*; 2021 Sep 15. IEEE; 2021. p. 1-6.
30. Lim XR, Lee CP, Lim KM, Ong TS. Enhanced traffic sign recognition with ensemble learning. *J Sens Actuator Netw*. 2023;12(2):33.