

# New Trends in Radio Frequency Design and Making Things Smaller

V. Basil Hans<sup>1,\*</sup>

## Abstract

Recent improvements in wireless communication, the Internet of Things (IoT), and 5G/6G networks have made people want small, powerful radio frequency (RF) equipment. With an emphasis on how developments in materials engineering, circuit architecture, and packaging technologies redefining RF system integration are, this article offers a thorough evaluation of current developments in RF downsizing. System-on-chip (SoC), system-in-package (SiP), and antenna-in-package (AiP) ideas, which allow tightly integrated RF front ends with enhanced bandwidth and decreased connection loss, have made significant strides. The miniaturization of passive, active, and antenna components has also been accelerated by the use of high-performance substrates like silicon-on-insulator (SoI) and low-temperature co-fired ceramics (LTCC), as well as innovative fabrication techniques like additive manufacturing and micro-scale 3D printing. As devices get smaller and smaller, it becomes harder to keep signals strong, save power, and make sure they work with other devices. This article looks at new trends in RF design and miniaturization, focusing on new materials, circuit layouts, and manufacturing methods. Some of the most important changes are the use of SoC and SiP technologies to combine RF front ends, the use of advanced substrates like LTCC and SoI, and the use of metamaterials and 3D printing to make components smaller. Even in sub-wavelength footprints, advanced antenna ideas such as beam-steerable metasurface arrays, dielectric resonator antennas, fractal geometries, and reconfigurable radiating structures significantly improve spectral agility and radiation performance. Novel electromagnetic design tools that enhance accuracy during early-stage co-simulation of RF circuits and packaging environments, like full-wave 3D solvers and AI-assisted optimization engines, complement these advancements. In order to provide reliable, scalable, and affordable RF downsizing solutions, advances in nanomaterial engineering, metamaterial-inspired RF structures, thermal-aware system co-design, and data-driven layout optimization will be essential. Also, new antenna designs, such as reconfigurable and fractal geometries, are making it possible for antennas to work well in small spaces. The essay ends by talking about the future of RF miniaturization, including nanotechnology, additive manufacturing, and AI-driven design optimization, and how they could change the way wireless communication networks work in the future.

**Keywords:** 5G/6G technologies, advanced materials, metamaterials, antenna design, radio frequency (RF) design, miniaturization, and system-on-chip (SoC)

### \*Author for Correspondence

V. Basil Hans  
E-mail: [vhans2011@gmail.com](mailto:vhans2011@gmail.com)

<sup>1</sup>Research Professor, Department of Management & Commerce, Srinivas University, Mangaluru, Karnataka, India.

Received Date: October 25, 2025

Accepted Date: October 28, 2025

Published Date: December 31, 2025

**Citation:** V. Basil Hans. New Trends in Radio Frequency Design and Making Things Smaller. International Journal of Radio Frequency Innovations. 2025; 3(2): 28–34p.

## INTRODUCTION

The radio frequency (RF) spectrum includes electromagnetic waves with wavelengths ranging from approximately 1 mm (300 GHz) to 100 km (3 Hz). Frequencies up to approximately 300 GHz are often called RF and are used extensively for cell phones, radio, and television communication. The RF spectrum is used for a variety of purposes, from cutting-edge millimeter-wave (mm-Wave) cellular and satellite communication networks to conventional long-range radio and television

transmissions. Wireless technologies, such as VHF/UHF broadcast services; cellular networks operating around 800–900 MHz; industrial, scientific, and medical (ISM) communication centered around 2.4 GHz, and satellite communication links operating typically above 3 GHz, are now supported by frequencies extending up to nearly 300 GHz. Compact electronic devices are required to provide not only basic connectivity, but also excellent spectral efficiency, improved data throughput, and wider operational bandwidths across many standards as the global wireless ecosystem grows. The Federal Communications Commission (FCC) has split frequency bands into more than 100 separate groups. The typical range for radar is 540–40 GHz. A VHF/UHF TV uses frequencies between 50 and 700 MHz. Cell phones use frequencies of 800–900 MHz. For personal communications services and the ISM radio bands, the range of 1.99 GHz to 2.4 GHz is set aside. Miniaturization is becoming a key engineering requirement in the design of contemporary RF systems due to this quick progress. RF front-end solutions that fit into incredibly constrained physical footprints are necessary for next-generation wireless platforms, such as wearable technologies, autonomous vehicle communication modules, mobile edge computing infrastructures, nanosatellite constellations, and densely networked IoT devices. Multiband, multimode, and multistranded functionality must all be supported concurrently by these devices to ensure consistent signal quality and low power consumption. Satellite communications use frequency ranges from 3.625 GHz to 4.2 GHz and from 5.85 GHz to 8.5 GHz. Ships can send safety messages between 24 MHz and 305 MHz. Other frequency bands, like 23.12 GHz to 23.62 GHz and 29.7 GHz to 30.3 GHz, are often employed for space-to-earth and earth-to-space operations [1].

Modern RF design requires that nearly every block in a radio not only fulfill its designated responsibilities but also have optimal durability, efficiency, and a reduced overall size. However, aggressive size reduction presents serious technical challenges that require traditional design approaches. Reducing the size of RF components introduces undesirable parasitic elements that deteriorate the high-frequency performance, decrease the available isolation, and increase the electromagnetic coupling between nearby structures. Alignment between antennas, active circuits, and embedded interconnects has become increasingly challenging to optimize because of the push toward thinner packaging and higher circuit density, which also increases the complexity of system level integration. As power density increases, thermal management also becomes a crucial issue because concentrated heat within smaller front-end circuits can negatively affect operational stability and long-term dependability. Traditional methods use large, dedicated sub-blocks for each function (mixer, amplifier, oscillator, frequency multiplier, etc.) and run full performance simulations at the system, circuit, and physical layout levels. Currently, designs use new architectures, new ways of making transmission lines, new materials, advanced complementary metal–oxide–semiconductor (CMOS) process technologies, and other new technologies to meet these complex requirements [2].

### **Current State of RF Design**

In the last twenty years, RF design has become very important because there are many more wireless users (one device/user), and the mobile wireless industry, the Internet of Things (IoT), a wide range of automotive applications, and satellite communications all want new ideas. These require a wide range of RF operating frequencies, from hundreds of megahertz (MHz) to millimeter waves (mmW). Size is also very important, especially because mobile electronics, automotive, and IoT applications are getting more modules, which means that they need to be made smaller. Design goals have changed as a result of this progression. RF architecture has changed at the electrical, thermal, system level, mechanical, and regulatory boundaries since the early 2000s, owing to significant developments in semiconductor technologies, sophisticated materials, and heterogeneous integration. However, parasitic effects, signal coupling, and conduction loss are amplified when circuit dimensions are reduced while the operation is extended to multi-GHz and mm-Wave frequencies. These parasitic components deteriorate the linearity, noise performance, and impedance matching, making it much harder to comply with contemporary RF design requirements. RF design has changed significantly since the year 2000. The emergence of new materials, processes, and a wide range of applications and cutting-edge technology requiring RF design,

modulation, performance, and more at the system, electrical, thermal, regulation, mechanical, and test levels in/mm towards mmW has given rise to new RF design trends. Because RF circuits have many parasitic parts that work at higher frequencies, like multi-GHz, the RF design is affected by many operating parameters. This makes it difficult to link them in a manner that follows the rules of modern RF design. The design process is made more difficult by the continuous drive for high-bandwidth connectivity, which necessitates sophisticated modulation methods and ultralow latency performance. To overcome these obstacles, RF front ends incorporate cutting-edge technologies, such as micro-electromechanical systems (MEMS) and newly developed two-dimensional nanomaterials, to attain small dimensions while allowing tunability and reconfigurability. Instead of viewing materials as passive carriers, modern RF designs view them as functional components with electromagnetic behavior that must be modeled and optimized from the very beginning of the design process. The need for mm-Wave RF to have a higher bandwidth and different modulation techniques makes it difficult to design RF circuits. The viewpoint from the micro-electronic mechanical system (MEMS) and RF applications of 2D materials towards condensed RF was examined. We discuss a material stack-up for RF design that can be used in new applications, including 5G communications and satellite connectivity. Some mobile applications that are getting a lot of interest right now are IoT, automotive applications, drone operation/modeling, and trends relating to 5G, 6G, and satellite communication. The traditional method of characterizing materials post-completion of RF electronic systems/modules is obsolete and requires an innovative approach, with the initiation of modeling from materials under investigation [2].

### **Advanced Materials and Methods for Making Things Smaller**

Advanced materials and technologies make it easier to reduce the size of RF circuits. Dielectric, magnetic, and semiconductor materials with low loss, low dispersion, and that work with planar microfabrication are some of the most important factors that make this possible. Inkjet printing, screen printing, wet and dry etching, and thin-film technologies are examples of additive and subtractive microfabrication processes that may define features very precisely at the micrometer scale. To create miniature passive and active structures precisely, modern RF manufacturing uses a combination of additive and subtractive microfabrication processes. Microstrip lines, inductors, resonators, and filters can be realized with micrometer scale accuracy using technologies such as inkjet printing, screen printing, photolithography, thin-film deposition, and sophisticated dry/wet etching. Planar circuit layouts and flexible RF topologies, which are becoming increasingly popular in wearable and embedded wireless systems, are supported by metallization using copper, nickel, or gold over substrates, such as polyimide and SU-8. People often utilize thick films and thin-film copper, nickel, gold, polyimide, and SU-8. Three-dimensional and stacked packaging also helps with miniaturization by reducing the horizontal area. RF components are currently being incorporated into three-dimensional (3D) and stacked substrate architectures, which greatly shorten interconnects and lower transmission losses in an effort to further reduce the footprint. While satisfying the strict isolation requirements for multiband transceiver front ends, vertical integration within silicon-based systems, such as SoI, and multilayer ceramics, such as LTCC, improves bandwidth and signal integrity [3].

Integration remains an important factor in making things smaller. Heterogeneous integration, which involves making different materials separately and then combining them later, is still the most prevalent method. In RF miniaturization, the integration strategy is crucial in RF miniaturization. Optimized RF devices, sensors, MEMS switches, and power stages can be manufactured independently and then integrated into a single RF module owing to heterogeneous integration. System-in-package (SiP), chip-in-package (CiP), and flip-chip bonding are examples of advanced packaging techniques that reduce interconnect parasitics, enhance electromagnetic compatibility, and enable tighter RF connections between antennas and active circuitry. As wireless products move toward mm-Wave and 6G-ready platforms, where each parasitic component directly affects the gain, linearity, and noise performance, these advantages are crucial. Other types of integration schemas are used, such as CiP, system-in-package, and flip-chip interconnects [2].

---

### Frontiers in Multi-GHz and mm-Wave Operation

New uses for wireless communications require small RF front ends that operate at multi-GHz or millimeter-wave frequencies. These designs put circuit functions at risk of high-frequency parasitic effects, propagation problems, and excessive losses. RF systems operating in millimeter-wave and multi-GHz ranges are becoming indispensable for next-generation wireless communication. The smallest parasitic element might act as a troublemaker at these high frequencies, causing undesired losses, distortion, or problems with propagation. The increased bandwidth also requires designers to use harmonic-aware circuit designs instead of more conventional linear designs. In addition, additional bandwidth makes it necessary to switch from basic circuit design to harmonic design. Phase-locked loops, constant-amplitude stabilization, impedance matching, and frequency doubling are all system requirements that make things even more complicated. However, many circuit topologies and device technologies can perform frequent up-conversion. Advanced architecture and multiport configurations come together in solutions for signal stabilization, power amplification, and wideband operation. To check the performance, particular tools are required to measure the time and frequency domains.

Miniaturized systems for millimeter-wave and multi-GHz applications require small circuitry and regulated signal distribution. Waveguide technology, gas discharge tubes, semiconductor saturation and mixing devices built into single substrates help solid-state microwave and millimeter microwave sources travel. The design process is made more complex by crucial RF subsystems, including phase-locked loops for frequency stability, constant-amplitude management for signal integrity, accurate impedance matching for effective power transmission, and frequency doubling for spectral extension. Fortunately, effective frequency up-conversion is supported by various semiconductor technologies and RF circuit topologies. Using standard diffused microwave integrated circuit (MIC) technology on microwave glass substrates, planar self-oscillating dual- and triple-balance mixers can operate at 1300 GHz, 860 GHz, 935 GHz, 1225 GHz, and 1565 GHz. High-speed four-terminal microwave integrators provide RF isolation, whereas multi-frequency and harmonically stepped solid-state oscillator topologies allow for high-efficiency frequency multipliers at 16 GHz. Dual-image and heterodyne mixers allow one to route signals independently and keep the drives separate. A commercial GaAs complementary metal-oxide-semiconductor method with a SiO<sub>2</sub> dielectric top was used to fabricate millimeter-wave monolithic integrated circuitry that included amplifiers, oscillators, mixers, and phase-locked loops. A K-band oscillator can obtain noise figures of 21 dB and a gain of 15 dB. A monolithic dual-2H mixer that operates at 24 GHz has a conversion loss of 4 dB when the input RF power is -4 dBm.

Dedicated tools that can perform RF techniques, such as time-domain reflectometry, time-gated oscilloscope measurements, vector signal analysis, CM-1 measurements, two-tone measurements, and spectral measurements, make it easier to develop methods for modeling, co-simulation, and verification of mixed-mode circuits for multi-GHz and millimeter-wave frequencies. Advanced full-wave electromagnetic modeling makes it possible to optimize circuit interconnections, devices, and substrates by eliminating the parasitic effects. An open-source mixed-signal simulator designed for multiband environments, where continuous and discrete-time signals coexist, enables further analysis. Circuit topologies implemented at millimeter-wave and multi-GHz RF frequencies address signal stabilization, up-conversion, and power amplification operations. Active-passive co-design, which includes a structure for waveguide RF propagation, facilitates electromagnetic characterization in circuits with several cross-coupled components. Using external reference signals to stabilize signals works with both active and passive devices that are spaced apart in the cavity designs [4].

### Making Antennas Work in Small Spaces

Antenna miniaturization is still a big problem, and it is worsening because of the rise of wireless services and the requirement for smaller form factors. The design of antennas that are becoming increasingly smaller for new and next-generation systems has sparked new interest at every level of the value chain. The antenna elements for the frequency bands from 300 MHz to over 100 GHz have a K value of approximately 0.25, whereas antenna-integrated circuits for the same frequency bands have a K value of approximately 0.5.

Reconfigurable antennas that use switches, phase shifters, or variable capacitors allow modification of the form factor or operating frequency. Multifunction antennas that have radiators with different frequency characteristics or antennas that add to the functionalities of nearby circuits are also options at the system level.

Quickly placing antennas together with substrates or packaging makes it less necessary to perform complicated detuning and use many antenna elements. Fewer layers or vias means that packing takes less time and costs less. Combining antennas with filters and other parts reduces the coupling between antennas and encourages the co-design of antenna performance and architecture. Systems that use two-dimensional or three-dimensional meta-surfaces use objects such as beam steering, frequency selective surfaces, defect state miniaturized antennas, or phase shifting to change the polarization or add more reflections, all while following strict K constraints [5].

### **Radio Frequency Integrated Circuits and Systems-on-Chip**

Single chip radio frequency integrated circuits (RFICs) are very important for modern transceiver architecture and society because they enable the fabrication of radios-on-chips. There are three degrees of integration: system-on-chip (SoC), SiP, and package-on-package (PoP). Each level can use a variety of shared resources. The compact IC design presents hurdles, including significant parasitic thermal and electrical impedance among components, power distribution issues, low-frequency noise, linearity concerns, and parasitic poles that influence circuit stability. For tiny RF modules to work well and be dependable, it is important to co-design the antenna, circuit, and packaging [6].

### **Strategies for Managing Heat in Dense RF Modules**

Miniaturizing equipment always makes more heat energy. Heat dissipation is a major problem for tightly packed RF modules used in telemetry systems such as car radar, satellite communications, and the Internet of Things [7]. There are many reasons for the increase in thermal generation. For example, as more people are using digitally modulated multi-carrier signals, there is an increasing demand for higher-order modulation formats, and module layouts are already packed [8]. Therefore, it is important to know how thermal generation and accumulation work to keep these flexible systems reliable and to make them last longer.

The power amplifier, transmit-receive switch, and frequency synthesizer are the most typical parts of a tiny RF module that creates heat. Power amplifiers are usually the main problem; therefore, it needs careful temperature management is required. Copper, aluminum, or aluminum nitride (AlN) heat spreaders can separate the thermal impedance between packaging and printed circuit boards (PCBs). A low-thermal-resistance gap filler, such as a thermal silicone compound, continues to spread under the spreader. The addition of thermally protected compounds, such as fluorinated polyimide and polybenzimidazole, can sometimes increase the reliable operating temperature. There are several ways to use microflight and microfluidic mappings to improve envelope-tracking systems at the PCB layer, ensuring that they all work together and that the architecture is symmetrical.

### **System Architecture and Co-Design Methods**

Owing to system architecture and co-design methods, RF systems have become smaller than ever before. More complex tactics look at how different blocks are connected and how they might be integrated in a more general way, rather than just looking at each block on its own. The co-design of the RF front-end, interconnects, and packaging is a complete way to examine system level specifications while improving performance, power use, and size.

The ongoing and swift advancement of integrated technologies and user requirements has attracted interest in the co-design of the electrical architecture and physical packaging of RF modules. The integration and convergence of different services and applications have made it necessary to fit different RF circuits into small platforms. However, it is important to automatically characterize and optimize certain performance measures (such as power, latency, area, and manufacturability) as soon as feasible

in the design flow. It is also important to avoid mismatches between metrics. To meet the strict needs of the industry, the idea of platform methods for RF design and two options of modularity—plug-in architecture and design automation—have been proposed.

### **Problems with Manufacturing and Reliability**

The miniaturization of active and passive components in RF design makes them smaller, more complicated, and more likely to send RF signals at higher frequencies. Inter-component coupling and parasitic effects from size reduction affect the performance of the RF circuits. This is very sensitive to changes in RF front-end design, packaging technology, and Material Interfaces. The reliability of these parts and materials significantly affects the number of products that can be produced.

The miniaturization of IC technology to 16 nm geometries has significantly enhanced the integration of functionality and digital components on a single chip. It is important to combine high-performance, high-frequency RF-CMOS materials and designs with the capacity to test and diagnose before deployment [9]. RF-CMOS technology must be used in wireless devices, and packaging must meet standards with a geometry of less than 28 nm [10]. Using an RF-CMOS IC on 28 nm bulk silicon technology is an excellent solution for mobile communications and wireless product systems, but it requires a testing process to ensure reliability [11].

### **New Uses and Case Studies**

New telecommunications technologies have made it possible for integrated, miniaturized RF solutions to operate at multi-gigahertz (multi-GHz) frequencies. The development of these technologies, including fifth- and sixth-generation (5G/6G) wireless communications, automotive radar, IoT devices, aerospace applications, and satellite connections, presents significant challenges and new opportunities for microwave and millimeter-wave circuit designers [12–14]. Recent advancements in semiconductor technology have facilitated the incorporation of multi-GHz capabilities into portable devices; however, the constraints of cost, size, and power efficiency established by previous generations remain. Therefore, an area-efficient design strategy can significantly improve performance and make multi-GHz systems more accessible. When time-to-market and extra supply voltage limits are in place, adding more modules is often cheaper, easier, and as effective as making one module more useful. These ideas are demonstrated by a number of circuits that were made to cut costs and size while improving performance at multi-GHz speeds. In these situations, the separation of the layout and circuit design shows degrees of freedom within a set of basic building blocks. Going forward, it is important to perform a detailed benchmarking of how well different transmitter and receiver modules, antennas, and materials work together. This includes the cost, size, performance, and adaptability [15]. This kind of cooperative evaluation is very important for obtaining a better idea of how to develop multi-GHz circuits that function with the current platform.

### **CONCLUSION**

Miniaturization in design remains an ongoing trend in RF systems. Amplification, fabrication, heat management, and co-design can all limit what can be achieved. RF design co-designs are generally better suited for RF/microwave (MW) frequencies than for GHz/THz frequencies. Before RF formation or GHz formation occurs, analysis tools evolve rapidly. Performance is fully utilized within a well-defined operating range.

### **REFERENCES**

1. Rezvani M. CMOS low noise amplifiers for wireless body area networks applications: techniques and designs. [Master's Thesis]. Toronto (ON): Ryerson University; 2013. p. 1–123.
2. Chirala MK. Passive and active circuits in CMOS technology for RF, microwave and millimeter wave applications. [doctoral dissertation]. College Station (TX): Texas A&M University; 2007.
3. Tatu SO, Moldovan E. Millimeter-wave multi-port interferometric radar sensors: evolution of fabrication and characterization technologies. *Sensors* (Basel). 2020;20(19):5477. doi:10.3390/s20195477. PubMed PMID: 32987889.

4. Ebrhimi N. Compact heterogeneous integration for next generation high-frequency scalable array with miniaturized and efficient power delivery network. [Preprint]. arXiv:2111.04567. 2021. doi:10.48550/arXiv.2111.04567.
5. Mufti S. Miniaturization and optimization of electrically small antennas, with investigation into emergent fabrication techniques. [Doctoral Dissertation]. Sheffield (UK): University of Sheffield.
6. Hajimiri A. MM-wave silicon ICs: an opportunity for holistic design. Proceedings of the IEEE Radio Frequency Integrated Circuits Symposium (RFIC), Digest of Technical Papers; 2008. p. 357–360. doi:10.1109/RFIC.2008.4561453.
7. Garimella SV, Persoons T, Weibel JA, Gektin V. Electronics thermal management in information and communications technologies: challenges and future directions. IEEE Trans Compon Packag Manuf Technol. 2017;7(8):1191–1205. doi:10.1109/TCPMT.2016.2603600.
8. Razumova TO, Burak ID. Further professional education: challenges in an unstable environment. Sustain Innov Dev Glob Digit Age. 2022;(3):033. doi:10.56199/dpcsebm.hkrc3496.
9. Wang Y, Zhang X, Yang X, Wang Z, Yan Y, Du B, Zhang J, Wang C. A novel swept-back fishnet-embedded microchannel topology. Micromachines (Basel). 2023;14(9):1705. doi:10.3390/mi14091705. PubMed PMID: 37763868.
10. Nagori K, Sharma R, Shukla A, Nakhate KT, Dewangan D. Bioink as integral material for 3D printing. In: Pradhan M, Yadav K, editors. 3D Printing and Microfluidics in Dermatology: Innovations in Drug Delivery. Boca Raton (FL): CRC Press; 2024. p. 30–55.
11. Senguttuvan R. Low-cost test, diagnosis, and tuning for adaptive radio frequency systems. [Doctoral Dissertation]. Atlanta (GA): Georgia Institute of Technology; 2008.
12. Gopalan A. Built-in self-test of RF front-end circuitry. [thesis]. Rochester (NY): Rochester Institute of Technology; 2005. p. 1–133.
13. Chen S. RF power amplifier and oscillator design for reliability and variability. [dissertation]. Orlando (FL): University of Central Florida; 2013.
14. Bautista MG. Miniaturised on-chip passive devices for millimetre-wave applications in Bi-CMOS technology. [Thesis]. Berkeley (CA): Lawrence Berkeley National Laboratory; 2019.
15. Hitko DA. Circuit design and technological limitations of silicon RFICs for wireless applications. [dissertation]. Cambridge (MA): Massachusetts Institute of Technology; 2002.