

A Review of Arduino Based Distance Measurement Device

Rajvardhan Bagal¹, Sarvesh Mahimkar², Omkar Shinde³,
Suyash Phadke⁴, M.M. Zade^{5,*}

Abstract

Distance measurement plays a vital role in modern engineering applications such as robotics, defense systems, automotive safety, industrial automation, and assistive technologies. Traditional measuring tools such as rulers and measuring tapes are simple but not suitable for real-time and dynamic environments. On the other hand, advanced technologies such as LiDAR and radar provide high accuracy but involve high cost and complex implementation. This review paper provides a thorough analysis of ultrasonic sensor-based Arduino-based distance measuring devices. The paper discusses system architecture, working principles, applications, advantages, limitations, and comparison with existing technologies. The ultrasonic sensor operates on the time-of-flight principle, enabling accurate distance calculation for short ranges. The review highlights that Arduino-based ultrasonic systems provide a low-cost, portable, and efficient solution for distance measurement. These systems are often utilized in assistive technology, parking systems, obstacle detection, and educational initiatives. Additionally, the paper explores future enhancements such as IoT integration, AI-based object detection, and deployment in autonomous systems. To improve measurement accuracy and operational dependability, the analysis also looks at current advancements in sensor interface, signal processing methods, and energy-efficient embedded system architecture. In order to identify current problems, such as limited sensing range, environmental interference, and sensitivity to surface properties, it also summarizes research findings. The study concludes that Arduino-based ultrasonic distance measurement systems provide a solid foundation for upcoming smart sensing technologies while offering an efficient balance between cost, simplicity, and performance, making them ideal for small-scale industrial applications, academic research, and prototype development.

Keywords: Arduino Uno, ultrasonic sensor, radar system, object detection, embedded system, automation

*Author for Correspondence

M.M. Zade
E-mail: mahesh.zade@sknscoe.ac.in

¹⁻⁴UG Students, Department of Electronics and Telecommunication Engineering, SKN Sinhgad College of Engineering, Pandharpur, Solapur, Maharashtra, India

⁵Assistant Professor, Department of Electronics and Telecommunication Engineering, SKN Sinhgad College of Engineering, Pandharpur, Solapur, Maharashtra, India

Received Date: July 24, 2026
Accepted Date: August 17, 2026
Published Date: August 22, 2026

Citation: Rajvardhan Bagal, Sarvesh Mahimkar, Omkar Shinde, Suyash Phadke, M.M. Zade. A Review of Arduino Based Distance Measurement Device. Journal of VLSI Design Tools & Technology. 2026; 16(2): 40–46p.

INTRODUCTION

Distance measurement is an essential requirement in various engineering fields, including robotics, industrial automation, navigation systems and defence surveillance. Accurate distance measurement is crucial for tasks such as object detection, collision avoidance, and environmental mapping. Traditional distance measurement methods, such as rulers and measuring tapes, are simple but unsuitable for dynamic and real-time applications. These methods are time-consuming and lack automation capabilities [1]. Advanced technologies such as LiDAR, radar, and laser range finders offer high precision and long-range measurement capabilities. However, they are expensive and require complex hardware and

software integration, rendering them unsuitable for low-cost applications. Microcontroller-based solutions have become effective and cost-effective substitutes with the development of embedded systems. Arduino-based systems have become increasingly popular owing to their simplicity, adaptability, and ease of programming. These devices employ ultrasonic sensors to estimate the distance by sending out sound waves and timing the duration for the echo to return [2]. The time-of-flight concept, which uses the speed of sound to determine the distance, is the basis for the functioning of ultrasonic sensors. These sensors provide reliable and accurate results for short-range measurements, typically between 2 and 400 cm. Owing to their low cost and ease of integration, ultrasonic sensors are widely used in obstacle detection systems, parking assistance, and robotic navigation. The Arduino platform simplifies the development process by providing an open-source environment and extensive library support [3]. This allows users to design and implement distance-measurement systems with minimal effort. Additionally, Arduino-based systems can be easily integrated with other components, such as displays, wireless modules, and actuators. Microcontroller-based solutions have become effective and cost-effective substitutes with the development of embedded systems. It discusses existing research, system design, advantages, limitations, and future developments. This study emphasizes the importance of low-cost and efficient solutions in modern engineering applications [4].

LITERATURE SURVEY

Table 1 shows a comparison of the performances of the distance-sensing technologies. Several researchers have explored the use of ultrasonic sensors and embedded systems for distance measurement and object detection.

An ultrasonic-based obstacle detection system and its technique are straightforward, inexpensive, and simple to implement. It provided accurate results for short-range measurements but was affected by environmental conditions, such as temperature and humidity.

An Arduino-based parking assistance system uses ultrasonic sensors to detect obstacles nearby. Drivers receive real-time notifications from the system, which enhances its usability and safety. However, its application is limited to vehicle-parking systems.

A hybrid system combining ultrasonic sensors with a laser module improved the alignment and targeting accuracy. Although the system provided superior performance, it was less appropriate because it increased system complexity and expense for low-cost applications.

An ultrasonic-based assistive device for visually impaired individuals. The system provides high accuracy and helps users detect obstacles in their path. However, its performance is affected by noisy environments and external disturbances.

Table 1. Performance comparison of distance sensing technologies.

System architecture	Cost	Ease of implementation	Performance	User experience	Limitations
Ultrasonic-based obstacle	Low	Easy setup	Accurate in short range	Simple and user friendly	Affected by temperature
Arduino-based parking assistance system	Low	Easy	Reliable for short range parking	Real time alerts improve usability	Limited to vehicle parking applications.
Ultrasonic sensor with laser module hybrid approach	Moderate	Moderate	Improved alignment	Better targeting experience	Not suitable for long rang
Ultrasonic based blind assistance devices	Low	Moderate	High accuracy	Helpful for visually impaired users	Reduced performance in noisy environment
Ultrasonic vs LiDAR vs Radar	High	Complex	Very high accuracy	Professional grade systems	Costly hardware.

A comparison of radar systems, LiDAR, and ultrasonic sensors showed that LiDAR and radar offer higher accuracy and longer range but are significantly more expensive. Although limited in range, ultrasonic systems provide a cost-effective solution for short-distance measurements.

From the literature, it is evident that ultrasonic sensor-based systems are widely used because of their affordability and ease of implementation. However, they have limitations, such as a short range and sensitivity to environmental conditions.

Several researchers have explored the use of ultrasonic sensors and embedded systems for distance measurement and object detection. An ultrasonic-based obstacle detection system was developed, which was simple, low-cost, and easy to implement. It provides accurate results for short-range measurements but is affected by environmental conditions such as temperature and humidity [5].

An Arduino-based parking assistance system that uses ultrasonic sensors to detect nearby obstacles. Drivers receive real-time notifications from the system, which enhances its usability and safety. However, its application is limited to vehicle-parking systems [6].

A hybrid system combining ultrasonic sensors with a laser module was developed. This approach improves the alignment and targeting accuracy. Although the system offers better performance, it increases the system complexity and cost, making it less suitable for low-cost applications [7].

An ultrasonic-based assistive device for visually impaired individuals. The system provides high accuracy and helps users detect obstacles in their path. However, their performance is affected by noisy environments and external disturbances [8].

A comparative study of ultrasonic sensors, LiDAR, and radar systems. Their research showed that LiDAR and Radar offer higher accuracy and longer range but are significantly more expensive. Although limited in range, ultrasonic systems provide a cost-effective solution for short-distance measurements [9].

Ultrasonic sensor-based systems are widely used because of their affordability and ease of implementation. However, they have limitations, such as a short range and sensitivity to environmental conditions.

PROPOSED METHODOLOGY

An Arduino Nano served as the core processing unit in the design of the proposed system.

The system integrates multiple components to measure the distance accurately and display the results in real time (Figure 1).

Components Used


- *Arduino Nano*: Acts as the main controller that processes sensor data
- *Ultrasonic Sensor (HC-SR04)*: Measures distance using sound waves
- *LCD Display (16×2)*: Displays real-time distance readings
- *Laser Module*: Provides precise alignment and targeting
- *Power Supply*: A 9V battery ensures portability

Working Principle

High-frequency sound waves or ultrasonic pulses are transmitted towards an object by the ultrasonic sensor. These waves are reflected in the sensor after they strike the object. The Arduino measures the time taken for the echo to return. The following formula was used to determine the distance:

$$\text{Distance} = \frac{\text{Speed of Sound} \times \text{Time}}{2}$$

Block Diagram of Arduino based distance measurement device

**Figure 1.** Block diagram of Arduino based distance measurement device.

The LCD panel displayed the computed distance in real time. The laser module helps in pointing the exact measurement direction, thereby improving the accuracy.

System Features

- Real-time distance measurement
- High accuracy for short-range detection
- Portable and battery-operated system
- Easy to use and user-friendly interface

The system is designed to be simple, cost-effective, and reliable, making it suitable for a variety of applications.

DISCUSSION

The system was tested under different conditions to evaluate its performance. The ultrasonic sensor provided accurate measurements within the range of 2–400 cm. The LCD displayed real-time results with minimal delay. The system performed well in indoor environments under stable conditions. However, owing to ambient conditions such as air pressure and temperature, some variations were noted. A laser module was added to increase the measurement precision by ensuring correct alignment. The system demonstrated reliable performance in short-range applications [10].

The experimental results indicate that the proposed system performs effectively in controlled indoor environments, where external disturbances are minimal. Under these conditions, the ultrasonic sensor produced repeatable and reliable measurements with satisfactory precision. The use of the time-of-flight principle enabled accurate calculation of the distance by measuring the travel time of ultrasonic waves between the sensor and target object. Because the processing requirements are relatively low, the Arduino platform successfully handled the signal acquisition, distance computation, and display functions without noticeable processing overhead [11].

Although the overall system performance was satisfactory, certain environmental factors influenced the measurement accuracy. Variations in the ambient temperature, humidity, and air pressure slightly affected the propagation speed of the ultrasonic waves, leading to minor deviations in the measured distance. In addition, the surface characteristics of the target object play an important role in determining the measurement quality. Smooth and hard surfaces reflected the ultrasonic waves efficiently, resulting in stable readings, whereas soft, irregular, or highly absorbent materials scattered the sound waves, producing occasional fluctuations. Similarly, measurements taken at large incidence angles reduce echo strength and slightly increase measurement uncertainty [12].

The inclusion of a laser module significantly improved the usability of the system by providing an accurate visual alignment between the sensor and target. Although the laser itself does not participate in the distance calculation, it assists users in positioning the sensor correctly, thereby reducing human alignment errors during the experiments. This feature is particularly valuable in laboratory demonstrations, educational activities, and applications requiring repeated measurements at specific locations [13].

The LCD display contributed to the overall effectiveness of the system by instantly presenting the measurement results in a clear and user-friendly format. Real-time visualization allows users to continuously monitor changes without requiring additional software or external computing devices. The combination of Arduino, ultrasonic sensing, LCD display, and laser alignment creates a compact and portable measurement platform that is simple to assemble, inexpensive to maintain, and suitable for rapid prototyping [14].

Compared with conventional manual measuring tools, such as rulers and measuring tapes, the proposed system offers significant advantages in terms of speed, automation, and ease of operation. Unlike manual methods, it enables non-contact distance measurement, making it suitable for applications involving moving objects or locations that are difficult to access. Although technologies such as LiDAR and radar provide superior range and precision, they involve considerably higher hardware costs and increased system complexities. Consequently, Arduino-based ultrasonic systems provide an attractive balance between performance and affordability for short-range measurement applications [15, 16].

The results also suggest that the system can be adapted for a wide range of engineering applications, including robotic obstacle detection, smart parking systems, industrial automation, warehouse monitoring, mobile robots, assistive devices for visually impaired individuals and educational laboratories. The modular design allows additional sensors and communication modules to be integrated without significant hardware modifications, thereby extending the system functionality for emerging smart applications [17, 18].

Despite its advantages, this system has certain limitations. Measuring accuracy decreases under unfavorable environmental conditions, highly reflective or absorbent surfaces, and long-distance operations near the sensor's maximum range. These challenges can be addressed using calibration techniques, digital filtering, temperature compensation, and sensor fusion approaches that combine ultrasonic sensing with infrared, vision-based, or LiDAR technologies [19, 20]. Future developments may also incorporate IoT connectivity, wireless communication, cloud-based monitoring, artificial intelligence algorithms, and autonomous decision-making capabilities to improve system intelligence, adaptability, and operational efficiency. Overall, the experimental evaluation confirmed that the Arduino-based ultrasonic distance measurement system provides a reliable, economical, and practical solution for short-range distance measurement while offering substantial opportunities for further technological enhancement.

CONCLUSION

This review concludes that Arduino-based ultrasonic distance measurement systems provide an effective and affordable solution for short-range distance measurements. Their simplicity, low cost, and versatility make them ideal for academic, civilian, and military applications. These systems provide reliable results at a low cost, making them widely used in educational projects and real-world applications. In many situations, their benefits outweigh their disadvantages, notwithstanding significant limitations. Future enhancements may include integration with the Internet of Things, GPS modules, AI-based object detection, and deployment in autonomous vehicles and drones. These developments will increase the application areas and further enhance the system performance. The analysis also highlights the expectation that ongoing developments in wireless communication, embedded system design, and microcontroller technology will enhance the precision, dependability,

and scalability of ultrasonic distance measuring systems. Real-time data analytics, edge computing, and cloud-based monitoring can be integrated to improve system responsiveness and enable remote monitoring applications. Furthermore, restrictions related to ambient noise, uneven object surfaces, and complicated operating circumstances can be solved by integrating ultrasonic sensing with complementary technologies, such as infrared, vision-based detection, and machine learning techniques. It is anticipated that these hybrid techniques will enhance the capacity of intelligent automation systems for decision-making and measurement accuracy. Overall, Arduino-based ultrasonic distance-measuring devices offer a useful platform for industrial innovation, rapid prototyping, and research.

REFERENCES

1. Manimegalai L, Rose SH, Abinaya B. Enhanced military spying sonar radar system using ultrasonic sensor. In: Proceedings of the 2022 International Conference on Computer Communication and Informatics (ICCCI); 2022 Jan 25-27; Coimbatore, India. IEEE; 2022. p. 1–4. doi:10.1109/ICCCI54379.2022.9740848.
2. Shelke D, Pawar P, Tate P, Shinde P, Mali AS. Obstacle avoiding robot car. *Int J Adv Res Sci Commun Technol*. 2025.
3. Kumar KP, Al-Rubaie YB, Alassedi Z, Bavireddi V, Srikar D, Reddy R. IoT based advanced security system in military for identification of trespassers using ultrasonic radar. In: Proceedings of the 2024 International Conference on Augmented Reality, Intelligent Systems, and Industrial Automation (ARIIA); 2024 Dec 20-21; Manipal, India. IEEE; 2024. p. 1–4. doi:10.1109/ARIIA63345.2024.11051534.
4. Singh S, Arya KV, Rodriguez CR, Mulani AO. Emerging trends in artificial intelligence, data science and signal processing. In: *Communications in Computer and Information Science (CCIS)*. 2025;2439.
5. Hasib A, Bin Zahid SMK, Nishat MR, Rahman SMM, Khan AN, Islam MA. Edge-integrated multi-modal intelligent autonomous vehicle with voice commands and obstacle avoidance using deep learning. In: Proceedings of the 2026 5th International Conference on Electrical, Computer & Telecommunication Engineering (ICECTE); 2026 Jan 29-31; Rajshahi, Bangladesh. IEEE; 2026. doi:10.1109/ICECTE69292.2026.11429330.
6. Pahuriray AV, Cerna PD. IoT-enabled flood monitoring and early warning systems: a systematic review. *Int J Comput Sci Mob Comput*. 2025;14(4):50–67.
7. Swami S, Singh R, Gehlot A, Iqbal MI, Sharma SD, Kumar D, et al. Vision-based approach for human motion detection and smart appliance control. *IAES Int J Robot Autom*. 2024;13(4):445.
8. Ahmed Amin A, Mubarak A, Manzoor HU. Design of intelligent vehicular and sensor communication network: a comprehensive survey. *Syst Sci Control Eng*. 2025;13(1):2529187.
9. Hellas A, Slaoui Hasnaoui F. A security radar system based on the ultrasonic sensor, servo motor, and Raspberry Pi with Kalman filtering. *E3S Web Conf*. 2025;680:00132.
10. Mulani AO, Deshmukh M, Jadhav V, Chaudhari K, Mathew AA, Salunkhe S. Transforming drug therapy with deep learning: the future of personalized medicine. *Drug Res (Stuttg)*. 2025;75(8):326–33.
11. Vijayarani S, Vinupriya M. Performance analysis of Canny and Sobel edge detection algorithms in image mining. *Int J Innov Res Comput Commun Eng*. 2013;1(8):1760-7.
12. Karande KJ, Talbar SN. Face recognition under variation of pose and illumination using independent component analysis. *ICGST J Graph Vis Image Process*. 2008 Dec;8(4):1-6.
13. Patil S, Navale P, Suryawanshi V, Godase SK. Advanced solar tracking and automatic sprinkler irrigation system. *Int J Adv Res Sci Commun Technol*. 2025 Nov. p. 837–56.
14. Modi S, Misal V, Kulkarni S, Mali AS. Hydroponic farming monitoring system—automated system to monitor and control nutrient and pH levels. *J Microcontroller Eng Appl*. 2025;12(3):11–6.
15. Gangonda SS. Bidirectional visitor counter with automatic door lock system. In: *National Conference on Computer, Communication and Information Technology (NCCCIT-2018)*; 2018 Mar 30-31; Korti, Pandharpur, India. Department of Electronics and Telecommunication Engineering, SKN Sinhgad College of Engineering; 2018.

16. Gangonda S, Mukherji P. Speech processing for Marathi numeral recognition using MFCC & DTW features. *Int J Eng Res Appl*. 2012 Mar. p. 118–22.
17. Malik M. Smart vehicle: a systematic review. *Int J Res Publ Rev*. 2019;4(10):2728–31.
18. Dhope V, Chavan A, Hadmode N, Godase V. Smart plant monitoring system. *Int J Creat Res Thoughts*. 2024. Available from: <https://www.ijert.org>
19. Khan MS, Patil R, Haider SA. Application of convolutional neural networks for wildfire detection. In: *Proceedings of the 2020 SoutheastCon*; 2020 Mar 28; Raleigh, NC, USA. IEEE; 2020. p. 1–5. doi:10.1109/SoutheastCon44009.2020.9368283.
20. Pawar V, Phule A, Metkari A, Takale SR. Review of smart energy meter implementations using ESP32 microcontroller and IoT platforms. *Int J Adv Res Sci Commun Technol*. 2025;5(4).